

rinohtype

Release 0.5.1

Contents

7	Chapter 1: Introduction
7	Usage Examples
9	Chapter 2: Installation
9	Dependencies
11	Chapter 3: Quickstart
11	Command-Line Renderer
11	Sphinx Builder
12	High-level PDF Library
15	Chapter 4: Basic Document Styling
15	Style Sheets
17	Document Templates
21	Chapter 5: Element Styling
21	Document Tree
22	Selectors
24	Matchers
24	Style Sheets
27	Style Logs
29	Chapter 6: Document Templates
29	Subclassing a Template
30	Creating a Custom Template
31	Chapter 7: Reference
31	rinoh
32	Sphinx Builder
34	Style Sheets
109	Standard Document Templates
115	Chapter 8: API Documentation
115	Attribute (rinoh.attribute)
115	Color (rinoh.color)

- 116** Dimension (rinoh.dimension)
 - 117** Document (rinoh.document)
 - 118** Drawing Primitives (rinoh.draw)
 - 119** Flowable (rinoh.flowable)
 - 121** Fonts and Typefaces (rinoh.font)
 - 123** Images and Figures (rinoh.image)
 - 124** Index (rinoh.index)
 - 125** Language (rinoh.language)
 - 128** Number (rinoh.number)
 - 129** Paper sizes (rinoh.paper)
 - 129** Paragraph (rinoh.paragraph)
 - 133** Cross-References and Fields (rinoh.reference)
 - 134** Structure (rinoh.structure)
 - 136** Strings (rinoh.strings)
 - 136** Style (rinoh.style)
 - 138** Tables (rinoh.table)
 - 139** Templates (rinoh.template)
- 149** [Chapter 9: Frequently Asked Questions](#)
- 151** [Chapter 10: Contributing](#)
- 151** Contributor License Agreement
 - 151** Coding guidelines
- 153** [Chapter 11: Developing](#)
- 153** Tox Environments
 - 154** Testing against multiple Python interpreter versions
 - 154** Continuous integration
 - 154** Making a release
- 157** [Chapter 12: Release History](#)
- 157** Release 0.5.1 (2021-02-19)
 - 157** Release 0.5.0 (2021-02-03)
 - 159** Release 0.4.2 (2020-07-28)
 - 159** Release 0.4.1 (2020-07-01)
 - 160** Release 0.4.0 (2020-03-05)
 - 161** Release 0.3.1 (2016-12-19)
 - 162** Release 0.3.0 (2016-11-23)
 - 164** Release 0.2.1 (2016-08-18)
 - 164** Release 0.2.0 (2016-08-10)
 - 166** Release 0.1.3 (2015-08-04)
 - 166** Release 0.1.2 (2015-07-31)
 - 166** Release 0.1.1 (2015-04-12)
- 167** [Chapter : Python Module Index](#)

Release v0.5.1. ([Release History](#))

rinohtype is a Python library that transforms a structured document into a professionally typeset PDF guided by a document template and style sheet. It can be used to create any kind of document, but its focus is on complex documents such as technical manuals.

Included with rinohtype is the rinohtype command line tool that renders reStructuredText and Markdown (CommonMark) documents. Support for [DITA](#) is available in the commercially supported Pro version.

rinohtype also includes support for [Sphinx](#), which helps writing large structured documents and supports a multitude of different output formats including searchable HTML. rinohtype adds support to produce PDF output.

Here is a list of rinohtype's main features:

- a powerful page layout system supporting columns, running headers/footers, floatable elements and footnotes
- figures, large tables and automatically generated table of contents
- automatic numbering and cross-referencing of sections, figures and tables
- use one of the highly configurable included document templates or create your own custom template
- the intuitive style sheets make it easy to change the style of individual document elements
- modular design allowing for multiple frontends (such as reStructuredText, Markdown, DocBook, ...) and backends (PDF, SVG, bitmap, ...)
- handles OpenType, TrueType and Type1 fonts with support for advanced typographic features such as kerning, ligatures and small capitals
- embeds PDF, PNG and JPEG images, preserving transparency and color profiles
- easy to deploy; pure-Python with few dependencies
- built on Unicode; ready for non-latin languages

rinohtype is currently in a beta phase. We are working toward a first stable release.

rinohtype is open source software licensed under the [GNU AGPL 3.0](#). Practically, this means you are free to use it in open-source software, but not in (commercial) closed-source software. For the latter, you need to obtain a commercial license. We are also available for consultancy projects involving rinohtype, so don't hesitate to [contact us](#).

rinohype was initially conceived as a modern replacement for [LaTeX](#). An important goal in the design of rinohype is for documents to be much easier to customize than in LaTeX. By today's standards, the arcane TeX macro language upon which LaTeX is built makes customization unnecessarily difficult for one. Simply being built with Python makes rinohype already much easier to approach than TeX. Additionally, rinohype is built around the following core concepts to ensure customizability:

Document Templates These determine the page layout and (for longer documents) the different parts of your document. The templates included with rinohype are highly configurable and allow changing margins, headers, footers, chapter titles, etc. If this is not sufficient, a custom template can be created.

Style Sheets The CSS-inspired style sheets determine the look of individual document elements. A style sheet assigns style attributes to each type of document element. For example, a paragraph's style is determined by the typeface, font weight, size and color, horizontal alignment of text etc.

Structured Input rinohype renders a document from a document tree that does not describe any style aspects but only semantics. The style sheet maps specific style properties to the elements in this document tree. The document tree can be automatically generated from a structured document format such as reStructuredText and CommonMark using one of the included frontends, or it can be constructed manually.

rinohype is implemented as a Python package and doubles as a high-level PDF library. Its modular design makes it easy to customize and extend for specific applications. Moreover, because rinohype's source code is open, all of its internals can be inspected and even modified, making it customizable at all levels.

1.1 Usage Examples

rinohype supports three modes of operation, which are discussed in more detail in the [Quick-start](#) guide. For each of these modes, you can choose to use one of the document templates included with rinohype or a third-party template available from PyPI and optionally customize it to your needs. Or you can create a custom template from scratch. The same is true for the style sheet used to style the document elements.

1.1.1 Command-Line Renderer

rinohype includes the `rinoh` command-line tool which renders structured text documents. Currently, [reStructuredText](#) and [CommonMark](#) documents are supported in the open-source version. Support for [DITA](#) is available in the commercially supported Pro version.

Rendering the reStructuredText demonstration article [demo.txt](#) (using the standard article template and style sheet) generates demo.pdf.

1.1.2 Sphinx Builder

Configuring rinohtype as a builder for Sphinx allows rendering a Sphinx project to PDF without the need for a LaTeX installation. This very document you are reading was rendered using rinohtype's Sphinx builder.

1.1.3 High-level PDF library

rinohtype can also be used as a Python library to generate PDF documents. Just like with rinohtype and the Sphinx builder, you can select which document template and style sheet to use.

Additionally, you need to supply a document tree. This document tree can be parsed from a structured document format such as reStructuredText by using one of the provided frontends or built manually using building blocks provided by rinohtype. You can also write a frontend for a custom format such as an XML dialect.

All of these approaches allow for parts of the content to be fetched from a database or other data sources. When parsing the document tree from a structured document format, a templating engine like [Jinja2](#) can be used.

Todo

sample documents

Installation

2

rinohtype supports Python 3.3 and up. Use [pip](#) to install the latest version of rinohtype and its dependencies:

```
pip install rinohtype
```

If you plan on using rinohtype as an alternative to LaTeX, you will want to install [Sphinx](#) as well:

```
pip install Sphinx
```

See [Sphinx Builder](#) in the [Quickstart](#) guide on how to render Sphinx documents with rinohtype.

2.1 Dependencies

For parsing reStructuredText and CommonMark documents, rinohtype depends on [docutils](#) and [recommonmark](#) respectively. pip takes care of these requirements automatically when you install rinohtype.

If you want to include images other than PDF, PNG or JPEG, you need to install [Pillow](#) additionally.

This section gets you started quickly, discussing each of the three modes of operation introduced in [Introduction](#). If you want to customize the style of the PDF document, please refer to [Basic Document Styling](#) which introduces style sheets and document templates.

3.1 Command-Line Renderer

Installing rinohtype places the rinohtype script in the PATH. This can be used to render structured documents such as [demo.txt \(reStructuredText\)](#):

```
rinoh --format reStructuredText demo.txt
```

After rendering finishes, you will find `demo.pdf` alongside the input file.

rinoh allows specifying the document template and style sheet to use when rendering the `reStructuredText` document. See its [command-line options](#) for details.

Two rendering passes are required to make sure that cross-references to page numbers are correct. After a document has been rendered, rinohtype will save the page reference data to a `.rtc` file. Provided the document (or the template or style sheet) doesn't change a lot, this can prevent the need to perform a second rendering pass.

3.2 Sphinx Builder

If your Sphinx project is already configured for the LaTeX builder, rinohtype will happily interpret `latex_documents`. Otherwise, you need to set the `rinoh_documents` configuration option:

```
rinoh_documents = [dict(doc='index',           # top-level file (index.rst)
                        target='manual')]    # output file (manual.pdf)
```

The dictionary accepts optional keys in addition to the required `doc` and `target` keys. See [Sphinx Builder](#) for details.

When building the documentation, select the rinohtype builder by passing it to the `sphinx-build -b` option:

```
sphinx-build -b rinohtype . _build/rinohtype
```

Note that, just like the rinohtype command line tool, the Sphinx builder requires two [rendering passes](#).

3.3 High-level PDF Library

Note

The focus of rinohtype development is currently on the rinohtype tool and Sphinx builder. Use as a Python library is possible, but documentation may be lacking. Please be patient.

The most basic way to use rinohtype in an application is to hook up an included frontend, a document template and a style sheet:

```
from rinohtype.frontend.rst import ReStructuredTextReader
from rinohtype.templates import Article

# the parser builds a rinohtype document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# render the document to 'my_document.pdf'
document = Article(document_tree)
document.render('my_document')
```

This basic application can be customized to your specific requirements by customizing the document template, the style sheet and the way the document's content tree is built. The basics of document templates and style sheets are covered in later sections.

The document tree returned by the ReStructuredTextReader in the example above can also be built manually. A DocumentTree is simply a list of Flowables, which can have child elements. These children in turn can also have children, and so on; together they form a tree.

Here is an example document tree of a short article:

```
from rinohtype.document import DocumentTree
from rinohtype.style import *

document_tree = DocumentTree(
    [Paragraph('My Document', style='title'), # metadata!
     Section([Heading('First Section'),
              Paragraph('This is a paragraph with some ' +
                        + StyledText('emphasized text',
                                    style='emphasis')
                        + ' and an ' +
                        + InlineImage('image.pdf'))),
              Section([Heading('A subsection'),
                      Paragraph('Another paragraph')])
             ]),
     Section([Heading('Second Section'),
              List([Paragraph('a list item'),
                    Paragraph('another list item')])
             ])
    ])
```

It is clear that this type of content is best parsed from a structured document format such as reStructuredText or XML. Manually building a document tree is well suited for short, custom

documents however.

Basic Document Styling

4

rinohtype allows for fine-grained control over the style of its output. Most aspects of a document's style can be controlled by style sheet files and template configuration files which are being introduced in this chapter. These files are plain text files that are easy to create, read and modify.

4.1 Style Sheets

A style sheet defines the look of each element in a document. For each type of document element, the style sheet assign values to the style properties available for that element. Style sheets are stored in plain text files using the Windows INI¹ format with the .rts extension. Below is an excerpt from the [Sphinx style sheet](#) included with rinohtype.

```
[STYLESHEET]
name=Sphinx
description=Mostly a copy of the LaTeX style included with Sphinx
pygments_style=friendly

[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
fallback_typeface=DejaVu Serif
thin_black_stroke=0.5pt, #000
blue=#20435c

[default:Paragraph]
typeface=$(serif_typeface)
font_weight=REGULAR
font_size=10pt
line_spacing=fixed(12pt, leading(0))
indent_first=0
space_above=0
space_below=0
text_align=JUSTIFY
kerning=True
ligatures=True
hyphen_lang=en_US
hyphen_chars=4

[fallback]
```

1 see Supported INI File Structure in [configparser](#)

```

typeface=$(fallback_typeface)

[body]
base=default
space_above=5pt
space_below=0
text_align=justify

[emphasis]
font_slant=italic

[strong]
font_weight=BOLD

[literal emphasis]
base=emphasis
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[literal strong]
base=strong
typeface=$(mono_typeface)
hyphenate=False
ligatures=False

[inline math]
base=monospaced

[quote]
font_slant=italic

```

Except for [STYLESHEET] and [VARIABLES], each configuration section in a style sheet determines the style of a particular type of document element. The emphasis style, for example, determines the look of emphasized text, which is displayed in an italic font. This is similar to how HTML's cascading style sheets work. In rinohtype however, document elements are identified by means of a descriptive label (such as emphasis) instead of a cryptic selector. rinohtype also makes use of selectors, but these are collected in a [matcher](#) which maps them to descriptive names to be used by many style sheets. Unless you are using rinohtype as a PDF library to create custom documents, the [default matcher](#) should cover your needs.

The following two subsections illustrate how to extend an existing style sheet and how to create a new, independent style sheet. For more in-depth information on style sheets, please refer to [Element Styling](#).

4.1.1 Extending an Existing Style Sheet

Starting from an existing style sheet, it is easy to make small changes to the style of individual document elements. The following style sheet file is based on the Sphinx stylesheet included with rinohtype.

```

[STYLESHEET]
name=My Style Sheet
description=Small tweaks made to the Sphinx style sheet
base=sphinx

[VARIABLES]

```

```

mono_typeface=Courier

[emphasis]
font_color=#00a

[strong]
base=DEFAULT_STYLE
font_color=#a00

```

By default, styles defined in a style sheet extend the corresponding style from the base style sheet. In this example, emphasized text will be set in an italic font (as configured in the [base style sheet](#)) and colored blue (#00a).

It is also possible to completely override a style definition. This can be done by setting the base of a style definition to DEFAULT_STYLE as illustrated by the strong style. This causes strongly emphasised text to be displayed in red (#a00) but not in a bold font as was defined in the [base style sheet](#) (the default for font_weight is Medium; see [TextStyle](#)). Refer to [Default Matcher](#) to find out which style attributes are accepted by each style (by following the hyperlink to the style class's documentation).

The style sheet also redefines the mono_typeface variable. This variable is used in the [base style sheet](#) in all style definitions where a monospaced font is desired. Redefining the variable in the derived style sheet affects all of these style definitions.

4.1.2 Starting from Scratch

If you don't specify a base style sheet in the [STYLESHEET] section, you create an independent style sheet. You should do this if you want to create a document style that is not based on an existing style sheet. If the style definition for a particular document element is not included in the style sheet, the default values for its style properties are used.

Todo

specifying a custom matcher for an INI style sheet

Unless a custom [StyledMatcher](#) is passed to [StyleSheetFile](#), the [default matcher](#) is used. Providing your own matcher offers even more customizability, but it is unlikely you will need this. See [Matchers](#).

Note

In the future, rinohtype will be able to generate an empty INI style sheet, listing all styles defined in the matcher with the supported style attributes along with the default values as comments. This generated style sheet can serve as a good starting point for developing a custom style sheet from scratch.

4.2 Document Templates

As with style sheets, you can choose to make use of a template provided by rinohtype and optionally customize it or you can create a custom template from scratch. This section discusses how you can configure an existing template. See [Document Templates](#) on how to create a custom template.

4.2.1 Configuring a Template

rinohtype provides a number of [Standard Document Templates](#). These can be customized by means of a template configuration file; a plain text file in the INI1 format with the .rtt extension. Here is an example configuration for the article template:

```
[TEMPLATE_CONFIGURATION]
name = my article configuration
template = article

parts =
    title
    ;front_matter
    contents
stylesheet = sphinx_base14
language = fr
abstract_location = title

[SectionTitles]
contents = 'Contents'

[AdmonitionTitles]
caution = 'Careful!'
warning = 'Please be warned'

[VARIABLES]
paper_size = A5

[title]
page_number_format = lowercase roman
end_at_page = left

[contents]
page_number_format = number

[title_page]
top_margin = 2cm
```

The TEMPLATE_CONFIGURATION sections collects global template options. Set name to provide a short label for your template configuration. template identifies the [document template](#) to configure.

All document templates consist of a number of document parts. The [Article](#) template defines three parts: `title`, `front_matter` and `contents`. The order of these parts can be changed (although that makes little sense for the article template), and individual parts can optionally be hidden by setting the `parts` configuration option. The configuration above hides the front matter part (commented out using a semicolon), for example.

The template configuration also specifies which style sheet is used for styling document elements. The `DocumentTemplate.stylesheet` option takes the name of an installed style sheet (see [rinoh --list-stylesheets](#)) or the filename of a stylesheet file (.rts).

The language option sets the default language for the document. It determines which language is used for standard document strings such as section and admonition titles.

The [Article](#) template defines two custom template options. The `abstract_location` option determines where the (optional) article abstract is placed, on the title page or in the front matter part. `table_of_contents` allows hiding the table of contents section. Empty document parts will not be

included in the document. When the table of contents section is suppressed and there is no abstract in the input document or abstract_location is set to title, the front matter document part will not appear in the PDF.

The standard document strings configured by the language option described above can be overridden by user-defined strings in the SectionTitles and AdmonitionTitles sections of the configuration file. For example, the default title for the table of contents section (Table of Contents) is replaced with Contents. The configuration also sets custom titles for the caution and warning admonitions.

The others sections in the configuration file are the VARIABLES section, followed by document part and page template sections. Similar to style sheets, the variables can be referenced in the template configuration sections. Here, the paper_size variable is set, which is being referenced by all page templates in Article (although indirectly through the page base page template).

For document part templates, page_number_format determines how page numbers are formatted. When a document part uses the same page number format as the preceding part, the numbering is continued.

The DocumentPartTemplate.end_at_page option controls at which page the document part ends. This is set to left for the title part in the example configuration to make the contents part start on a right page.

Each document part finds page templates by name. They will first look for specific left/right page templates by appending _left_page or _right_page to the document part name. If these page templates have not been defined in the template, it will look for the more general <document part name>_page template. Note that, if left and right page templates have been defined by the template (such as the book template), the configuration will need to override these, as they will have priority over the general page template defined in the configuration.

The example configuration only adjusts the top margin for the TitlePageTemplate, but many more aspects of the page templates are configurable. Refer to [Standard Document Templates](#) for details.

Todo

base for part template?

4.2.2 Using a Template Configuration File

A template configuration file can be specified when rendering using the command-line rino tool by passing it to the --template command-line option. When using the [Sphinx Builder](#), you can set the rino_template option in conf.py.

To render a document using this template configuration programatically, load the template file using TemplateConfigurationFile:

```
import sys
from pathlib import Path

from rino.frontend.rst import ReStructuredTextReader
from rino.template import TemplateConfigurationFile

# the parser builds a rinohtype document tree
parser = ReStructuredTextReader()
with open('my_document.rst') as file:
    document_tree = parser.parse(file)

# load the article template configuration file
script_path = Path(sys.path[0]).resolve()
```

```
config = TemplateConfigurationFile(script_path / 'my_article.rtt')

# render the document to 'my_document.pdf'
document = config.document(document_tree)
document.render('my_document')
```

The `TemplateConfigurationFile.document()` method creates a `document` instance with the template configuration applied. So if you want to render your document using a different template configuration, it suffices to load the new configuration file.

Refer to the [Article](#) documentation to discover all of the options accepted by it and the document part and page templates.

Element Styling

5

This section describes how styles defined in a style sheet are applied to document elements. Understanding how this works will help you when designing a custom style sheet.

rinohtype's style sheets are heavily inspired by [CSS](#), but add some additional functionality. Similar to CSS, rinohtype makes use of so-called selectors to select document elements in the document tree to style. Unlike CSS however, these selectors are not directly specified in a style sheet. Instead, all selectors are collected in a matcher where they are mapped to descriptive labels for the selected elements. A style sheet assigns style properties to these labels. Besides the usefulness of having these labels instead of the more cryptic selectors, a matcher can be reused by multiple style sheets, avoiding duplication.

Note

This section currently assumes some Python or general object-oriented programming knowledge. A future update will move Python-specific details to another section, making things more accessible for non-programmers.

5.1 Document Tree

A [Flowable](#) is a document element that is placed on a page. It is usually a part of a document tree. Flowables at one level in a document tree are rendered one below the other.

Here is schematic representation of an example document tree:

```
| - Section
|   | - Paragraph
|   \- Paragraph
\ - Section
  | - Paragraph
  | - List
  |   | - ListItem
  |   |   | - Paragraph (item label; a number or bullet symbol)
  |   |   \- StaticGroupedFlowables (item body)
  |   |       | - Paragraph
  |   \- ListItem
  |       | - Paragraph
  |       \- StaticGroupedFlowables
  |           | - List
  |           |   | - ListItem
  |           |   |   | - ...
  |           |   \- ...
  \- Paragraph
```

This represents a document consisting of two sections. The first section contains two paragraphs. The second section contains a paragraph followed by a list and another paragraph. All of the elements in this tree are instances of `Flowable` subclasses.

`Section` and `List` are subclasses of `GroupedFlowables`; they group a number of flowables. In the case of `List`, these are always of the `ListItem` type. Each list item contains an item number (ordered list) or a bullet symbol (unordered list) and an item body. For simple lists, the item body is typically a single `Paragraph`. The second list item contains a nested `List`.

A `Paragraph` does not have any `Flowable` children. It is however the root node of a tree of inline elements. This is an example paragraph in which several text styles are combined:

```
Paragraph
| - SingleStyledText('Text with ')
| - MixedStyledText(style='emphasis')
|   | - SingleStyledText('multiple ')
|   \ - MixedStyledText(style='strong')
|     | - SingleStyledText('nested ')
|     \ - SingleStyledText('styles', style='small caps')
\ - SingleStyledText('.')
.'
```

The visual representation of the words in this paragraph is determined by the applied style sheet. Read more about how this works in the next section.

Besides `SingleStyledText` and `MixedStyledText` elements (subclasses of `StyledText`), paragraphs can also contain `InlineFlowables`. Currently, the only inline flowable is `InlineImage`.

The common superclass for flowable and inline elements is `Styled`, which indicates that these elements can be styled using the style sheets.

5.2 Selectors

Selectors in rinohtype select elements of a particular type. The class of a document element serves as a selector for all instances of the class (and its subclasses). The `Paragraph` class is a selector that matches all paragraphs in the document, for example:

```
Paragraph
```

As with [CSS selectors](#), elements can also be matched based on their context. For example, the following matches any paragraph that is a direct child of a list item or in other words, a list item label:

```
ListItem / Paragraph
```

Python's [ellipsis](#) can be used to match any number of levels of elements in the document tree. The following selector matches paragraphs at any level inside a table cell:

```
TableCell / ... / Paragraph
```

To help avoid duplicating selector definitions, context selectors can reference other selectors defined in the same `matcher` using `SelectorByName`:

```
SelectorByName('definition term') / ... / Paragraph
```

Selectors can select all instances of `Styled` subclasses. These include `Flowable` and `StyledText`, but also `TableSection`, `TableRow`, `Line` and `Shape`. Elements of some of the latter classes only appear as children of other flowables (such as `Table`).

Similar to a HTML element's class attribute, `Styled` elements can have an optional `style` attribute which can be used when constructing a selector. This one selects all styled text elements with

the emphasis style, for example:

```
StyledText.like('emphasis')
```

The Styled.like() method can also match arbitrary attributes of elements by passing them as keyword arguments. This can be used to do more advanced things such as selecting the background objects on all odd rows of a table, limited to the cells not spanning multiple rows:

```
TableCell.like(row_index=slice(0, None, 2), rowspan=1) / TableCellBackground
```

The argument passed as row_index is a slice object that is used for extended indexing². To make this work, TableCell.row_index is an object with a custom __eq__() that allows comparison to a slice.

Rinohtype borrows CSS's concept of [specificity](#) to determine the "winning" selector when multiple selectors match a given document element. Each part of a selector adds to the specificity of a selector. Roughly stated, the more specific selector will win. For example:

```
ListItem / Paragraph # specificity (0, 0, 0, 0, 2)
```

wins over:

```
Paragraph # specificity (0, 0, 0, 0, 1)
```

since it matches two elements instead of just one.

Specificity is represented as a 5-tuple. The last four elements represent the number of location (currently not used), style, attribute and class matches. Here are some selectors along with their specificity:

```
StyledText.like('emphasis') # specificity (0, 0, 1, 0, 1)
TableCell / ... / Paragraph # specificity (0, 0, 0, 0, 2)
TableCell.like(row_index=2, rowspan=1) # specificity (0, 0, 0, 2, 1)
```

Specificity ordering is the same as tuple ordering, so (0, 0, 1, 0, 0) wins over (0, 0, 0, 5, 0) and (0, 0, 0, 0, 3) for example. Only when the number of style matches are equal, the attributes match count is compared and so on.

In practice, the class match count is dependent on the element being matched. If the class of the element exactly matches the selector, the right-most specificity value is increased by 2. If the element's class is a subclass of the selector, it is only increased by 1.

The first element of the specificity tuple is the priority of the selector. For most selectors, the priority will have the default value of 0. The priority of a selector only needs to be set in some cases. For example, we want the CodeBlock selector to match a CodeBlock instance. However, because CodeBlock is a [Paragraph](#) subclass, another selector with a higher specificity will also match it:

```
CodeBlock # specificity (0, 0, 0, 0, 2)
DefinitionList / Definition / Paragraph # specificity (0, 0, 0, 0, 3)
```

To make sure the CodeBlock selector wins, we increase the priority of the CodeBlock selector by prepending it with a + sign:

```
+CodeBlock # specificity (1, 0, 0, 0, 2)
```

In general, you can use multiple + or - signs to adjust the priority:

```
++CodeBlock # specificity (2, 0, 0, 0, 2)
---CodeBlock # specificity (-3, 0, 0, 0, 2)
```

² Indexing a list like this lst[slice(0, None, 2)] is equivalent to lst[0::2].

5.3 Matchers

At the most basic level, a [StyledMatcher](#) is a dictionary that maps labels to selectors:

```
matcher = StyledMatcher()  
...  
matcher['emphasis'] = StyledText.like('emphasis')  
matcher['chapter'] = Section.like(level=1)  
matcher['list item number'] = ListItem / Paragraph  
matcher['nested line block'] = (GroupedFlowables.like('line block')  
                                / GroupedFlowables.like('line block'))  
...
```

Rinohtype currently includes one matcher which defines labels for all common elements in documents:

```
from rinoh.stylesheets import matcher
```

5.4 Style Sheets

A [StyleSheet](#) takes a [StyledMatcher](#) to provide element labels to assign style properties to:

```
styles = StyleSheet('IEEE', matcher=matcher)  
...  
styles['strong'] = TextStyle(font_weight=BOLD)  
styles('emphasis', font_slant=ITALIC)  
styles('nested line block', margin_left=0.5*CM)  
...
```

Each [Styled](#) has a [Style](#) class associated with it. For [Paragraph](#), this is [ParagraphStyle](#). These style classes determine which style attributes are accepted for the styled element. Because the style class can automatically be determined from the selector, it is possible to simply pass the style properties to the style sheet by calling the [StyleSheet](#) instance as shown above.

Style sheets are usually loaded from a .rts file using [StyleSheetFile](#). An example style sheet file is shown in [Style Sheets](#).

A style sheet file contains a number of sections, denoted by a section title enclosed in square brackets. There are two special sections:

- [STYLESHEET] describes global style sheet information (see [StyleSheetFile](#) for details)
- [VARIABLES] collects variables that can be referenced elsewhere in the style sheet

Other sections define the style for a document elements. The section titles correspond to the labels associated with selectors in the [StyledMatcher](#). Each entry in a section sets a value for a style attribute. The style for enumerated lists is defined like this, for example:

```
[enumerated list]  
margin_left=8pt  
space_above=5pt  
space_below=5pt  
ordered=true  
flowable_spacing=5pt  
number_format=NUMBER
```

```
label_suffix='')
```

Since this is an enumerated list, ordered is set to true. number_format and label_suffix are set to produce list items labels of the style 1), 2), Other entries control margins and spacing. See [ListStyle](#) for the full list of accepted style attributes.

Todo

base stylesheets are specified by name ... entry points

5.4.1 Base Styles

It is possible to define styles which are not linked to a selector. These can be useful to collect common attributes in a base style for a set of style definitions. For example, the Sphinx style sheet defines the header_footer style to serve as a base for the header and footer styles:

```
[header_footer : Paragraph]
base=default
typeface=$(sans_typeface)
font_size=10pt
font_weight=BOLD
indent_first=0pt
tab_stops=50% CENTER, 100% RIGHT

[header]
base=header_footer
padding_bottom=2pt
border_bottom=$(thin_black_stroke)
space_below=24pt

[footer]
base=header_footer
padding_top=4pt
border_top=$(thin_black_stroke)
space_above=18pt
```

Because there is no selector associated with header_footer, the element type needs to be specified manually. This is done by adding the name of the relevant [Styled](#) subclass to the section name, using a colon (:) to separate it from the style name, optionally surrounded by spaces.

5.4.2 Custom Selectors

It is also possible to define new selectors directly in a style sheet file. This allows making tweaks to an existing style sheet without having to create a new [StyledMatcher](#). However, this should be used sparingly. If a great number of custom selectors are required, it is better to create a new [StyledMatcher](#)

The syntax for specifying a selector for a style is similar to that when constructing selectors in a Python source code (see [Matchers](#)), but with a number of important differences. A [Styled](#) subclass name followed by parentheses represents a simple class selector (without context). Arguments to be passed to [Styled.like\(\)](#) can be included within the parentheses.

```
[special_text : StyledText('special')]
font_color=#FF00FF

[accept_button : InlineImage(filename='images/ok_button.png')]
```

```
baseline=20%
```

Even if no arguments are passed to the class selector, it is important that the class name is followed by parentheses. If the parentheses are omitted, the selector is not registered with the matcher and the style can only be used as a base style for other style definitions (see [Base Styles](#)).

As in Python source code, context selectors are constructed using forward slashes (/) and the ellipsis (...). Another selector can be referenced in a context selector by enclosing its name in single or double quotes.

```
[admonition title colon : Admonition / ... / StyledText('colon')]
font_size=10pt

[chapter title : LabeledFlowable('chapter title')]
label_spacing=1cm
align_baselines=false

[chapter title number : 'chapter title' / Paragraph('number')]
font_size=96pt
text_align=right
```

5.4.3 Variables

Variables can be used for values that are used in multiple style definitions. This example declares a number of typefaces to allow easily replacing the fonts in a style sheet:

```
[VARIABLES]
mono_typeface=TeX Gyre Cursor
serif_typeface=TeX Gyre Pagella
sans_typeface=TeX Gyre Heros
thin_black_stroke=0.5pt, #000
blue=#20435c
```

It also defines the thin_black_stroke line style for use in table and frame styles, and a specific color labelled blue. These variables can be referenced in style definitions as follows:

```
[code block]
typeface=$(mono_typeface)
font_size=9pt
text_align=LEFT
indent_first=0
space_above=6pt
space_below=4pt
border=$(thin_black_stroke)
padding_left=5pt
padding_top=1pt
padding_bottom=3pt
```

Another stylesheet can inherit (see below) from this one and easily replace fonts in the document by overriding the variables.

5.4.4 Style Attribute Resolution

The style system makes a distinction between text (inline) elements and flowables with respect to how attribute values are resolved.

Text elements by default inherit the properties from their parent. Take for example the emphasis style definition from the example above. The value for style properties other than font_slant

(which is defined in the emphasis style itself) will be looked up in the style definition corresponding to the parent element, which can be either another `StyledText` instance, or a `Paragraph`. If the parent element is a `StyledText` that neither defines the style attribute, lookup proceeds recursively, moving up in the document tree.

For flowables, there is no fall-back to the parent's style by default. A base style can be specified explicitly however. If a style attribute is not present in a particular style definition, it is looked up in the base style. This can help avoid duplication of style information and the resulting maintenance difficulties. In the following example, the unnumbered heading level 1 style inherits all properties from heading level 1, overriding only the `number_format` attribute:

```
[heading level 1]
typeface=$(sans_typeface)
font_weight=BOLD
font_size=16pt
font_color=$(blue)
line_spacing=SINGLE
space_above=18pt
space_below=12pt
number_format=NUMBER
label_suffix=' '


[unnumbered heading level 1]
base=heading level 1
number_format=None
```

When a value for a particular style attribute is set nowhere in the style definition lookup hierarchy, its default value is returned. The default values for all style properties are defined in the class definition for each of the `Style` subclasses.

For text elements, it is possible to override the default behavior of falling back to the parent's style. Setting `base` to the label of a `TextStyle` or `ParagraphStyle` prevents fallback to the parent element's style.

For flowables, `base` can be set to `PARENT_STYLE` to enable fallback, but this requires that the current element type is the same or a subclass of the parent type, so it cannot be used for all styles.

5.5 Style Logs

When rendering a document, `rinohtype` will create a style log. It is written to disk using the same base name as the output file, but with a `.stylelog` extension. The information logged in the style log is invaluable when debugging your style sheet. It tells you which style maps to each element in the document.

The style log lists the document elements (as a tree) that have been rendered to each page, and for each element all matching styles are listed together with their specificity. No styles are listed when there aren't any selectors matching an element and the default values are used. The winning style is indicated with a `>` symbol. Styles that are not defined in the style sheet or its base(s) are marked with an `x`. If none of the styles are defined, `rinohtype` falls back to using the default style.

Here is an example excerpt from a style log:

```
...
Paragraph('January 03, 2012', style='title page date')
    > (0,0,1,0,2) title page date
        (0,0,0,0,2) body
SingleStyledText('January 03, 2012')
```

```

----- page 3 -----
#### ChainedContainer('column1')
DocumentTree()
    Section(id='structural-elements')                               demo.txt:62 <section>
        > (0,0,0,1,2) chapter
    Heading('1 Structural Elements')                            demo.txt:62 <title>
        > (0,0,0,1,2) heading level 1
        (0,0,0,0,2) other heading levels
    MixedStyledText('1 Structural Elements')
        SingleStyledText('1')
        MixedStyledText(' ')
            SingleStyledText(' ')
        SingleStyledText('Structural Elements')
    Paragraph('A paragraph.')                                     demo.txt:64 <paragraph>
        > (0,0,0,0,2) body
        MixedStyledText('A paragraph.')
            SingleStyledText('A paragraph.')
    List(style='bulleted')                                       demo.txt:66 <bullet_list>
        > (0,0,1,0,2) bulleted list
    ListItem()
        x (0,0,1,0,4) bulleted list item
        > fallback to default style
    ListItemLabel('•')
        > (0,0,1,0,6) bulleted list item label
        (0,0,0,0,2) list item label
    MixedStyledText('•')
        SingleStyledText(' ')
        SingleStyledText('•')
    StaticGroupedFlowables()                                    demo.txt:66 <list_item>
        > (0,0,0,0,3) list item body
...

```

Document Templates

6

When it is not possible to achieve a particular document style using one of the existing templates and a custom template configuration, you can create a new template. A new template is programmed in Python and therefore it is required that you are familiar with Python, or at least with general object-oriented programming.

6.1 Subclassing a Template

If you need to customize a template beyond what is possible by configuration, you can subclass a template class and override document part and page templates with custom templates. The following example subclasses `Article`.

```
from rinoh.attribute import OverrideDefault
from rinoh.template import DocumentPartTemplate, PageTemplate
from rinoh.templates import Article

class BibliographyPartTemplate(DocumentPartTemplate):
    ...

class MyTitlePageTemplate(PageTemplate):
    ...

class MyArticle(Article):
    parts = OverrideDefault(['title', 'contents', 'bibliography'])

    # default document part templates
    bibliography = BibliographyPartTemplate()

    # default page templates
    title_page = MyTitlePageTemplate(base='page')
    bibliography_page = PageTemplate(base='page')
```

`MyArticle` extends the `Article` template, adding the extra `bibliography` document part, along with the page template `bibliography_page`. The new document part is included in `parts`, while also leaving out `front_matter` by default. Finally, the template also replaces the title page template with a custom one.

6.2 Creating a Custom Template

A new template can be created from scratch by subclassing [DocumentTemplate](#), defining all document parts, their templates and page templates.

The [Article](#) and [Book](#) templates are examples of templates that inherit directly from [DocumentTemplate](#). We will briefly discuss the article template. The [Article](#) template overrides the default style sheet and defines the two custom template attributes discussed in [Configuring a Template](#). The document parts [title](#), [front_matter](#) and [contents](#) are listed in the [parts](#) attribute and part templates for each are provided along with page templates:

```
class Article(DocumentTemplate):
    stylesheet = OverrideDefault(sphinx_article)
    table_of_contents = Attribute(Bool, True,
                                  'Show or hide the table of contents')
    abstract_location = Attribute(AbstractLocation, 'front matter',
                                   'Where to place the abstract')

    parts = OverrideDefault(['title', 'front_matter', 'contents'])

    # default document part templates
    title = TitlePartTemplate()
    front_matter = ArticleFrontMatter()
    contents = ContentsPartTemplate()

    # default page templates
    page = PageTemplate(page_size=Var('paper_size'))
    title_page = TitlePageTemplate(base='page',
                                   top_margin=8*CM)
    front_matter_page = PageTemplate(base='page')
    contents_page = PageTemplate(base='page')
```

The custom [ArticleFrontMatter](#) template reads the values for the two custom template attributes defined in [Article](#) to determine which flowables are included in the front matter:

```
class ArticleFrontMatter(DocumentPartTemplate):
    toc_section = TableOfContentsSection()

    def _flowables(self, document):
        meta = document.metadata
        abstract_loc = document.get_option('abstract_location')
        if ('abstract' in meta
            and abstract_loc == AbstractLocation.FRONT_MATTER):
            yield meta['abstract']
        if document.get_option('table_of_contents'):
            yield self.toc_section
```

Have a look at the [Book template source code](#) for an example of a slightly more complex template that defines separate templates for left and right pages.

7.1 rinoh

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME or FILENAME]
              [-s NAME or FILENAME] [-O FILENAME or DIRECTORY] [-p PAPER] [-i]
              [--list-templates] [--list-stylesheets] [--list-fonts
              [FILENAME]] [--list-formats] [--list-options FRONTEND] [--version] [--docs]
              [input]
```

input the document to render

-h, --help show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-O <filename or directory>, --output <filename or directory>

write the PDF output to FILENAME or to an existing DIRECTORY with a filename derived from the input filename (default: the current working directory)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

-i, --install-resources

automatically install missing resources (fonts, templates, style sheets) from PyPI

--list-templates list the installed document templates and exit

--list-stylesheets list the installed style sheets and exit

```
--list-fonts <filename>
    list the installed fonts or, if FILENAME is given, write a PDF file displaying
    all the fonts
--list-formats list the supported input formats and exit
--list-options <frontend>
    list the options supported by the given frontend and exit
--version show program's version number and exit
--docs open the online documentation in the default browser
```

7.2 Sphinx Builder

`rinoh.frontend.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name `rinoh`. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required.

`rinoh_documents` Determines which PDF documents to build. Its format is a list of dictionaries, one for each document to be generated. The supported keys for these dictionaries are listed below. Two of them are required:

doc (required) String that specifies the name of the master document (typically `index`).

target (required) The name of the target PDF file without the extension.

The following keys allow overriding the content included on the document's title page and page headers/footers (depending on the template and its configuration). The values for text content can be plain text or `StyledText`.

logo (no default) Path (absolute or relative to the location of the `conf.py` file) to an image file, typically included on the title page.

title (default: “`project documentation`”) The title of the document.

subtitle (default: “`Release release`”) Subtitle of the document.

author (default: “`author`”) The document's author.

date (default: determined from `today` and `today_fmt`) The document (build) date.

The remaining keys control what is included in the document and the document template (configuration) to use.

toctree_only (default: False) Must be True or False. If true, the document itself is not included in the output, only the documents referenced by it via TOC trees.

domain_indices (default: True) If true, generate domain-specific indices in addition to the general index. It is equivalent to the `html_domain_indices` and `latex_domain_indices` configuration variables.

template (default: `Book`) Determines the template used to render the document. It takes:

- the filename of a `Template configuration file`,
- a `TemplateConfiguration` instance,
- the name of an installed template (see `rinoh-list-templates`), or

- a [DocumentTemplate](#) subclass

`rinoh_documents` will also accept other keys than those listed above. These items will be available as document metadata and can be used in a [custom document template](#).

Example:

```
rinoh_documents = [
    dict(doc='index', target='manual', toctree_only=False,
         template='manual.rtt', logo='logo.pdf'),
    dict(doc='ref', target='reference', title='Reference
Manual',
         template='reference.rtt', stamp='DRAFT'),
]
```

7.2.1 Legacy Configuration Variables

The configuration variables below are no longer supported. Instead, their functionality can now be configured per document in `rinoh_documents`.

`rinoh_template` This configuration variable is no longer supported since the document template can be specified in `rinoh_documents` entries.

`rinoh_stylesheet` This configuration variable is no longer supported since it is not obvious which style sheet will be used when the template configuration also specifies a style sheet. Please specify the style sheet to use in your [template configuration file](#):

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book
stylesheet = my_stylesheet.rts
```

`rinoh_paper_size` This configuration variable is no longer supported since it was not obvious which paper size was being used when the template configuration (`rinoh_template`) also specified a paper size. Please specify the `paper_size` to use in your [template configuration file](#):

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book

[VARIABLES]
paper_size = A5
```

`rinoh_logo` This configuration variable is no longer supported since the logo can be specified in the `rinoh_documents` entries.

`rinoh_domain_indices`

This configuration variable is no longer supported since the `domain_indices` can be specified in the `rinoh_documents` entries.

`rinoh_metadata` This configuration variable is no longer supported. Metadata entries can now be added to `rinoh_documents` entries.

7.3 Style Sheets

7.3.1 Included Style Sheets

These style sheets are included with rinohtype:

`rinohtypesheets.sphinx`

Mostly a copy of the LaTeX style included with Sphinx

Entry point name: `sphinx`

`rinohtypesheets.sphinx_article`

The Sphinx stylesheet adjusted for the article template

Entry point name: `sphinx_article`

`rinohtypesheets.sphinx_base14`

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)

Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinohtype --list-stylesheets`.

7.3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

`rinohtypesheets.matcher`

The default matcher defines the following styles

- title page rule: `HorizontalRuleStyle`
- title page logo: `FlowableStyle`
- title page title: `ParagraphStyle`
- title page subtitle: `ParagraphStyle`
- title page author: `ParagraphStyle`
- title page date: `ParagraphStyle`
- title page extra: `ParagraphStyle`
- front matter section title: `ParagraphStyle`
- body matter chapter label: `ParagraphStyle`
- body matter chapter number: `TextStyle`
- body matter chapter title: `ParagraphStyle`
- fallback: `TextStyle`
- italic: `TextStyle`

- bold: `TextStyle`
- monospaced: `TextStyle`
- emphasis: `TextStyle`
- strong: `TextStyle`
- literal emphasis: `TextStyle`
- literal strong: `TextStyle`
- inline math: `TextStyle`
- quote: `TextStyle`
- file path: `TextStyle`
- keystrokes: `TextStyle`
- regular expression: `TextStyle`
- code with variable: `TextStyle`
- mail header: `TextStyle`
- MIME type: `TextStyle`
- newsgroup: `TextStyle`
- command: `TextStyle`
- make variable: `TextStyle`
- program: `TextStyle`
- man page: `TextStyle`
- window title: `TextStyle`
- UI control: `TextStyle`
- UI control accelerator: `TextStyle`
- menu cascade: `TextStyle`
- draft comment: `TextStyle`
- title reference: `TextStyle`
- error: `TextStyle`
- linked reference: `TextStyle`
- unlinked reference: `TextStyle`
- internal hyperlink: `TextStyle`
- external hyperlink: `TextStyle`
- broken hyperlink: `TextStyle`
- glossary inline definition: `TextStyle`

- body: [ParagraphStyle](#)
- code block: [ParagraphStyle](#)
- code block caption: [CaptionStyle](#)
- math block: [ParagraphStyle](#)
- attribution: [ParagraphStyle](#)
- centered: [ParagraphStyle](#)
- line block: [ParagraphStyle](#)
- block quote: [GroupedFlowablesStyle](#)
- chapter: [SectionStyle](#)
- heading level 1: [HeadingStyle](#)
- unnumbered heading level 1: [HeadingStyle](#)
- heading level 2: [HeadingStyle](#)
- unnumbered heading level 2: [HeadingStyle](#)
- heading level 3: [HeadingStyle](#)
- unnumbered heading level 3: [HeadingStyle](#)
- heading level 4: [HeadingStyle](#)
- unnumbered heading level 4: [HeadingStyle](#)
- heading level 5: [HeadingStyle](#)
- unnumbered heading level 5: [HeadingStyle](#)
- other heading levels: [HeadingStyle](#)
- appendix: [SectionStyle](#)
- appendix heading level 1: [HeadingStyle](#)
- appendix heading level 2: [HeadingStyle](#)
- appendix heading level 3: [HeadingStyle](#)
- appendix heading level 4: [HeadingStyle](#)
- appendix heading level 5: [HeadingStyle](#)
- title: [ParagraphStyle](#)
- prerequisites: [GroupedFlowablesStyle](#)
- prerequisites title: [ParagraphStyle](#)
- post requirement: [GroupedFlowablesStyle](#)
- abstract: [GroupedFlowablesStyle](#)
- abstract paragraph: [ParagraphStyle](#)

- example: `GroupedFlowablesStyle`
- example title: `ParagraphStyle`
- topic: `GroupedFlowablesStyle`
- topic title: `ParagraphStyle`
- rubric: `ParagraphStyle`
- sidebar: `GroupedFlowablesStyle`
- sidebar title: `ParagraphStyle`
- sidebar subtitle: `ParagraphStyle`
- list item label: `ListLabelStyle`
- list item body: `GroupedFlowablesStyle`
- list item paragraph: `ParagraphStyle`
- enumerated list: `ListStyle`
- enumerated list item: `LabeledFlowableStyle`
- enumerated list item label: `ListLabelStyle`
- nested enumerated list: `ListStyle`
- (table) enumerated list: `ListStyle`
- (table) enumerated list item: `LabeledFlowableStyle`
- (table) enumerated list item label: `ListLabelStyle`
- bulleted list: `ListStyle`
- compact bulleted list: `ListStyle`
- bulleted list item: `LabeledFlowableStyle`
- bulleted list item label: `ListLabelStyle`
- nested bulleted list: `ListStyle`
- (table) bulleted list: `ListStyle`
- (table) bulleted list item: `LabeledFlowableStyle`
- (table) bulleted list item label: `ListLabelStyle`
- steps list: `ListStyle`
- steps list title: `ParagraphStyle`
- steps list item: `LabeledFlowableStyle`
- steps list item label: `ListLabelStyle`
- unordered steps list: `ListStyle`
- unordered steps list title: `ParagraphStyle`

- unordered steps list item: `LabeledFlowableStyle`
- unordered steps list item label: `ListItemLabelStyle`
- choices list: `ListStyle`
- choices list item: `LabeledFlowableStyle`
- choices list item label: `ListItemLabelStyle`
- definition list: `GroupedFlowablesStyle`
- definition list item: `LabeledFlowableStyle`
- definition term: `GroupedFlowablesStyle`
- definition term paragraph: `ParagraphStyle`
- definition term classifier: `TextStyle`
- definition: `GroupedFlowablesStyle`
- definition paragraph: `ParagraphStyle`
- related links: `GroupedFlowablesStyle`
- related links section title: `ParagraphStyle`
- related links list: `ListStyle`
- related links list item: `LabeledFlowableStyle`
- related links list item label: `ListItemLabelStyle`
- related links list item paragraph: `ReferencingParagraphStyle`
- related link title reference: `TextStyle`
- related link page reference: `TextStyle`
- related link number reference: `TextStyle`
- related link reference: `TextStyle`
- versionmodified: `TextStyle`
- object description: `LabeledFlowableStyle`
- object signatures: `GroupedFlowablesStyle`
- object signature: `ParagraphStyle`
- object name: `TextStyle`
- additional name part: `TextStyle`
- object type: `TextStyle`
- object returns: `TextStyle`
- object parentheses: `TextStyle`
- object parameter list: `TextStyle`

- object parameter: `TextStyle`
- object parameter (no emphasis): `TextStyle`
- object brackets: `TextStyle`
- object optional parameter: `TextStyle`
- object annotation: `TextStyle`
- object description content: `GroupedFlowablesStyle`
- object description content paragraph: `ParagraphStyle`
- production list: `GroupedFlowablesStyle`
- production: `LabeledFlowableStyle`
- token name: `ParagraphStyle`
- token definition: `ParagraphStyle`
- field list: `GroupedFlowablesStyle`
- field list item: `LabeledFlowableStyle`
- field name: `ParagraphStyle`
- option list: `GroupedFlowablesStyle`
- option list item: `LabeledFlowableStyle`
- option: `ParagraphStyle`
- option string: `TextStyle`
- option argument: `TextStyle`
- admonition: `AdmonitionStyle`
- admonition title: `ParagraphStyle`
- admonition inline title: `TextStyle`
- attention admonition: `AdmonitionStyle`
- attention admonition title: `ParagraphStyle`
- attention admonition inline title: `TextStyle`
- caution admonition: `AdmonitionStyle`
- caution admonition title: `ParagraphStyle`
- caution admonition inline title: `TextStyle`
- danger admonition: `AdmonitionStyle`
- danger admonition title: `ParagraphStyle`
- danger admonition inline title: `TextStyle`
- error admonition: `AdmonitionStyle`

- error admonition title: [ParagraphStyle](#)
- error admonition inline title: [TextStyle](#)
- hint admonition: [AdmonitionStyle](#)
- hint admonition title: [ParagraphStyle](#)
- hint admonition inline title: [TextStyle](#)
- important admonition: [AdmonitionStyle](#)
- important admonition title: [ParagraphStyle](#)
- important admonition inline title: [TextStyle](#)
- note admonition: [AdmonitionStyle](#)
- note admonition title: [ParagraphStyle](#)
- note admonition inline title: [TextStyle](#)
- tip admonition: [AdmonitionStyle](#)
- tip admonition title: [ParagraphStyle](#)
- tip admonition inline title: [TextStyle](#)
- warning admonition: [AdmonitionStyle](#)
- warning admonition title: [ParagraphStyle](#)
- warning admonition inline title: [TextStyle](#)
- seealso admonition: [AdmonitionStyle](#)
- seealso admonition title: [ParagraphStyle](#)
- seealso admonition inline title: [TextStyle](#)
- header: [ParagraphStyle](#)
- footer: [ParagraphStyle](#)
- footnote marker: [NoteMarkerStyle](#)
- citation marker: [NoteMarkerStyle](#)
- footnote paragraph: [ParagraphStyle](#)
- footnote label: [ParagraphStyle](#)
- image: [FlowableStyle](#)
- inline image: [InlineFlowableStyle](#)
- figure: [FigureStyle](#)
- figure image: [FlowableStyle](#)
- figure caption: [CaptionStyle](#)
- figure legend: [GroupedFlowablesStyle](#)

- figure legend paragraph: [ParagraphStyle](#)
- table of contents section: [SectionStyle](#)
- table of contents title: [HeadingStyle](#)
- table of contents: [TableOfContentsStyle](#)
- local table of contents: [TableOfContentsStyle](#)
- toc level 1: [TableOfContentsEntryStyle](#)
- toc level 2: [TableOfContentsEntryStyle](#)
- toc level 3: [TableOfContentsEntryStyle](#)
- L3 toc level 3: [TableOfContentsEntryStyle](#)
- toc linked reference: [TextStyle](#)
- list of figures section: [SectionStyle](#)
- list of figures: [ListOfType](#)
- list of figures entry: [ListOfType](#)
- list of tables section: [SectionStyle](#)
- list of tables: [ListOfType](#)
- list of tables entry: [ListOfType](#)
- table: [TableStyle](#)
- table with caption: [TableWithCaptionStyle](#)
- table caption: [CaptionStyle](#)
- choices table: [TableStyle](#)
- table cell: [TableCellStyle](#)
- table body cell background on even row: [TableCellBackgroundStyle](#)
- table body cell background on odd row: [TableCellBackgroundStyle](#)
- table body cell paragraph: [ParagraphStyle](#)
- table first column paragraph: [ParagraphStyle](#)
- table body cell list item number: [ParagraphStyle](#)
- table head cell: [TableCellStyle](#)
- table head cell paragraph: [ParagraphStyle](#)
- table cell left border: [TableCellBorderStyle](#)
- table cell top border: [TableCellBorderStyle](#)
- table cell right border: [TableCellBorderStyle](#)
- table cell bottom border: [TableCellBorderStyle](#)

- table top border: [TableCellBorderStyle](#)
- table bottom border: [TableCellBorderStyle](#)
- table left border: [TableCellBorderStyle](#)
- table right border: [TableCellBorderStyle](#)
- table head cell left border: [TableCellBorderStyle](#)
- table head cell right border: [TableCellBorderStyle](#)
- table head bottom border: [TableCellBorderStyle](#)
- table head left border: [TableCellBorderStyle](#)
- table head right border: [TableCellBorderStyle](#)
- table body top border: [TableCellBorderStyle](#)
- table body left border: [TableCellBorderStyle](#)
- table body right border: [TableCellBorderStyle](#)
- horizontal rule: [HorizontalRuleStyle](#)
- index: [IndexStyle](#)
- index section label: [ParagraphStyle](#)
- level 1 index entry: [ParagraphStyle](#)
- level 2 index entry: [ParagraphStyle](#)
- level 3 index entry: [ParagraphStyle](#)
- level 4 index entry: [ParagraphStyle](#)
- domain index entry name: [TextStyle](#)

7.3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

draw.LineStyle	Style class for Line
draw.ShapeStyle	Style class for Shape
flowable.FlowableStyle	Style class for Flowable
flowable.LabeledFlowableStyle	Style class for LabeledFlowable
flowable.GroupedFlowablesStyle	Style class for GroupedFlowables
flowable.FloatStyle	Style class for Float
image.CaptionStyle	Style class for Caption
image.FigureStyle	Style class for Figure
index.IndexStyle	Style class for Index
paragraph.ParagraphStyle	Style class for Paragraph
text.TextStyle	Style class for Text

inline.InlineFlowableStyle	Style class for InlineFlowable
reference.ReferencingParagraphStyle	Style class for ReferencingParagraph
reference.NoteMarkerStyle	Style class for NoteMarker
structure.SectionStyle	Style class for Section
structure.HeadingStyle	Style class for Heading
structure.ListStyle	Style class for List
structure.ListItemLabelStyle	Style class for ListItemLabel
structure.TableOfContentsStyle	Style class for TableOfContents
structure.TableOfContentsEntryStyle	Style class for TableOfContentsEntry
structure.AdmonitionStyle	Style class for Admonition
structure.HorizontalRuleStyle	Style class for HorizontalRule
table.TableStyle	Style class for Table
table.TableCellStyle	Style class for TableCell
table.TableCellBorderStyle	Style class for TableCellBorder
table.TableCellBackgroundColor	Style class for TableCellBackground

LineStyle

```
class rino.draw.LineStyle ( base=None, **attributes )
    Style class for Line
    stroke Width and color used to draw the line
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke,
        separated by a comma (,)
        Default: 1pt, #000
    hide Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

ShapeStyle

```
class rino.draw.ShapeStyle ( base=None, **attributes )
    Style class for Shape
    fill_color Color to fill the shape
        Accepts Color: HEX string with optional alpha component
        (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
        Default: #e5e5e5
    stroke Width and color used to draw the line (inherited from LineStyle)
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke,
        separated by a comma (,)
        Default: 1pt, #000
    hide Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

FlowableStyle

```
class rino.flowable.FlowableStyle ( base=None, **attributes )
    Style class for Flowable
```

width Width to render the flowable at

Accepts **FlowableWidth**: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable

Accepts **HorizontalAlignment**: left, right, center

Default: left

space_above Vertical space preceding the flowable

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page

Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_bottom` Border below the flowable
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`background_color`
 Color of the area within the flowable's borders
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable
 Accepts [Break](#): none, any, left, right
 Default: None

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for [LabeledFlowable](#)

`label_min_width` Minimum label width
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 12pt

`label_max_width` Maximum label width
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 80pt
label_spacing Spacing between a label and the labeled flowable
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 3pt
align_baselines Line up the baselines of the label and the labeled flowable
 Accepts [Bool](#): true or false
 Default: true
wrap_label Wrap the label at **label_max_width**
 Accepts [Bool](#): true or false
 Default: false
width Width to render the flowable at (inherited from [FlowableStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: auto
horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left
space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable

(inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts Bool: true or false

Default: false

GroupedFlowablesStyle

class rino.h.flowable.GroupedFlowablesStyle (base=None, **attributes)

Style class for [GroupedFlowables](#)

width Overrides the default set in [FlowableStyle](#)

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title Title to precede the flowables

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`background_color`

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

`hide` Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

[FloatStyle](#)

`class rino.h.flowable.FloatStyle (base=None, **attributes)`

Style class for [Float](#)

`float` Float the flowable to the top or bottom of the page

Accepts [Bool](#): true or false

Default: false

`width` Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

`horizontal_align` Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

`space_above` Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`space_below` Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`margin_left` Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

CaptionStyle

```
class rino.h.image.CaptionStyle ( base=None, **attributes )
```

Style class for [Caption](#)

number_format Overrides the default set in [ParagraphStyle](#)

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

numbering_level Overrides the default set in [ParagraphStyle](#)

Accepts [Integer](#): a natural number (positive integer)

Default: 1

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from [ParagraphStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ''

horizontal_align

Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts **Bool**: true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
 Accepts [Bool](#): true or false
 Default: false

typeface Typeface to set the text in (inherited from [TextStyle](#))
 Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fs](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
 Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))
 Accepts [FontSlant](#): upright, oblique, italic
 Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

FigureStyle

```
class rinoх.image.FigureStyle ( base=None, **attributes )
```

Style class for [Figure](#)

float Float the flowable to the top or bottom of the page (inherited from [FloatStyle](#))
 Accepts [Bool](#): true or false
 Default: false

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`background_color`
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

`title` Title to precede the flowables (inherited from [GroupedFlowableStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

`flowable_spacing` Spacing between flowables (inherited from

[GroupedFlowablesStyle](#)

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

IndexStyle

class rinoх.index.IndexStyle (base=None, **attributes)

Style class for [Index](#)

initials Group index entries based on their first letter

Accepts [Bool](#): true or false

Default: true

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of

the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts Bool: true or false
 Default: false

ParagraphStyle

```
class rinoх.paragraph.ParagraphStyle ( base=None, **attributes )
```

Style class for [Paragraph](#)

width Overrides the default set in [FlowableStyle](#)
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

indent_first Indentation of the first line of text
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text
 Accepts [LineSpacing](#): a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align Alignment of text to the margins
 Accepts [TextAlign](#): left, right, center, justify
 Default: justify

tab_stops List of tab positions
 Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

number_format Overrides the default set in [NumberStyle](#)
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

	Default: None
number_separator	Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label.
	Accepts StyledText : a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
	Default: ''
numbering_level	At which section level to restart numbering (positive: absolute, negative: relative)
	Accepts Integer : a natural number (positive integer)
	Default: (no value)
horizontal_align	Horizontal alignment of the flowable (inherited from FlowableStyle)
	Accepts HorizontalAlignment : left, right, center
	Default: left
space_above	Vertical space preceding the flowable (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
space_below	Vertical space following the flowable (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
margin_left	Left margin (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
margin_right	Right margin (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
padding	Padding (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
padding_left	Left padding (inherited from FlowableStyle)
	Accepts Dimension : a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
	Default: 0
padding_right	Right padding (inherited from FlowableStyle)

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))

Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts **Bool**: true or false

Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width (**Dimension**) and color (**Color**) of the stroke, separated by a comma (,)

Default: none

`background_color`

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
 Accepts [Bool](#): true or false
 Default: false

typeface Typeface to set the text in (inherited from [TextStyle](#))
 Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fОНts](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
 Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))
 Accepts [FontSlant](#): upright, oblique, italic
 Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

[TextStyle](#)

```
class rinoх.text.TextStyle ( base=None, **attributes )
```

Style class for Text

typeface Typeface to set the text in
 Accepts [Typeface](#): the name of a typeface. See [rinoх --list-fonTs](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height

Accepts **FontWeight**: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font
 Accepts **FontSlant**: upright, oblique, italic
 Default: upright

font_width Stretch of the characters
 Accepts **FontWidth**: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt

font_color Color of the font
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font
 Accepts **FontVariant**: normal, small capital, oldstyle figures
 Default: normal

position Vertical text position
 Accepts **TextPosition**: normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing
 Accepts **Bool**: true or false
 Default: true

ligatures Run letters together where possible
 Accepts **Bool**: true or false
 Default: true

hyphenate Allow words to be broken over two lines
 Accepts **Bool**: true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word
 Accepts **Integer**: a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US'
 Accepts **Locale**: locale identifier in the <language ID>_<region ID> format

Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

InlineFlowableStyle

class rinoх.inline.[InlineFlowableStyle](#) (base=None, **attributes)

Style class for [InlineFlowable](#)

baseline The location of the flowable's baseline relative to the bottom edge

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts **Stroke**: the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts **Color**: HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts **Break**: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts **Bool**: true or false
 Default: false

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts **StyledText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

ReferencingParagraphStyle

```
class rinoх.reference.ReferencingParagraphStyle ( base=None, **attributes )
```

Style class for [ReferencingParagraph](#)

text The text content of this paragraph
 Accepts **ReferenceText**: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: '{TITLE}'

width Width to render the flowable at (inherited from [ParagraphStyle](#))
 Accepts **FlowableWidth**: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))
 Accepts **Dimension**: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

`text_align` Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

`tab_stops` List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

`number_format` How numbers are formatted (inherited from [ParagraphStyle](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

`number_separator`

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from [ParagraphStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ''

`numbering_level` At which section level to restart numbering (positive: absolute, negative: relative) (inherited from [ParagraphStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: (no value)

`horizontal_align` Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

`space_above` Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`space_below` Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`margin_left` Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding` Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_left` Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_right` Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`background_color`

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))

Accepts Break: none, any, left, right

Default: None

`label_prefix` Text to prepend to the label (inherited from [LabelStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

`label_suffix` Text to append to the label (inherited from [LabelStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

`custom_label` Use a custom label if specified (inherited from [LabelStyle](#))

Accepts [Bool](#): true or false

Default: false

`typeface` Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fon](#)t for a list of the available typefaces.

Default: Times

`font_weight` Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

`font_slant` Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright
 font_width Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5
 font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt
 font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000
 font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal
 position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal
 kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2
 hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US
 before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

NoteMarkerStyle

class rinoх.reference.NoteMarkerStyle (base=None, **attributes)

Style class for NoteMarker

typeface Typeface to set the text in (inherited from [TextStyle](#))

Accepts [Typeface](#): the name of a typeface. See [rinoх --list-fonTs](#) for a list of the available typefaces.

Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))

Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic

Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))

Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size Height of characters (inherited from [TextStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))

Accepts [FontVariant](#): normal, small capital, oldstyle figures

Default: normal

position Vertical text position (inherited from [TextStyle](#))

Accepts [TextPosition](#): normal, superscript, subscript

Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

number_format How numbers are formatted (inherited from [NumberStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))

Accepts [Bool](#): true or false

Default: false

SectionStyle

class rinooh.structure.SectionStyle (base=None, **attributes)

Style class for [Section](#)

show_in_toc List this section in the table of contents

Accepts [Bool](#): true or false

Default: true

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in,

pc, mm, cm, %, /2, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the

stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts Bool: true or false
 Default: false

[HeadingStyle](#)

```
class rinostructure.HeadingStyle ( base=None, **attributes )
```

Style class for [Heading](#)

keep_with_next Overrides the default set in [FlowableStyle](#)
 Accepts Bool: true or false
 Default: true

numbering_level Overrides the default set in [ParagraphStyle](#)
 Accepts Integer: a natural number (positive integer)
 Default: -1

width Width to render the flowable at (inherited from [ParagraphStyle](#))
 Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))
 Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))
 Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify
 Default: justify

`tab_stops` List of tab positions (inherited from [ParagraphStyle](#))
 Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

`number_format` How numbers are formatted (inherited from [ParagraphStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: None

`number_separator`
 Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from [ParagraphStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: ','

`horizontal_align` Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left

`space_above` Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

`space_below` Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

`margin_left` Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

`padding` Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from [FlowableStyle](#))

Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)

Default: none

`page_break` Type of page break to insert before rendering this flowable
(inherited from [FlowableStyle](#))
Accepts Break: none, any, left, right
Default: None

`label_prefix` Text to prepend to the label (inherited from [LabelStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

`label_suffix` Text to append to the label (inherited from [LabelStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

`custom_label` Use a custom label if specified (inherited from [LabelStyle](#))
Accepts [Bool](#): true or false
Default: false

`typeface` Typeface to set the text in (inherited from [TextStyle](#))
Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fon](#)ts for a list of the available typefaces.
Default: Times

`font_weight` Thickness of character outlines relative to their height (inherited from [TextStyle](#))
Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

`font_slant` Slope style of the font (inherited from [TextStyle](#))
Accepts [FontSlant](#): upright, oblique, italic
Default: upright

`font_width` Stretch of the characters (inherited from [TextStyle](#))
Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

`font_size` Height of characters (inherited from [TextStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

`font_color` Color of the font (inherited from [TextStyle](#))
Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000
 font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal
 position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal
 kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true
 hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2
 hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US
 before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)
 after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)
 hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

ListStyle

```

class rinoh.structure.ListStyle ( base=None, **attributes )
  Style class for List
  ordered This list is ordered or unordered

```

Accepts [Bool](#): true or false
 Default: false
bullet Bullet to use in unordered lists
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: '•'
width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill
title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)
flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left
space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0
padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

number_format How numbers are formatted (inherited from [NumberStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
 Default: number

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
 Accepts [Bool](#): true or false
 Default: false

[ListItemLabelStyle](#)

```
class rinoх.structure.ListItemLabelStyle ( base=None, **attributes )
```

Style class for [ListItemLabel](#)

width Width to render the flowable at (inherited from [ParagraphStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format How numbers are formatted (inherited from [ParagraphStyle](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from [ParagraphStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ''

numbering_level At which section level to restart numbering (positive: absolute, negative: relative) (inherited from [ParagraphStyle](#))

Accepts [Integer](#): a natural number (positive integer)

Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding Padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
 Accepts [Bool](#): true or false
 Default: false

typeface Typeface to set the text in (inherited from [TextStyle](#))
 Accepts [Typeface](#): the name of a typeface. See [rino --list-fs](#) for a list of the available typefaces.
 Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
 Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
 Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))

Accepts [FontSlant](#): upright, oblique, italic
 Default: upright

`font_width` Stretch of the characters (inherited from [TextStyle](#))
 Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
 Default: 5

`font_size` Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt

`font_color` Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

`font_variant` Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

`position` Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

`kerning` Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

`ligatures` Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

`hyphenate` Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

`hyphen_chars` Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

`hyphen_lang` Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

`before` Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)
 after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)
 hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

[TableOfContentsStyle](#)

```
class rinostructure.TableOfContentsStyle ( base=None, **attributes )
```

Style class for [TableOfContents](#)

depth The number of section levels to include in the table of contents
 Accepts [Integer](#): a natural number (positive integer)
 Default: 3

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

`margin_left` Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`margin_right` Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding` Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_left` Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_right` Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_top` Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`padding_bottom` Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

`keep_with_next` Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

`border` Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_left` Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

`background_color`
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

`indent_first` Indentation of the first line of text (inherited from [ParagraphStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0pt

`line_spacing` Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))
 Accepts [LineSpacing](#): a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
 Default: default

`text_align` Alignment of text to the margins (inherited from [ParagraphStyle](#))
 Accepts [TextAlign](#): left, right, center, justify
 Default: justify

`tab_stops` List of tab positions (inherited from [ParagraphStyle](#))
 Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.
 Default: (no value)

`number_format` How numbers are formatted (inherited from [ParagraphStyle](#))
 Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

	Default: None
number_separator	Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from ParagraphStyle)
	Accepts StyledText : a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
	Default: ''
numbering_level	At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)
	Accepts Integer : a natural number (positive integer)
	Default: (no value)
label_prefix	Text to prepend to the label (inherited from LabelStyle)
	Accepts StyledText : a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
	Default: (no value)
label_suffix	Text to append to the label (inherited from LabelStyle)
	Accepts StyledText : a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
	Default: (no value)
custom_label	Use a custom label if specified (inherited from LabelStyle)
	Accepts Bool : true or false
	Default: false
typeface	Typeface to set the text in (inherited from TextStyle)
	Accepts Typeface : the name of a typeface. See rinoh --list-fon t for a list of the available typefaces.
	Default: Times
font_weight	Thickness of character outlines relative to their height (inherited from TextStyle)
	Accepts FontWeight : hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
	Default: 500
font_slant	Slope style of the font (inherited from TextStyle)
	Accepts FontSlant : upright, oblique, italic
	Default: upright
font_width	Stretch of the characters (inherited from TextStyle)
	Accepts FontWidth : ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded,

expanded, extra-expanded, ultra-expanded
 Default: 5

font_size Height of characters (inherited from [TextStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
 Accepts [FontVariant](#): normal, small capital, oldstyle figures
 Default: normal

position Vertical text position (inherited from [TextStyle](#))
 Accepts [TextPosition](#): normal, superscript, subscript
 Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

TableOfContentsEntryStyle

class rinooh.structure.TableOfContentsEntryStyle (base=None, **attributes)

Style class for [TableOfContentsEntry](#)

text Overrides the default set in [ReferencingParagraphStyle](#)

Accepts [ReferenceText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}'

width Width to render the flowable at (inherited from [ParagraphStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first Indentation of the first line of text (inherited from [ParagraphStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing Spacing between the baselines of two successive lines of text (inherited from [ParagraphStyle](#))

Accepts [LineSpacing](#): a [predefined line spacing](#) type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align Alignment of text to the margins (inherited from [ParagraphStyle](#))

Accepts [TextAlign](#): left, right, center, justify

Default: justify

tab_stops List of tab positions (inherited from [ParagraphStyle](#))

Accepts [TabStopList](#): a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position ([Dimension](#)) is required and align ([TabAlign](#)) and fill string (string enclosed in quotes) are optional.

Default: (no value)

number_format How numbers are formatted (inherited from [ParagraphStyle](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from [ParagraphStyle](#))

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces:

'text string' (style name)
Default: ''

numbering_level At which section level to restart numbering (positive: absolute, negative: relative) (inherited from [ParagraphStyle](#))
Accepts [Integer](#): a natural number (positive integer)
Default: (no value)

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
Accepts [HorizontalAlignment](#): left, right, center
Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding Padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

label_prefix Text to prepend to the label (inherited from [LabelStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

label_suffix Text to append to the label (inherited from [LabelStyle](#))
Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label Use a custom label if specified (inherited from [LabelStyle](#))
Accepts [Bool](#): true or false
Default: false

typeface Typeface to set the text in (inherited from [TextStyle](#))
Accepts [Typeface](#): the name of a typeface. See [rinoh --list-fs](#) for a list of the available typefaces.
Default: Times

font_weight Thickness of character outlines relative to their height (inherited from [TextStyle](#))
Accepts [FontWeight](#): hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

font_slant Slope style of the font (inherited from [TextStyle](#))
Accepts [FontSlant](#): upright, oblique, italic
Default: upright

font_width Stretch of the characters (inherited from [TextStyle](#))
Accepts [FontWidth](#): ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

font_size Height of characters (inherited from [TextStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color Color of the font (inherited from [TextStyle](#))
Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant Variant of the font (inherited from [TextStyle](#))
Accepts [FontVariant](#): normal, small capital, oldstyle figures
Default: normal

position Vertical text position (inherited from [TextStyle](#))
Accepts [TextPosition](#): normal, superscript, subscript
Default: normal

kerning Improve inter-letter spacing (inherited from [TextStyle](#))
Accepts [Bool](#): true or false
Default: true

ligatures Run letters together where possible (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphenate Allow words to be broken over two lines (inherited from [TextStyle](#))
 Accepts [Bool](#): true or false
 Default: true

hyphen_chars Minimum number of characters in a hyphenated part of a word (inherited from [TextStyle](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: 2

hyphen_lang Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from [TextStyle](#))
 Accepts [Locale](#): locale identifier in the <language ID>_<region ID> format
 Default: en_US

before Item to insert before this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

after Item to insert after this one (inherited from [InlineStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

AdmonitionStyle

```

class rinostructure.AdmonitionStyle ( base=None, **attributes )
  Style class for Admonition
  inline_title Show the admonition's title inline with the body text, if possible
    Accepts Bool: true or false
    Default: true
  width Width to render the flowable at (inherited from GroupedFlowablesStyle)
    Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
    Default: fill
  title Title to precede the flowables (inherited from GroupedFlowablesStyle)
    Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
  
```

Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
Accepts [HorizontalAlignment](#): left, right, center
Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding Padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))
Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

HorizontalRuleStyle

```
class rinoх.structure.HorizontalRuleStyle ( base=None, **attributes )  
    Style class for HorizontalRule  
    width Width to render the flowable at (inherited from FlowableStyle)  
        Accepts FlowableWidth: auto, fill or a numeric value followed by a  
        unit (pt, in, pc, mm, cm, %, /2, /4)  
        Default: auto  
    horizontal_align Horizontal alignment of the flowable (inherited from  
        FlowableStyle)  
        Accepts HorizontalAlignment: left, right, center  
        Default: left  
    space_above Vertical space preceding the flowable (inherited from  
        FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    space_below Vertical space following the flowable (inherited from  
        FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    margin_left Left margin (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    margin_right Right margin (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    padding Padding (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc,  
        mm, cm, %, /2, /4)  
        Default: 0  
    padding_left Left padding (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    padding_right Right padding (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)  
        Default: 0  
    padding_top Top padding (inherited from FlowableStyle)  
        Accepts Dimension: a numeric value followed by a unit (pt, in,  
        pc, mm, cm, %, /2, /4)
```

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))
 Accepts [Bool](#): true or false
 Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)
 Default: none

background_color Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

stroke Width and color used to draw the line (inherited from [LineStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke,

separated by a comma (,)

Default: 1pt, #000

TableStyle

class rinoх.table.TableStyle (base=None, **attributes)

Style class for [Table](#)

column_widths Absolute or relative widths of each column

Accepts [ColumnWidths](#): a whitespace-delimited list of column widths; [Dimensions](#) (absolute width), integers (relative width) and/or 'auto' (automatic width)

Default: none

split_minimum_rows

The minimum number of rows to display when the table is split across pages

Accepts [Integer](#): a natural number (positive integer)

Default: (no value)

repeat_head Repeat the head when the table is split across pages

Accepts [Bool](#): true or false

Default: false

width Width to render the flowable at (inherited from [FlowableStyle](#))

Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))

Accepts [HorizontalAlignment](#): left, right, center

Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_right Border right of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_top Border above the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_bottom Border below the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

background_color
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBAA, #RGB or #RGBA)
 Default: none

page_break Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts Break: none, any, left, right
 Default: None

hide Suppress rendering this element (inherited from [Style](#))
 Accepts Bool: true or false
 Default: false

TableCellStyle

```
class rinoh.table.TableCellStyle ( base=None, **attributes )
```

Style class for [TableCell](#)

vertical_align Vertical alignment of the cell contents within the available space
 Accepts [VerticalAlign](#): top, middle, bottom
 Default: middle

width Width to render the flowable at (inherited from [GroupedFlowablesStyle](#))
 Accepts [FlowableWidth](#): auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: fill

title Title to precede the flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
 Default: (no value)

flowable_spacing Spacing between flowables (inherited from [GroupedFlowablesStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

horizontal_align Horizontal alignment of the flowable (inherited from [FlowableStyle](#))
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left

space_above Vertical space preceding the flowable (inherited from [FlowableStyle](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: 0

space_below Vertical space following the flowable (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left Left margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right Right margin (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding Padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left Left padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right Right padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top Top padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom Bottom padding (inherited from [FlowableStyle](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next Keep this flowable and the next on the same page (inherited from [FlowableStyle](#))

Accepts [Bool](#): true or false

Default: false

border Border surrounding the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

border_left Border left of the flowable (inherited from [FlowableStyle](#))

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_right` Border right of the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_top` Border above the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`border_bottom` Border below the flowable (inherited from [FlowableStyle](#))
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`background_color`
 Color of the area within the flowable's borders (inherited from [FlowableStyle](#))
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
 Default: none

`page_break` Type of page break to insert before rendering this flowable (inherited from [FlowableStyle](#))
 Accepts [Break](#): none, any, left, right
 Default: None

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

TableCellBorderStyle

```
class rinoth.table.TableCellBorderStyle ( base=None, **attributes )
```

Style class for [TableCellBorder](#)

`stroke` Overrides the default set in [LineStyle](#)
 Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

`hide` Suppress rendering this element (inherited from [Style](#))
 Accepts [Bool](#): true or false
 Default: false

TableCellBackgroundColor

```
class rinoth.table.TableCellBackgroundColor ( base=None, **attributes )
```

Style class for [TableCellBackground](#)

`fill_color` Overrides the default set in [ShapeStyle](#)
 Accepts [Color](#): HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

stroke Overrides the default set in [LineStyle](#)

Accepts [Stroke](#): the width ([Dimension](#)) and color ([Color](#)) of the stroke, separated by a comma (,)

Default: none

hide Suppress rendering this element (inherited from [Style](#))

Accepts [Bool](#): true or false

Default: false

7.4 Standard Document Templates

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

7.4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

class rinohtype.templates.article.Article (document_tree, configuration=None, backend=None)

stylesheet Overrides the default set in [DocumentTemplate](#)

Accepts [StyleSheet](#): the name of an [installed style sheet](#) or the file-name of a stylesheet file (with the .rts extension)

Default: sphinx_article (= [rinohtype.stylesheets.sphinx_article](#))

table_of_contents Show or hide the table of contents

Accepts [Bool](#): true or false

Default: true

abstract_location Where to place the abstract

Accepts [AbstractLocation](#): title, front matter

Default: front matter

parts Overrides the default set in [DocumentTemplate](#)

Accepts [PartsList](#): a space-separated list of document part template names

Default: title front_matter contents

language The main language of the document (inherited from [DocumentTemplate](#))

Accepts [Language](#): the code of one of the [supported languages](#)

Default: EN (English)

strings Strings to override standard element names (inherited from [DocumentTemplate](#))

Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses

Default: none

title base: None

Type [TitlePartTemplate](#)

```

front_matter base: None
    Type ArticleFrontMatter
contents base: None
    Type ContentsPartTemplate
page base: None
    Overrides these defaults:
        • page_size = $(paper_size)

        Type PageTemplate
title_page base: page
    Overrides these defaults:
        • top_margin = 8cm

        Type TitlePageTemplate
front_matter_page
    base: page
        Type PageTemplate
contents_page base: page
    Type PageTemplate
Configuration alias of rinoh.template.ArticleConfiguration
ConfigurationFile alias of rinoh.template.ArticleConfigurationFile
class rinoh.templates.article.AbstractLocation
    Where to place the article's abstract
    Accepts: title, front matter

```

7.4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

```

class rinoh.templates.book.Book ( document_tree, configuration=None, backend=None )
    stylesheet Overrides the default set in DocumentTemplate
        Accepts StyleSheet: the name of an installed style sheet or the file-
        name of a stylesheet file (with the .rts extension)
        Default: sphinx (= rinoh.stylesheets.sphinx)
    parts Overrides the default set in DocumentTemplate
        Accepts PartsList: a space-separated list of document part template
        names
        Default: title front_matter contents back_matter
    language The main language of the document (inherited from
        DocumentTemplate)
        Accepts Language: the code of one of the supported languages
        Default: EN (English)

```

strings Strings to override standard element names (inherited from [DocumentTemplate](#))

Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses

Default: none

cover base: None

Overrides these defaults:

- [drop_if_empty](#) = False
- [page_number_format](#) = None
- [end_at_page](#) = left

Type [FixedDocumentPartTemplate](#)

title base: None

Overrides these defaults:

- [page_number_format](#) = number
- [end_at_page](#) = left

Type [TitlePartTemplate](#)

front_matter base: None

Overrides these defaults:

- [flowables](#) = [TableOfContentsSection(), ListOfFiguresSection(), ListOfTablesSection()]
- [page_number_format](#) = lowercase roman
- [end_at_page](#) = left

Type [FixedDocumentPartTemplate](#)

contents base: None

Overrides these defaults:

- [page_number_format](#) = number
- [end_at_page](#) = left

Type [ContentsPartTemplate](#)

back_matter base: None

Overrides these defaults:

- [page_number_format](#) = number
- [end_at_page](#) = left

Type [BackMatterTemplate](#)

page base: None

Overrides these defaults:

- `page_size` = `$(paper_size)`
- `left_margin` = `1in`
- `right_margin` = `1in`
- `top_margin` = `1in`
- `bottom_margin` = `1in`

Type `PageTemplate`

`cover_page` base: `page`

Type `PageTemplate`

`title_page` base: `page`

Type `TitlePageTemplate`

`front_matter_page`

base: `page`

Overrides these defaults:

- `header_footer_distance` = `0`
- `header_text` = `None`

Type `PageTemplate`

`front_matter_right_page`

base: `front_matter_page`

Overrides these defaults:

- `footer_text` = `'\t' '\t' '{PAGE_NUMBER}'`
- `chapter_header_text` = `None`
- `chapter_footer_text` = `'\t' '\t' '{PAGE_NUMBER}'`
- `chapter_title_height` = `2.5in`
- `chapter_title_flowables` = `[<rinoh.paragraph.Paragraph object at 0x7fee371c2610>]`

Type `PageTemplate`

`front_matter_left_page`

base: `front_matter_page`

Overrides these defaults:

- `footer_text` = `'{PAGE_NUMBER}'`

Type `PageTemplate`

`contents_page` base: `page`

Overrides these defaults:

- `header_footer_distance` = `0`

Type [PageTemplate](#)

contents_right_page

base: [contents_page](#)

Overrides these defaults:

- `header_text` = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{SECTION_NUMBER(2)}' '. ' '{SECTION_TITLE(2)}' '\t' '\t' '{PAGE_NUMBER}'
- `chapter_header_text` = None
- `chapter_footer_text` = '\t' '\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.4in
- `chapter_title_flowables` = [`<rinoh.paragraph.Paragraph object at 0x7fee371c2580>`, `<rinoh.paragraph.Paragraph object at 0x7fee371dbb50>`]

Type [PageTemplate](#)

contents_left_page

base: [contents_page](#)

Overrides these defaults:

- `header_text` = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{PAGE_NUMBER}' '\t' '\t' '{SectionTitles.chapter}' ' ' '{SECTION_NUMBER(1)}' '. ' '{SECTION_TITLE(1)}'

Type [PageTemplate](#)

back_matter_page

base: [page](#)

Overrides these defaults:

- `columns` = 2
- `header_footer_distance` = 0

Type [PageTemplate](#)

back_matter_right_page

base: [back_matter_page](#)

Overrides these defaults:

- `header_text` = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{SECTION_TITLE(1)}' '\t' '\t' '{PAGE_NUMBER}'
- `chapter_header_text` = None

- `chapter_footer_text` = '\t' '\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.5in
- `chapter_title_flowables` = [`<rinoh.paragraph.Paragraph object at 0x7fee371c2610>`]

Type [PageTemplate](#)

`back_matter_left_page`

base: [back_matter_page](#)

Overrides these defaults:

- `header_text` = '{DOCUMENT_TITLE}' ' ' '{DOCUMENT_SUBTITLE}'
- `footer_text` = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE(1)}'

Type [PageTemplate](#)

Configuration alias of `rinoh.template.BookConfiguration`

ConfigurationFile alias of `rinoh.template.BookConfigurationFile`

Note

The API documentation is still incomplete.

8.1 Attribute ([rinoh.attribute](#))

```
class rinoh.attribute.AcceptNoneAttributeType
    Accepts 'none' (besides other values)
class rinoh.attribute.OptionSet
    Accepts the values listed in values
    Accepts:
class rinoh.attribute.Attribute ( accepted_type, default_value, description )
    Descriptor used to describe a style attribute
class rinoh.attribute.OverrideDefault ( default_value )
    Overrides the default value of an attribute defined in a superclass
class rinoh.attribute.AttributesDictionary ( base=None, **attributes )
class rinoh.attribute.RuleSet ( name, base=None, source=None, **kwargs )
class rinoh.attribute.RuleSetFile ( filename, base=None, source=None, **kwargs )
    property location Textual representation of this source
    property root Directory path for resolving paths relative to this source
class rinoh.attribute.Bool
    Expresses a binary choice
class rinoh.attribute.Integer
    Accepts natural numbers
exception rinoh.attribute.ParseError
```

8.2 Color ([rinoh.color](#))

```
class rinoh.color.Color ( red, green, blue, alpha=1 )
    Color defined by component values
```

```

Parameters      • red (float) – red component (0 .. 1)
                • blue (float) – blue component (0 .. 1)
                • green (float) – green component (0 .. 1)
                • alpha (float) – opacity (0 .. 1)

property rgba

classmethod parse_string ( string, source )
classmethod doc_format ( )

class rinoх.color.HexColor ( string )
    Color defined as a hexadecimal string
    Parameters string (str) – #RGBA or #RRGGBBAA (# and A are optional)

class rinoх.color.Gray ( luminance, alpha=1 )
    Shade of gray
    Parameters      • luminance (float) – brightness (0 .. 1)
                    • alpha (float) – opacity (0 .. 1)

```

8.3 Dimension ([rinoх.dimension](#))

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```

height = 100*PT
width = 50*PERCENT

```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a Flowable is evaluated with respect to the total width available to it.

```
class rinoх.dimension.Dimension ( value=0, unit=None )
```

A simple dimension

```

Parameters      • value (int or float) – the magnitude of the dimension
                • unit (DimensionUnit) – the unit this dimension is expressed
                    in. Default: PT.

```

```
grow ( value ) Grow this dimension (in-place)
```

The value is interpreted as a magnitude expressed in the same unit as this dimension.

```
Parameters value (int or float) – the amount to add to the
magnitude of this dimension
```

Returns [Dimension](#) – this (growed) dimension itself

```
rinoх.dimension.PT = DimensionUnit(1.0, 'pt')
```

PostScript points

```

rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')
    computer pica
rinoh.dimension.INCH = DimensionUnit(72.0, 'in')
    imperial/US inch
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
    millimeter
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
    centimeter
rinoh.dimension.PERCENT = FractionUnit(100, '%')
    fraction of 100
rinoh.dimension.QUARTERS = FractionUnit(4, '/4')
    fraction of 4

```

8.4 Document (rinoh.document)

```

class rinoh.document.DocumentTree ( flowables, options=None )
    Holds the document's contents as a tree of flowables
    Parameters
        • flowables (list\[Flowable\]) – the list of top-level flowables
        • source_root (Path) – path used to locate images and include
            in logging and error and warnings.
        • options (Reader) – frontend-specific options

class rinoh.document.Document ( document_tree, stylesheet, language, strings=None,
backend=None )
    Renders a document tree to pages
    Parameters
        • document_tree (DocumentTree) – a tree of the document's
            contents
        • stylesheet (StyleSheet) – style sheet used to style document
            elements
        • language (Language) – the language to use for standard
            strings
        • strings (Strings) – overrides localized strings provided by
            language
        • backend – the backend used for rendering the document

    render ( filename_root=None, file=None )
        Render the document repeatedly until the output no
        longer changes due to cross-references that need some
        iterations to converge.

```

8.4.1 Pages

```
class rinoх.document.Page ( document_part, number, paper, orientation='portrait' )
```

A single page in a document.

A [Page](#) is a Container, so other containers can be added as children.

Parameters

- `document_part` ([DocumentPart](#)) – the document part this page is part of
- `number` ([int](#)) – the 1-based index of this page in the document part
- `paper` ([Paper](#)) – determines the dimensions of this page
- `orientation` ([PageOrientation](#)) – the orientation of this page

property `page` Returns the page itself.

`render ()` Render the contents of this container to its canvas.

Note that the rendered contents need to be [place\(\)](#)d on the parent container's canvas before they become visible.

`place ()` Place this container's canvas onto the parent container's canvas.

```
class rinoх.document.PageOrientation
```

Accepts: portrait, landscape

```
class rinoх.document.PageType
```

Accepts: left, right, any

8.5 Drawing Primitives ([rinoх.draw](#))

```
class rinoх.draw.Stroke ( width, color )
```

The display properties of a line

Parameters

- `width` ([Dimension](#)) – the width of the line
- `color` ([Color](#)) – the color of the line

```
class rinoх.draw.Line ( start, end, style=None, parent=None )
```

Draws a line

Parameters

- `start` (2-tuple) – coordinates for the start point of the line
- `end` (2-tuple) – coordinates for the end point of the line

`style_class` alias of [rinoх.draw.LineStyle](#)

```
class rinoх.draw.Shape ( style=None, parent=None )
```

Base class for closed shapes

`style_class` alias of [rinoх.draw.ShapeStyle](#)

```
class rinoх.draw.Polygon ( points, style=None, parent=None )
```

```
class rinoх.draw.Rectangle ( bottom_left, width, height, style=None, parent=None )
```

8.6 Flowable (rinoх.flowable)

```
class rinoх.flowable.Flowable ( align=None, width=None, id=None, style=None, parent=None, source=None )
```

A document element that can be “flowed” into a container on the page.

A flowable can adapt to the width of the container, or it can horizontally align itself in the container.

Parameters

- align ([HorizontalAlignment](#)) – horizontal alignment of the flowable
- width ([FlowableWidth](#) or [DimensionBase](#)) – the width of the flowable.

```
class rinoх.flowable.FlowableState ( flowable, _initial=True )
```

Stores a flowable’s rendering state, which can be copied.

This enables saving the rendering state at certain points in the rendering process, so rendering can later be resumed at those points, if needed.

8.6.1 No-Output Flowables

These flowables do not directly place anything on the page. All except [DummyFlowable](#) do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

```
class rinoх.flowable.DummyFlowable ( id=None, parent=None )
```

A flowable that does not directly place anything on the page.

Subclasses can produce side-effects to affect the output in another way.

```
class rinoх.flowable.AnchorFlowable ( id=None, parent=None )
```

A dummy flowable that registers a destination anchor.

Places a destination for the flowable’s ID at the current cursor position.

```
class rinoх.flowable.SetMetadataFlowable ( parent=None, **metadata )
```

A dummy flowable that stores metadata in the document.

The metadata is passed as keyword arguments. It will be available to other flowables during the rendering stage.

```
class rinoх.flowable.WarnFlowable ( message, parent=None )
```

A dummy flowable that emits a warning during the rendering stage.

Parameters message ([str](#)) – the warning message to emit

```
class rinoх.flowable.PageBreak ( page_break='any' )
```

8.6.2 Labeled Flowables

```
class rinoх.flowable.LabeledFlowable ( label, flowable, id=None, style=None, parent=None )
```

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the label_max_width style attribute value, the flowable is rendered below the label.

```

Parameters      • label (Flowable) – the label for the flowable
                • flowable (Flowable) – the flowable to label

style_class alias of rinoh.flowable.LabeledFlowableStyle

prepare ( flowable_target )
    Determine number labels and register references with the
    document

render ( container, last_descender, state, label_column_width=None,
space_below=0, **kwargs )
    Renders the flowable's content to container, with the flow-
    able's top edge lining up with the container's cursor.
    descender is the descender height of the preceding line or
    None.

class rinoх.flowable.LabeledFlowableState ( flowable, content_flowable_state, _initial=True )

```

8.6.3 Grouping Flowables

```

class rinoх.flowable.GroupedFlowables ( align=None, width=None, id=None, style=None,
parent=None, source=None )
    Groups a list of flowables and renders them one below the other.

    Makes sure that a flowable for which keep_with_next is enabled is not seper-
    ated from the flowable that follows it.

    Subclasses should implement flowables\(\).

style_class alias of rinoh.flowable.GroupedFlowablesStyle

flowables ( container )
    Generator yielding the Flowables to group

render ( container, descender, state, first_line_only=False, **kwargs )
    Renders the flowable's content to container, with the flow-
    able's top edge lining up with the container's cursor.
    descender is the descender height of the preceding line or
    None.

class rinoх.flowable.GroupedFlowableState ( groupedflowables, flowables,
first_flowable_state=None, _initial=True, _index=0 )
    Groups a static list of flowables.

    Parameters flowables (iterable[Flowable]) – the flowables to group

flowables ( container )
    Generator yielding the Flowables to group

build_document ( flowable_target )
    Set document metadata and populate front and back
    matter

prepare ( flowable_target )
    Determine number labels and register references with the
    document

```

```
class rinoх.flowable.GroupedLabeledFlowables ( align=None, width=None, id=None,
style=None, parent=None, source=None )
    Groups a list of labeled flowables, lining them up.
    render ( container, descender, state, **kwargs )
        Renders the flowable's content to container, with the flow-
        able's top edge lining up with the container's cursor.
        descender is the descender height of the preceding line or
        None.
```

8.6.4 Floating Flowables

```
class rinoх.flowable.Float ( align=None, width=None, id=None, style=None, parent=None,
source=None )
    A flowable that can optionally be placed elsewhere on the page.
    If this flowable's float style attribute is set to True, it is not flowed in line with
    the surrounding flowables, but it is instead flowed into another container
    pointed to by the former's Container.float_space attribute.
    This is typically used to place figures and tables at the top or bottom of a
    page, instead of in between paragraphs.
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical
        space consumed.
        The flowable's contents are preceded by a vertical space
        with a height as specified in its style's space_above
        attribute. Similarly, the flowed content is followed by a
        vertical space with a height given by the space_below style
        attribute.
```

8.6.5 Styling Properties

```
class rinoх.flowable.HorizontalAlignment
    Controls horizontal placement
    Accepts: left, right, center
class rinoх.flowable.FlowableWidth
    Controls the width of a flowable
    Accepts: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm,
    %, /2, /4)
```

8.7 Fonts and Typefaces (rinoх.font)

Classes for fonts and typefaces.

```
class rinoх.font.Font ( filename, weight, slant, width )
    A collection of glyphs in a particular style
    This is a base class for classes that parse different font formats. See rinoх-
    font.type1 and rinoх.font.opentype.
    Parameters
        • filename (str) – filename of the font file to load
```

- weight ([FontWeight](#)) – weight of the font
- slant ([FontSlant](#)) – slant of the font
- width ([FontWidth](#)) – width of the font

encoding If no encoding is set for the [Font](#), glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

`get_glyph (char, variant)`

Return the glyph for a particular character

If the glyph of requested font variant is not present in the font, the normal variant is returned instead. If that is not present either, an exception is raised.

Parameters

- `char` (str of length 1) – the character for which to find the glyph
- `variant` ([FontVariant](#)) – the variant of the glyph to return

Returns [GlyphMetrics](#) – the requested glyph

Raises [MissingGlyphException](#) – when the requested glyph is not present in the font

`get_ligature (glyph, successor_glyph)`

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return None.

Parameters

- `glyph` ([GlyphMetrics](#)) – the first of the glyphs to combine
- `successor_glyph` ([GlyphMetrics](#)) – the second of the glyphs to combine

Returns [GlyphMetrics](#) or None – the ligature to replace the given glyphs

`get_kerning (a, b)`

Look up the kerning for two glyphs

Parameters

- `a` ([GlyphMetrics](#)) – the first of the glyphs
- `b` ([GlyphMetrics](#)) – the second of the glyphs

Returns float – the kerning value in font units

`class rinoh.font.Typeface (name, *fonts)`

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters `*fonts` ([Font](#)) – the fonts that make up this typeface

`fonts ()` Generator yielding all fonts of this typeface

Yields [Font](#) – the next font in this typeface

```

get_font ( weight=400, slant='upright', width=5 )
    Return the font matching or closest to the given style
    If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters
    • weight (FontWeight) – weight of the font
    • slant (FontSlant) – slant of the font
    • width (FontWidth) – width of the font

Returns Font – the requested font

class rinoh.font.style.FontWeight
    Accepts: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

class rinoh.font.style.FontSlant
    Accepts: upright, oblique, italic

class rinoh.font.style.FontWidth
    Accepts: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

class rinoh.font.style.FontVariant
    Accepts: normal, small capital, oldstyle figures

class rinoh.font.style.TextPosition
    Accepts: normal, superscript, subscript

```

8.8 Images and Figures ([rinoh.image](#))

```

class rinoh.image.Image ( filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, id=None, style=None, parent=None, source=None )

class rinoh.image.InlineImage ( filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, baseline=None, id=None, style=None, parent=None, source=None )
    arguments alias of rinoh.image.InlineImageArgs

class rinoh.image.BackgroundImage ( filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, id=None, style=None, parent=None, source=None )
    Image to place in the background of a page
    Takes the same arguments as Image.
    arguments alias of rinoh.image.ImageArgs

class rinoh.image.ImageArgs ( base=None, **attributes )
    limit_width Limit the image width when none of scale, width and height are given and the image would be wider than the container
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

```

Default: 100%
 align How to align the image within the page
 Accepts [HorizontalAlignment](#): left, right, center
 Default: left
 file_or_filename Path to the image file (inherited from [ImageArgsBase](#))
 Accepts [ImagePath](#): path to an image file enclosed in quotes
 Default: none
 scale Scaling factor for the image (inherited from [ImageArgsBase](#))
 Accepts [Scale](#): fit, fill or a float larger than 0
 Default: fit
 width The width to scale the image to (inherited from [ImageArgsBase](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: none
 height The height to scale the image to (inherited from [ImageArgsBase](#))
 Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
 Default: none
 dpi Overrides the DPI value set in the image (inherited from [ImageArgsBase](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: (no value)
 rotate Angle in degrees to rotate the image (inherited from [ImageArgsBase](#))
 Accepts [Integer](#): a natural number (positive integer)
 Default: (no value)

class rinoх.image.Scale

Scaling factor for images

Can be a numerical value where a value of 1 keeps the image's original size or one of values.

Accepts: fit, fill or a float larger than 0

class rinoх.image.Caption (content, custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None)

style_class alias of [rinoх.image.CaptionStyle](#)

class rinoх.image.Figure (flowables, align=None, width=None, id=None, style=None, parent=None, source=None)

style_class alias of [rinoх.image.FigureStyle](#)

class rinoх.image.ListOfFiguresSection

list_class alias of [rinoх.image.ListOfFigures](#)

class rinoх.image.ListOfFigures (local=False, id=None, style=None, parent=None)

8.9 Index ([rinoх.index](#))

class rinoх.index.IndexSection (title=None, flowables=None, style=None)

```

class rinoх.index.Index ( id=None, style=None, parent=None )
    style_class alias of rinoх.index.IndexStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoх.index.IndexLabel ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )
class rinoх.index.IndexTerm ( *levels )
class rinoх.index.InlineIndexTarget ( index_terms, *args, **kwargs )
    to_string ( flowable_target )
        Return the text content of this styled text.
class rinoх.index.IndexTarget ( index_terms, parent=None )
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical
        space consumed.
        The flowable's contents are preceded by a vertical space
        with a height as specified in its style's space_above
        attribute. Similarly, the flowed content is followed by a
        vertical space with a height given by the space_below style
        attribute.

```

8.10 Language ([rinoх.language](#))

```

class rinoх.language.Language ( code, name )
    Collects localized strings for a particular language
    Parameters
        • code (str) – short code identifying the language
        • name (str) – native name of the language

```

languages Dictionary mapping codes to [Languages](#)

The following languages are supported:

```

rinoх.language.EN = Language('en', 'English')
    Localized strings for English
    SectionTitles
    Contents Table of Contents
    List_of_figures List of Figures
    List_of_tables List of Tables
    Chapter Chapter
    Index Index
    AdmonitionTitles
    Attention Attention!
    Caution Caution!
    Danger !DANGER!
    Error Error

```

Hint Hint
Important Important
Note Note
Tip Tip
Warning Warning
Seealso See also

rinoh.language.FR = Language('fr', 'Français')
 Localized strings for Français
 SectionTitles
 Contents Table des Matières
 List_of_figures Liste des Figures
 List_of_tables Liste des Tableaux
 Chapter Chapitre
 Index Index
 AdmonitionTitles
 Attention Attention!
 Caution Prudence!
 Danger !DANGER!
 Error Erreur
 Hint Conseil
 Important Important
 Note Note
 Tip Astuce
 Warning Avertissement
 Seealso Voir aussi

rinoh.language.IT = Language('it', 'Italiano')
 Localized strings for Italiano
 SectionTitles
 Contents Contenuti
 List_of_figures Elenco delle Figure
 List_of_tables Elenco delle Tabelle
 Chapter Capitolo
 Index Indice
 AdmonitionTitles
 Attention Attenzione!
 Caution Prudenza!
 Danger !PERICOLO!
 Error Errore
 Hint Consiglio
 Important Importante
 Note Nota

Tip Suggerimento

Warning Avvertimento

Seealso Vedi anche

rinoh.language.NL = Language('nl', 'Nederlands')

Localized strings for Nederlands

SectionTitles

Contents Inhoudsopgave

List_of_figures Lijst van Figuren

List_of_tables Lijst van Tabellen

Chapter Hoofdstuk

Index Index

AdmonitionTitles

Attention Opgelet!

Caution Pas op!

Danger !GEVAAR!

Error Fout

Hint Hint

Important Belangrijk

Note Noot

Tip Tip

Warning Waarschuwing

Seealso Zie ook

rinoh.language.PL = Language('pl', 'Polski')

Localized strings for Polski

SectionTitles

Contents Spis Treści

List_of_figures Spis Ilustracji

List_of_tables Spis Tabel

Chapter Rozdział

Index Skorowidz

AdmonitionTitles

Attention Uwaga!

Caution Ostrożnie!

Danger !NIEBEZPIECZEŃSTWO!

Error Błąd

Hint Wskazówka

Important Ważne

Note Notatka

Tip Porada

Warning Ostrzeżenie

Seealso Zobacz również

8.11 Number (rinoх.number)

Functions for formatting numbers:

- [format_number\(\)](#): Format a number according to a given style.

```
class rinoх.number.NumberFormat
    How (or if) numbers are displayed
    Accepts: none, number, symbol, lowercase character, uppercase character,
              lowercase roman, uppercase roman

class rinoх.number.NumberStyle ( base=None, **attributes )
    Style class for Number
    number_format How numbers are formatted
        Accepts NumberFormat: none, number, symbol, lowercase
                               character, uppercase character, lowercase roman,
                               uppercase roman
        Default: number
    label_prefix Text to prepend to the label (inherited from LabelStyle)
        Accepts StyledText: a list of styled text strings, separated by
                             spaces. A styled text string is a quoted string (' or "),
                             optionally followed by a style name enclosed in braces:
                             'text string' (style name)
        Default: (no value)
    label_suffix Text to append to the label (inherited from LabelStyle)
        Accepts StyledText: a list of styled text strings, separated by
                             spaces. A styled text string is a quoted string (' or "),
                             optionally followed by a style name enclosed in braces:
                             'text string' (style name)
        Default: (no value)
    custom_label Use a custom label if specified (inherited from LabelStyle)
        Accepts Bool: true or false
        Default: false
    hide Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false

class rinoх.number.Label ( custom_label=None )
    Mixin class that formats a label
    Parameters custom_label (StyledText) – a frontend can supply a custom label
              to use instead of an automatically determined label (typically a
              number)

rinoх.number.format_number ( number, format )
    Format number according the given format (NumberFormat)
```

8.12 Paper sizes ([rinoh.paper](#))

The [Paper](#) class and a number of predefined paper formats.

```
class rinoh.paper.Paper ( name, width, height )
```

Defines a paper size.

Parameters

- name ([str](#)) – the name of this paper type
- width ([Dimension](#)) – the (portrait) width of this paper type
- height ([Dimension](#)) – the (portrait) height of this paper type

```
rinoh.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)
```

```
rinoh.paper.A1 = Paper('A1', width=594*MM, height=841*MM)
```

```
rinoh.paper.A2 = Paper('A2', width=420*MM, height=594*MM)
```

```
rinoh.paper.A3 = Paper('A3', width=297*MM, height=420*MM)
```

```
rinoh.paper.A4 = Paper('A4', width=210*MM, height=297*MM)
```

```
rinoh.paper.A5 = Paper('A5', width=148*MM, height=210*MM)
```

```
rinoh.paper.A6 = Paper('A6', width=105*MM, height=148*MM)
```

```
rinoh.paper.A7 = Paper('A7', width=74*MM, height=105*MM)
```

```
rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)
```

```
rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)
```

```
rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)
```

```
rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)
```

```
rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)
```

```
rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH, height=5*INCH)
```

```
rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)
```

```
rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)
```

8.13 Paragraph ([rinoh.paragraph](#))

```
class rinoh.paragraph.ParagraphBase ( custom_label=None, align=None, width=None,  
id=None, style=None, parent=None, source=None )
```

Base class for paragraphs

A paragraph holds styled text and other line elements to be flowed into a container.

style_class alias of [rinoh.paragraph.ParagraphStyle](#)

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
render ( container, descender, state, space_below=0, first_line_only=False )
```

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When

the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

- `container` (`Container`) – the container to render to
- `descender` (`float` or `None`) – descender height of the preceding line
- `state` (`ParagraphState`) – the state where rendering will continue
- `first_line_only` (`bool`) – typeset only the first line

```
class rinoх.paragraph.Paragraph ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )
class rinoх.paragraph.ParagraphState ( paragraph, words, nested_flowable_state=None,
_first_word=None, _initial=True )
```

8.13.1 Styled Text (`rinoх.text`)

```
class rinoх.text.StyledText ( id=None, style=None, parent=None, source=None )
```

Base class for text that has a `TextStyle` associated with it.

```
to_string ( flowable_target )
```

Return the text content of this styled text.

```
is_script ( container )
```

Returns True if this styled text is super/subscript.

```
script_level ( container )
```

Nesting level of super/subscript.

```
height ( container )
```

Font size after super/subscript size adjustment.

```
y_offset ( container )
```

Vertical baseline offset (up is positive).

```
property items The list of items in this StyledText.
```

```
style_class alias of rinoх.text.TextStyle
```

```
class rinoх.text.SingleStyledText ( text, style=None, parent=None, source=None )
```

Text with a single style applied

```
class rinoх.text.MixedStyledText ( text_or_items, id=None, style=None, parent=None,
source=None )
```

Concatenation of styled text

Parameters

- `text_or_items` (`str`, `StyledText` or iterable of these) – mixed styled text
- `style` – see `StyledText`
- `parent` – see `DocumentElement`

```

    prepare ( flowable_target )
        Determine number labels and register references with the
        document

    append ( item ) Append item (StyledText or str) to the end of this
        mixed-styled text.

        The parent of item is set to this mixed-styled text.

    property items The list of items in this StyledText.

    copy ( parent=None )
        Return a shallow copy of the list.

class rinoх.text.Locale
    Selects a language

```

8.13.2 Inline Elements ([rinoх.inline](#))

```

class rinoх.inline.InlineFlowable ( baseline=None, id=None, style=None, parent=None,
source=None )
    style_class alias of rinoх.inline.InlineFlowableStyle

```

8.13.3 Styling Properties

```

class rinoх.paragraph.TextAlign
    Text justification
    Accepts: left, right, center, justify

```

Line Spacing

```

class rinoх.paragraph.LineSpacing
    Base class for line spacing types
    Line spacing is defined as the distance between the baselines of two consecutive
    lines of text in a paragraph.

    advance ( line, last_descender, container )
        Return the distance between the descender of the previous
        line and the baseline of the current line.

```

```

class rinoх.paragraph.DefaultSpacing
    The default line spacing as specified by the font.
    advance ( line, last_descender, container )
        Return the distance between the descender of the previous
        line and the baseline of the current line.

```

```

class rinoх.paragraph.ProportionalSpacing ( factor )
    Line spacing proportional to the line height
    Parameters factor (float) – amount by which the line height is multiplied to
    obtain the line spacing
    advance ( line, last_descender, container )
        Return the distance between the descender of the previous
        line and the baseline of the current line.

```

```

class rinoh.paragraph.FixedSpacing ( pitch, minimum=ProportionalSpacing(1.0) )
    Fixed line spacing, with optional minimum spacing
Parameters
    • pitch (Dimension) – the distance between the baseline of two consecutive lines of text
    • minimum (LineSpacing) – the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to None if no minimum is required, set to None

    advance ( line, last_descender, container )
        Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.Leading ( leading )
    Line spacing determined by the space in between two lines
Parameters leading (Dimension) – the space between the bottom of a line and the top of the next line of text
    advance ( line, last_descender, container )
        Return the distance between the descender of the previous line and the baseline of the current line.

The following standard line spacings have been predefined:
rinoh.paragraph.DEFAULT = DefaultSpacing()
    The default line spacing as specified by the font.
rinoh.paragraph.STANDARD = ProportionalSpacing(1.2)
    Line spacing of 1.2 times the line height.
rinoh.paragraph.SINGLE = ProportionalSpacing(1.0)
    Line spacing equal to the line height (no leading).
rinoh.paragraph.DOUBLE = ProportionalSpacing(2.0)
    Line spacing of double the line height.

```

Tabulation

```

class rinoh.paragraph.TabAlign
    Alignment of text with respect to a tab stop
    Accepts: left, right, center
class rinoh.paragraph.TabStop ( position, align='left', fill=None )
    Horizontal position for aligning text of successive lines
Parameters
    • position (Dimension or Fraction) – tab stop position
    • align (TabAlign) – the alignment of text with respect to the tab stop positon
    • fill (str) – string pattern to fill the empty tab space with

    get_position ( line_width )
        Return the absolute position of this tab stop.

```

```
class rinoх.paragraph.TabStopList ( iterable=(), / )
    List of tab stop positions (with alignment and fill string)
```

8.13.4 Rendering Internals

```
class rinoх.paragraph.Glyph ( glyph, width, char )
class rinoх.paragraph.GlyphsSpan ( span, chars_to_glyphs, glyphs_and_widths=[] )
```

8.13.5 Miscellaneous Internals

```
class rinoх.paragraph.HyphenatorStore
```

8.14 Cross-References and Fields ([rinoх.reference](#))

```
class rinoх.reference.Reference ( target_id, type='number', link=True, style=None, quiet=False,
**kwargs )
class rinoх.reference.ReferenceField ( type='number', link=True, quiet=False, style=None,
parent=None, source=None )
class rinoх.reference.ReferenceText ( id=None, style=None, parent=None, source=None )
class rinoх.reference.ReferenceType
    Accepts: reference, number, title, page
class rinoх.reference.ReferencingParagraph ( target_id_or_flowable, id=None, style=None,
parent=None )
    style_class alias of rinoх.reference.ReferencingParagraphStyle
    target_style ( document )
        Filter selection on the style attribute of the target flowable
    target_has_class ( document )
        Filter selection on a class of the target flowable
    target_has_classes ( document )
        Filter selection on a set of classes of the target flowable
class rinoх.reference.Note ( flowable, id=None, style=None, parent=None )
class rinoх.reference.RegisterNote ( note, parent=None )
    prepare ( flowable_target )
        Determine number labels and register references with the
        document
class rinoх.reference.NoteMarkerBase ( custom_label=None, **kwargs )
    style_class alias of rinoх.reference.NoteMarkerStyle
    prepare ( flowable_target )
        Determine number labels and register references with the
        document
class rinoх.reference.NoteMarkerByID ( target_id, type='number', link=True, style=None,
quiet=False, **kwargs )
```

```

class rinoх.reference.NoteMarkerWithNote ( referenceable, type='number', link=False,
style=None, **kwargs )
    prepare ( flowable_target )
        Determine number labels and register references with the
        document
class rinoх.reference.Field ( type, id=None, style=None, parent=None, source=None )

```

8.15 Structure ([rinoх.structure](#))

8.15.1 Sections

```

class rinoх.structure.Section ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )
    A subdivision of a document
    A section usually has a heading associated with it, which is optionally
    numbered.
class rinoх.structure.Heading ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )
    The title for a section
    Parameters title (StyledText) – this heading's text
    style_class alias of rinoх.structure.HeadingStyle
    prepare ( container )
        Determine number labels and register references with the
        document
    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical
        space consumed.
        The flowable's contents are preceded by a vertical space
        with a height as specified in its style's space_above
        attribute. Similarly, the flowed content is followed by a
        vertical space with a height given by the space_below style
        attribute.
class rinoх.structure.SectionTitles ( **strings )
    Collection of localized titles for common sections
    contents Title for the table of contents section
        Type String
    list_of_figures Title for the list of figures section
        Type String
    list_of_tables Title for the list of tables section
        Type String
    chapter Label for top-level sections
        Type String
    index Title for the index section
        Type String

```

8.15.2 Lists

```
class rinoх.structure.List ( list_items, start_index=1, id=None, style=None, parent=None )
    style_class alias of rinoх.structure.ListStyle
class rinoх.structure.DefinitionList ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )
```

8.15.3 Table of Contents

```
class rinoх.structure.TableOfContentsSection
class rinoх.structure.TableOfContents ( local=False, id=None, style=None, parent=None )
    style_class alias of rinoх.structure.TableOfContentsStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoх.structure.TableOfContentsEntry ( flowable, id=None, style=None, parent=None )
    style_class alias of rinoх.structure.TableOfContentsEntryStyle
```

8.15.4 Admonitions

```
class rinoх.structure.Admonition ( flowables, title=None, type=None, id=None, style=None,
parent=None )
    style_class alias of rinoх.structure.AdmonitionStyle
    flowables ( container )
        Generator yielding the Flowables to group
class rinoх.structure.AdmonitionTitles ( **strings )
    Collection of localized titles for common admonitions
    attention Title for attention admonitions
        Type String
    caution Title for caution admonitions
        Type String
    danger Title for danger admonitions
        Type String
    error Title for error admonitions
        Type String
    hint Title for hint admonitions
        Type String
    important Title for important admonitions
        Type String
    note Title for note admonitions
        Type String
    tip Title for tip admonitions
        Type String
```

```
warning Title for warning admonitions
    Type String
seealso Title for see-also admonitions
    Type String
```

8.15.5Horizontal Rule

```
class rinoh.structure.HorizontalRule ( align=None, width=None, id=None, style=None,
parent=None, source=None )
    style_class alias of rinoh.structure.HorizontalRuleStyle
    render ( container, descender, state, **kwargs )
        Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.
```

8.16 Strings ([rinoh.strings](#))

```
class rinoh.strings.String ( description )
    Descriptor used to describe a configurable string
    Parameters description (str) – a short description for this string
class rinoh.strings.StringCollection ( **strings )
    A collection of related configurable strings
    Subclasses
        • AdmonitionTitles
        • SectionTitles
        • UserStrings
class rinoh.strings.UserStrings ( **strings )
    Collection of user-specified strings
    Unlike other string collections, these are not limited to a predefined set.
    Attributes:
class rinoh.strings.Strings ( *string_collections )
    Stores several StringCollections
class rinoh.strings.StringField ( strings_class, key, style=None, parent=None, source=None )
    Styled text that will be substituted with a configured string
    The displayed string is either the localized string as determined by the language set for the document or the user-supplied string passed to the TemplateConfiguration.
```

8.17 Style ([rinoh.style](#))

```
class rinoh.style.Styled ( id=None, style=None, parent=None, source=None )
    A document element who's style can be configured.
```

Parameters style ([str](#), [Style](#)) – the style to associate with this element. If style is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class The [Style](#) subclass that corresponds to this [Styled](#) subclass.

property has_class

Filter selection on a class of this [Styled](#)

property has_classes

Filter selection on a set of classes of this [Styled](#)

```
class rino.style.Style ( base=None, **attributes )
```

Dictionary storing style attributes.

The style attributes associated with this [Style](#) are specified as class attributes of type [Attribute](#).

Style attributes can also be accessed as object attributes.

hide Suppress rendering this element

Accepts [Bool](#): true or false

Default: false

8.17.1 Style Sheet

```
class rino.style.StyleSheet ( name, matcher=None, base=None, source=None, description=None, pygments_style=None, **user_options )
```

Dictionary storing a collection of related styles by name.

[Styles](#) stored in a [StyleSheet](#) can refer to their base style by name.

Parameters

- name ([str](#)) – a label for this style sheet
- matcher ([StyledMatcher](#)) – the matcher providing the selectors the styles contained in this style sheet map to. If no matcher is given and base is specified, the base's matcher is used. If base is not set, the default matcher is used.
- base ([StyleSheet](#) or [str](#)) – the style sheet to extend
- description ([str](#)) – a short string describing this style sheet
- pygments_style ([str](#)) – the Pygments style to use for styling code blocks

```
get_selector ( name )
```

Find a selector mapped to a style in this or a base style sheet.

Parameters name ([str](#)) – a style name

Returns Selector – the selector mapped to the style name

Raises [KeyError](#) – if the style name was not found in this or a base style sheet

```
class rino.style.StyleSheetFile ( filename, base=None, source=None, **kwargs )
```

Loads styles defined in a .rts file (INI format).

Parameters filename ([str](#)) – the path to the style sheet file

`StyleSheetFile` takes the same optional arguments as `StyleSheet`. These can also be specified in the [STYLESHEET] section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

```
class rinoх.style.StyledMatcher ( mapping_or_iterable=None, **kwargs )
```

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a `dict` by passing a mapping, an iterable and/or keyword arguments.

```
update ( **F [ , E ] ) → None. Update D from dict/iterable E and F.
```

If E is present and has a `.keys()` method, then does: for k in E: D[k] = E[k] If E is present and lacks a `.keys()` method, then does: for k, v in E: D[k] = v In either case, this is followed by: for k in F: D[k] = F[k]

8.18 Tables (`rinoh.table`)

```
class rinoх.table.Table ( body, head=None, align=None, width=None, column_widths=None, id=None, style=None, parent=None )
```

style_class alias of `rinoh.table.TableStyle`

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
render ( container, last_descender, state, space_below=0, **kwargs )
```

Renders the flowable's content to container, with the flowable's top edge lining up with the container's cursor. descender is the descender height of the preceding line or None.

```
class rinoх.table.TableWithCaption ( flowables, align=None, width=None, id=None, style=None, parent=None, source=None )
```

style_class alias of `rinoh.table.TableWithCaptionStyle`

```
class rinoх.table.TableSection ( rows, style=None, parent=None )
```

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
class rinoх.table.TableHead ( rows, style=None, parent=None )
```

```
class rinoх.table.TableBody ( rows, style=None, parent=None )
```

```
class rinoх.table.TableRow ( cells, style=None, parent=None )
```

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
get_rowspanned_columns ( )
```

Return a dictionary mapping column indices to the number of columns spanned.

```
class rinoх.table.TableCell ( flowables, rowspan=1, colspan=1, id=None, style=None, parent=None )
```

style_class alias of `rinoh.table.TableCellStyle`

```

class rinohtable.TableCellBorder ( rendered_cell, cell_height, position, style=None )
    style_class alias of rinohtable.TableCellBorderStyle
class rinohtable.TableCellBackground ( bottom_left, width, height, style=None, parent=None )
    style_class alias of rinohtable.TableCellBackgroundStyle
class rinohtable.VerticalAlign
    Accepts: top, middle, bottom
class rinohtable.ListOfTables ( local=False, id=None, style=None, parent=None )
class rinohtable.ListOfTablesSection
    list_class alias of rinohtable.ListOfTables

```

8.19 Templates (rinohtemplate)

Document templates are created by subclassing [DocumentTemplate](#), just like the [standard templates](#) shipped with rinohtype.

```
class rinohtemplate.DocumentTemplate ( document_tree, configuration=None, backend=None )
```

Template for documents

Parameters

- `document_tree` ([DocumentTree](#)) – a tree of the document's contents
- `configuration` ([TemplateConfiguration](#)) – configuration for this template
- `backend` – the backend used for rendering the document

`language` The main language of the document

Accepts [Language](#): the code of one of the [supported languages](#)

Default: [EN](#) (English)

`strings` Strings to override standard element names

Accepts [Strings](#): strings need to be entered in INI sections named after the [StringCollection](#) subclasses

Default: none

`stylesheet` The stylesheet to use for styling document elements

Accepts [StyleSheet](#): the name of an [installed style sheet](#) or the file-name of a stylesheet file (with the .rts extension)

Default: [sphinx](#) (= [rinohtemplate.stylesheets.sphinx](#))

`parts` The parts making up this document

Accepts [PartsList](#): a space-separated list of document part template names

Default: (empty list)

`Configuration` alias of [rinohtemplate.DocumentTemplateConfiguration](#)

`ConfigurationFile` alias of [rinohtemplate.DocumentTemplateConfigurationFile](#)

Document templates can be customized by setting values for the configuration attributes defined in a [DocumentTemplate](#) subclass in a [TemplateConfiguration](#). An template configura-

tion can be passed as configuration on template instantiation. However, it is better to make use of the `document` method, however.

```
class rinohtemplate.TemplateConfiguration ( name, base=None, source=None, template=None, description=None, **options )
```

Stores a configuration for a `DocumentTemplate`

Parameters

- `name` (`str`) – a label for this template configuration
- `base` (`TemplateConfiguration`) – the template configuration to extend
- `template` (`DocumentTemplateMeta` or `str`) – the document template to configure
- `description` (`str`) – a short string describing this style sheet
- `**options` – configuration values for the configuration attributes defined by the document `template`

`template = None` The `DocumentTemplate` subclass to configure

```
document ( document_tree, backend=None )
```

Create a `DocumentTemplate` object based on the given document tree and this template configuration

Parameters

- `document_tree` (`DocumentTree`) – tree of the document's contents
- `backend` – the backend to use when rendering the document

```
class rinohtemplate.PartsList ( *parts )
```

Stores the names of the document part templates making up a document

```
Parameters *parts (list[str]) – the names of the document parts
```

8.19.1 Document Parts

```
class rinohtemplate.DocumentPart ( template, document, flowables )
```

Part of a document.

Parameters

- `template` (`DocumentPartTemplate`) – the template that determines the contents and style of this document part
- `document` (`Document`) – the document this part belongs to
- `flowables` (`list[Flowable]`) – the flowables to render in this document part

`configuration_class`

alias of `rinohtemplate.DocumentPartTemplate`

```
add_page ( page )
```

Append page (`Page`) to this `DocumentPart`.

```
new_page ( page_number, new_chapter, **kwargs )
```

Called by `render()` with the Chain's that need more

:class:`Container`'s. This method should create a new :class:`Page` which contains a container associated with chain.

The document part templates which are listed by name in [DocumentTemplate.parts](#) are looked up as attributes of the [DocumentTemplate](#) subclass. They are instances of [DocumentPartTemplate](#) subclasses:

```
class rinoth.template.DocumentPartTemplate ( base=None, **attributes )
```

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the [TemplateConfiguration](#) where this part template was.

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on

Accepts [PageType](#): left, right, any

Default: any

drop_if_empty Exclude this part from the document if it is empty (no flowables)

Accepts [Bool](#): true or false

Default: true

The following document part templates are used in the standard document templates:

```
class rinoth.template.TitlePartTemplate ( base=None, **attributes )
```

The title page of a document.

drop_if_empty Overrides the default set in [DocumentPartTemplate](#)

Accepts [Bool](#): true or false

Default: false

page_number_format

The format for page numbers in this document part. If it is different from the preceding part's number format, numbering restarts at 1 (inherited from [DocumentPartTemplate](#))

Accepts [NumberFormat](#): none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

end_at_page The type of page to end this document part on (inherited from [DocumentPartTemplate](#))

Accepts [PageType](#): left, right, any

Default: any

```
class rinohtemplate.ContentsPartTemplate ( base=None, **attributes )
    The body of a document.
    Renders all of the content present in the DocumentTree passed to the
    DocumentTemplate.
    page_number_format
        The format for page numbers in this document part. If it is
        different from the preceding part's number format,
        numbering restarts at 1 (inherited from
        DocumentPartTemplate)
        Accepts NumberFormat: none, number, symbol, lowercase
        character, uppercase character, lowercase roman, uppercase
        roman
        Default: number
    end_at_page The type of page to end this document part on (inherited from
        DocumentPartTemplate)
        Accepts PageType: left, right, any
        Default: any
    drop_if_empty Exclude this part from the document if it is empty (no flow-
        ables) (inherited from DocumentPartTemplate)
        Accepts Bool: true or false
        Default: true
class rinohtemplate.FixedDocumentPartTemplate ( base=None, **attributes )
    A document part template that renders a fixed list of flowables
    flowables The list of flowables to include in this document part
        Accepts FlowablesList: Python source code that represents a list of
        Flowables
        Default: []
    page_number_format
        The format for page numbers in this document part. If it is
        different from the preceding part's number format,
        numbering restarts at 1 (inherited from
        DocumentPartTemplate)
        Accepts NumberFormat: none, number, symbol, lowercase
        character, uppercase character, lowercase roman, uppercase
        roman
        Default: number
    end_at_page The type of page to end this document part on (inherited from
        DocumentPartTemplate)
        Accepts PageType: left, right, any
        Default: any
    drop_if_empty Exclude this part from the document if it is empty (no flow-
        ables) (inherited from DocumentPartTemplate)
        Accepts Bool: true or false
        Default: true
```

8.19.2 Page Templates

The document templates make use of page templates:

```
class rinohtemplate.PageTemplate ( base=None, **attributes )  
    header_footer_distance  
        Distance of the header and footer to the content area  
        Accepts Dimension: a numeric value followed by a unit  
        (pt, in, pc, mm, cm, %, /2, /4)  
        Default: 14pt  
    columns The number of columns for the body text  
        Accepts Integer: a natural number (positive integer)  
        Default: 1  
    column_spacing The spacing between columns  
        Accepts Dimension: a numeric value followed by a unit (pt,  
        in, pc, mm, cm, %, /2, /4)  
        Default: 1cm  
    header_text The text to place in the page header  
        Accepts StyledText: a list of styled text strings, separated by  
        spaces. A styled text string is a quoted string (' or "), optionally  
        followed by a style name enclosed in braces: 'text string' (style  
        name)  
        Default: '{SECTION_NUMBER(1)}' '' '{SECTION_TITLE(1)}'  
    footer_text The text to place in the page footer  
        Accepts StyledText: a list of styled text strings, separated by  
        spaces. A styled text string is a quoted string (' or "), optionally  
        followed by a style name enclosed in braces: 'text string' (style  
        name)  
        Default: '\t'{PAGE_NUMBER}' /' '{NUMBER_OF_PAGES}'  
    chapter_header_text  
        The text to place in the header on a page that starts a new  
        chapter  
        Accepts StyledText: a list of styled text strings, separated  
        by spaces. A styled text string is a quoted string (' or "),  
        optionally followed by a style name enclosed in braces:  
        'text string' (style name)  
        Default: (no value)  
    chapter_footer_text  
        The text to place in the footer on a page that starts a new  
        chapter  
        Accepts StyledText: a list of styled text strings, separated  
        by spaces. A styled text string is a quoted string (' or "),  
        optionally followed by a style name enclosed in braces:  
        'text string' (style name)  
        Default: (no value)
```

`chapter_title_flowables`

Generator that yields the flowables to represent the chapter title

Accepts `FlowablesList`: Python source code that represents a list of `Flowables`

Default: none

`chapter_title_height`

The height of the container holding the chapter title

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 150pt

`page_size` The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a `predefined paper format` or <width> * <height> where width and height are `Dimensions`

Default: A4

`page_orientation` The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

`left_margin` The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`right_margin` The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`top_margin` The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`bottom_margin` The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`background` An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

`after_break_background`

An image to place in the background after a page break
(inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

`class rinoх.template.TitlePageTemplate (base=None, **attributes)`

`show_date` Show or hide the document's date

Accepts [Bool](#): true or false

Default: true

`show_author` Show or hide the document's author

Accepts [Bool](#): true or false

Default: true

`extra` Extra text to include on the title page below the title

Accepts [StyledText](#): a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

`page_size` The format of the pages in the document (inherited from [PageTemplateBase](#))

Accepts [Paper](#): the name of a [predefined paper format](#) or `<width> * <height>` where width and height are [Dimensions](#)

Default: A4

`page_orientation` The orientation of pages in the document (inherited from [PageTemplateBase](#))

Accepts [PageOrientation](#): portrait, landscape

Default: portrait

`left_margin` The margin size on the left of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`right_margin` The margin size on the right of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`top_margin` The margin size at the top of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`bottom_margin` The margin size at the bottom of the page (inherited from [PageTemplateBase](#))

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`background` An image to place in the background of the page (inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

`after_break_background`

An image to place in the background after a page break (inherited from [PageTemplateBase](#))

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

The base class for these collects the common options:

```
class rinoth.template.PageTemplateBase ( base=None, **attributes )
```

`page_size` The format of the pages in the document

Accepts [Paper](#): the name of a [predefined paper format](#) or `<width> * <height>` where width and height are [Dimensions](#)

Default: A4

`page_orientation` The orientation of pages in the document

Accepts [PageOrientation](#): portrait, landscape

Default: portrait

`left_margin` The margin size on the left of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`right_margin` The margin size on the right of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`top_margin` The margin size at the top of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`bottom_margin` The margin size at the bottom of the page

Accepts [Dimension](#): a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

`background` An image to place in the background of the page

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

`after_break_background`

An image to place in the background after a page break

Accepts [BackgroundImage](#): filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (`<keyword>=<value>`) that determine how the image is displayed

Default: none

Frequently Asked Questions

9

Below is the start of a list of commonly encountered problems and solutions to them. You can also find answers to usage questions on rinohtype on [StackOverflow](#).

PDFs produced by rinohtype contain mostly empty pages. What's up? Old versions of some PDF viewers do not support the way rinohtype embeds fonts in a PDF (see [issue 2](#)). PDF viewers that are known to be affected are:

- pre-37.0 Firefox's built-in PDF viewer (pdf.js)
- pre-0.41 [poppler](#)-based applications such as Evince

Contributing

10

Thank you for considering contributing to rinohtype! This document contains some general information with respect to contributions. Please refer to DEVELOPING.rst for specific information on running tests etc.

10.1 Contributor License Agreement

Please send your contributions by creating a pull request on GitHub. You will be asked to agree to the [contributor license agreement](#). Why, you might ask? In the past, I had plans to sell a commercial version of rinohtype. This version would basically be the same as the open source version, but with the addition of a closed-source backend for the DITA format. While I'm no longer actively pursuing these plans at this point, I would like to keep this option open. In combination with the Afferro GPL, the CLA allows me to include contributions by others in this commercial version while preventing others from releasing commercial closed-source versions of rinohtype. Additionally, the CLA protects the project from legal risks. Since I'm no legal expert, I adapted the contributor license agreement from [Project Harmony](#). You can find a quick summary and a detailed walkthrough of the license in the [guide](#).

10.2 Coding guidelines

Please follow the coding style used in the existing codebase, which generally follows the [PEP 8](#) style guide. Here are the most important rules the codebase conforms to:

- lines are wrapped at 80 columns
- 4 spaces indentation (no tabs)
- descriptive variable/function/class names (not shortened)
- imports are grouped into sections: standard library, external packages and rinohtype modules
- minimize use of external dependencies

This project makes use of [tox](#) to manage running tests and other tasks. The tests can be divided into three categories: checks, unit tests and regression (integration) tests. tox.ini defines “environments” that configure these tasks. Each of these are described in the next section. The unit and regression tests make use of [pytest](#).

The repository includes a [Poetry](#) pyproject.toml file to help you set up a virtual environment with tox and other development dependencies. From the repository checkout root directory execute:

```
poetry install
```

Poetry will create a virtual environment in .venv, which you can activate like this³:

```
source .venv/bin/activate
```

Now tox is available for running the tests. Starting tox without any arguments will run the check, unit and regression environments. Refer to the next section for an overview of all environments.

11.1 Tox Environments

The following environments execute unit tests and regression tests:

unit Runs the unit tests.

regression Runs integration/regression tests. Each of these tests render a tiny document (often a single page) focusing on a specific feature, which means they also execute quickly. Their PDF output is compared to a reference PDF that is known to be good.

longrunning (not maintained, broken) Runs regressions tests that render larger documents. These tests take several minutes to complete.

The other environments run checks, build documentation and build “binary” distributions for Mac and Windows:

check Performs basic checks; just poetry check at this point.

check-docs Perform checks on the documentation source files using [doc8](#) and [sphinx-doctest](#). [restview](#) can be useful when fixing syntax errors in README.rst, CHANGES.rst, ...

build-docs Build the rinohtype documentation using Sphinx, both in HTML and PDF formats.

macapp (not maintained, broken?) Build a stand-alone macOS application bundle using [briefcase](#). This task can only be run on macOS.

³ If you install [direnv](#), the virtual environment can be automatically activated when you enter the rinohtype repository checkout (see the .envrc file).

wininst (not maintained, broken?) Build a stand-alone rinohtype installer for the Windows platform with the help of [pynsist](#). This task also can be run on other platforms than Windows.

Customization settings for [doc8](#) and [pytest](#) are stored in `setup.cfg`.

11.2 Testing against multiple Python interpreter versions

Tox facilitates running tests on multiple Python interpreter versions. You can combine the test environment names with a [factor](#) to execute them on a specific Python interpreter version. For example, to run the unit tests on CPython 3.8:

```
tox -e unit-py38
```

While it is typically sufficient to test on a single Python version during development, it can be useful to run tests on a set of Python versions before pushing your commits. Of course, this requires these versions to be available on your machine. It is highly recommended you use [pyenv](#) (or [pyenv-win](#)) to install and manage these. For example, to install CPython 3.8.1, you can run:

```
pyenv install 3.8.1
```

and pyenv will download, build and install this version of CPython for you. pyenv will install the different Python versions in an isolated location (typically under `~/.penv`), so they will not interfere with your system-default Python versions.

The file `.python-version` in the root of the repository specifies which Python versions pyenv should make available whenever we are inside the repository checkout directory. The file lists specific the versions of CPython rinohtype aims to support plus recent PyPy3 versions (ideally, we should closely track the latest releases). The `pyenv_install.py` script can install these for you (skipping any that are already installed).

11.3 Continuous integration

[GitHub Actions](#) automatically executes the tox environments when new commits are pushed to the repository. The tox environments are run on Linux, macOS and Windows, and run the tests on an array of Python versions to make sure that we don't break any corner cases. See `.github/-workflows` for details.

11.4 Making a release

This is a list of steps to follow when making a new release of rinohtype. Publishing the new release to [PyPI](#) and uploading the documentation to GitHub Pages is handled by the GitHub Actions workflow.

1 Make sure your checkout is clean.

2 Run run tests and checks locally:

```
tox -e check,check-docs,build-docs,unit,regression
```

3 Push your commits to master on GitHub. Don't create a tag yet!

4 Check whether all tests on [GitHub Actions](#) are green.

5 Set the release date.

- set `__release_date__` in `src/rinoh/__init__.py` (YYYY-MM-DD)
- add release date to this release's section (see other sections for examples)

6 Create a git tag: `git tag v$(poetry version --short)`

7 Push the new tag: `git push origin v$(poetry version --short)`

8 The GitHub workflow will run all tox environments and upload the new version to PyPI if all checks were successful.

9 Create a [new release on GitHub](#). Include the relevant section of the changelog. Use previous releases as a template.

- Tag version: the release's tag `vx.y.z`
- Release title: Release `x.y.z` (date)
- Add a link to the release on PyPI:

```
Install from [PyPI] (https://pypi.org/project/rinohtype/x.y.z/)
```

- Copy the release notes from the change log

10 Bump version number and reset the release date to "upcoming".

- poetry version patch # or 'minor'
- add new section at the top of the changelog
- set `__release_date__` in `src/rinoh/__init__.py` to 'upcoming'

12.1 Release 0.5.1 (2021-02-19)

New Features:

- Paragraphs can now be numbered. rinohtype also allows for referencing them by number, but docutils/Sphinx doesn't readily offer the means express that. A workaround for this will be included in a future release.

Fixed:

- Fix issues with metadata (title, author) stored in the PDF Info dictionary
- Fix handling of no-break spaces (they were rendered using the fallback font)
- When a caption occurs in an unnumbered chapter, an exception aborts rendering (even when number_separator style attribute is set to None)
- Handling of base template specified as string in a template configuration
- Table column widths entries now also accept fractions

Part of the work included in this release was kindly sponsored by [Joby Aviation](#).

12.2 Release 0.5.0 (2021-02-03)

New Features:

- Google Fonts: if a specified typeface is not installed, rinohtype attempts to download the corresponding fonts from Google Fonts. Simply supply the font name as listed on <https://fonts.googleapis.com> as a value for the typeface style property.
- Table: in addition to fixed and relative-width columns, you can indicate columns to be automatically sized by specifying a value of 'auto' in the 'column_widths' style parameter in your style sheet.
- docutils frontend: support the :align: option to table directives, which will override the alignment set for the table in the style sheet.
- The starting number of enumerated lists in reStructuredText is respected.
- Table column widths can be specified in the style sheet, which take effect when these

haven't been specified in the source document.

- Document elements now store where they have been defined (document tree, style sheet file or template configuration file); when you specify relative paths (e.g. for images), they are interpreted relative to the location of their source. This should make things more intuitive.
- The `page_break` style attribute is no longer reserved for sections; a page break can be forced before any flowable.
- Enumerated list items with a hidden label ('`hide`' style attribute) are no longer counted in the numbering.
- Templates and typefaces can be registered by name at runtime. This makes them referencable from template configuration and style sheet files. For example, custom templates/-typefaces can be imported in a Sphinx project's `conf.py` (to be documented).
- It's now possible to add arbitrary `reStructuredText` content to the front/back matter or elsewhere by adding a `.. container::` with the 'out-of-line' class and a `:name:` to reference it by in the document template configuration, e.g. in the list of front matter flowables (to be documented).
- Selectors in style sheet files (`.rts`) now support boolean and 'None' values. For example, you can select `StaticGroupedFlowables` based on whether they have any children or not: e.g `TableCell(empty=True)` selects empty table cells.
- The document's title and author are now stored in the PDF metadata.
- "0" is now accepted as a valid value for Dimension-type attributes in style sheets and template configurations.

Changed:

- Rendering speed was more than doubled (caching)! (PR #197 by Alex Fargus)
- Sphinx frontend: `rino_documents` now takes a list of dictionaries, one for each PDF document to be built. This allows selecting e.g. the template and logo on a per-document level. Support for `rino_template`, `rino_stylesheet`, `rino_paper_size`, `rino_domain_indices` and `rino_logo` was removed. Fallback to `latex_documents` is retained. (PR #182, #192, #195, #208 and #216 by Alex Fargus)
- The default stylesheet ('Sphinx') now prevents captions from being separated from their image/table/code block (across pages).
- Font weights and widths are now internally represented by integer classes. In addition to integer values, string values are still accepted (mapped to classes).
- `OpenTypeFont` now determines the font weight, slant and width from the file. For backward compatibility, it still accepts these as arguments on instantiation but warns when they don't match the values stored in the font.

Fixed:

- Table column width determination was overhauled. Now fixed-width tables are supported and automatic-width columns should be handled better.
- The 'nested bulleted/enumerated list' selectors were broken; their corresponding styles were never applied
- Items inside a table cannot be referenced (issue #174)

- Sphinx frontend: fix handling of relative image paths in .rst files inside a directory in the Sphinx project root
- rino: fix –install-resources (broken since PyPI disabled XMLRPC searches)
- GroupedLabeledFlowables: respect label_min_width and fix a crash with respect to space_below handling
- Duplicate rendering of content in columns; if content was too small to fill the first column, it was rendered again in subsequent columns.
- Crash on encountering a style for which no selector is defined.

Part of the work included in this release was kindly sponsored by [Joby Aviation](#).

12.3 Release 0.4.2 (2020-07-28)

New Features:

- before/after style attributes for StyledText (issue #158)
- docutils/Sphinx frontend: don't abort on encountering math/math_block, output the (LaTeX) math markup instead, along with printing a warning.
- docutils frontend: raw inline text (with :format: 'rino') is parsed as styled text

Fixed:

- crash when the 'contents' topic has multiple IDs (issue #173)
- loading of the references cache (issue #170)
- some issues with space_below handling

12.4 Release 0.4.1 (2020-07-01)

New Features:

- UserStrings: arbitrary user-defined strings that can be defined in the template configuration or as a substitution definition in reStructuredText
- strings in a StringCollection can now be styled text
- Sphinx frontend: use the today and today_fmt configuration variables for the date on the title page
- Sphinx frontend: allow extensions access to the builder object (issue #155)
- rino: --output writes the output PDF to a specified location

Fixed:

- Regression in handling images that don't fit on the current page (issue #153)
- Fix crash when rendering local table of contents (issue #160)

- Sphinx frontend: support code-block/literalinclude with caption (issue #128)
- rinoH: variables set in a template configuration file are sometimes ignored (issue #164)
- Crash when using a font that contains unsupported lookups (issue #141)

12.5 Release 0.4.0 (2020-03-05)

New Features:

- automatically generated lists of figures and tables
- paragraphs now provide default tab stops (proportional to font size) for indentation
- stylesheet (.rts) and template configuration (.rtt) files now support specifying inline and background images (#107 and #108); to be documented
- it is now possible to specify selector priority (+-) in style sheets
- Sphinx frontend: the rinoH builder can be discovered by entry point (no more need to add 'rinoH.frontend.sphinx' to the list of extensions)
- rinoH: set a return code of 1 when one or more referenced images could not be found (issue #104)
- rinoH: introduce the --install-resources option to control the automatic installation of resources from PyPI
- German locale (contributed by Michael Kaiser)
- Polish locale (contributed by Mariusz Jamro)

Changed:

- Python 3.3 & 3.4 are no longer supported since they have reached end-of-life
- remove the dependency on purepng by embedding its png.py
- limit the width of images to the available width by default
- XML frontend: special case mixed content nodes
- fixes in the design of stylesheet/template code

Fixed:

- various regressions (PR #142 by Norman Lorrain)
- fix issues with variables defined in a base style sheet/template config
- various footnote rendering issues
- border width is also taken into account for flowables that are continued on a new page (#127)
- Sphinx: handle case when source_suffix is a list (PR #110 by Nick Barrett)
- incompatibility with Sphinx 1.6.1+ (latex_paper_size)

- docutils: crash when a footnote is defined in an admonition (issue #95)
- docutils: crash on encountering a raw text role (issue #99)
- docutils: ‘decoration’ node (header/footer) is not yet supported (issue #112)
- crash when a table cell contains (only) an image
- colours of PNG images with gamma (gAMA chunk) set are incorrect (#102)
- Sphinx: image paths with wildcard extension are not supported (#119)
- GroupedFlowables: space_below should only be considered at the end
- adapt to PEP 479 (Change StopIteration handling inside generators), the default in Python 3.7 (issue #133)
- fix compatibility with Python 3.6.7 and 3.7.1 (tokenizer changes)
- fix crash caused by Python 3.8’s changes to int.__str__

12.6 Release 0.3.1 (2016-12-19)

New Features:

- rinoth is now also available as a stand-alone application for both Windows (installer) and macOS (app); they include an embedded CPython installation
- index terms can be StyledText now (in addition to str)
- the ‘document author’ metadata entry can now be displayed using a Field
- Sphinx frontend: support the ‘desc_signature_line’ node (new in Sphinx 1.5)
- rinoth –docs: open the online documentation in the default browser

Changed:

- more closely mimic the Sphinx LaTeX builder’s title page (issue #60)
- there is no default for PageTemplate.chapter_title_flowables anymore since they are specific to the document template

Fixed:

- handle StyledText metadata (such as document title)
- Sphinx frontend: support the ‘autosummary_toc’ node
- DummyFlowable now sticks to the flowable following it (keep_with_next), so that (1) it does not break this behavior of Heading preceding it, and (2) IndexTargets do not get separated from the following flowable
- bug in LabeledFlowable that broke keep_with_next behavior
- the descender size of the last flowable in a GroupedFlowables with keep_with_next=True was getting lost

- GroupedFlowables should not mark the page non-empty; this caused empty pages before the first chapter if it is preceded by grouped DummyFlowables

12.7 Release 0.3.0 (2016-11-23)

New Features:

- support localization of standard document strings (en, fr, it, nl) (#53)
- localized strings can be overridden in the document template configuration
- make use of a fallback typeface when a glyph is not available (#55) (the ‘fallback’ style in the Sphinx stylesheet sets the fallback typeface)
- template configuration (INI) files: specify which document parts to include, configure document part and page templates, customize localized strings, ...
- support specifying more complex selectors directly in a style sheet file
- (figure and table) captions support hierarchical numbering (see `CaptionStyle`)
- make the frontends independent of the current working directory
- `reStructuredText`: support the table `:widths:` option (upcoming `docutils` 0.13)
- Sphinx frontend: provide styles for Sphinx’s inline markup roles
- `rino` (command line renderer):
 - support template configuration files
 - support file formats for which a frontend is installed (see `-list-formats`)
 - accept options to configure the frontend (see `-list-options`)
 - option to list the installed fonts (on the command line or in a PDF file)
- show the current page number as part of the rendering progress indicator
- Book template: support for setting a cover page
- frontends: raise a more descriptive exception when a document tree node is not mapped
- validate the default value passed to an Attribute
- preliminary support for writing a style sheet to an INI file, listing default values for non-specified attributes (#23)

Changed:

- `rino`: the output PDF is now placed in the current directory, not in the same directory as the input file
- Sphinx builder configuration: replace the `rino_document_template` and `rino_template_-configuration` options with `rino_template`
- if no base is given for a style, style attribute lookup proceeds to look in the style of the same name in the base style sheet (#66)

- DEFAULT_STYLE can be used as a base style to prevent style attribute lookup in the style of the same name in the base style sheet
- rename FieldList to DefinitionList and use it to replace uses (docutils and Sphinx frontends) of the old DefinitionList (#54)
- the new DefinitionList (FieldList) can be styled like the old DefinitionList by setting max_label_width to None, 0 or a 0-valued Dimension
- figures are now non-floating by default (float placement needs more work)
- hide the index chapter when there are no index entries (#51)
- style sheets: use the default matcher if none is specified
- Sphinx style sheet: copy the admonition style from the Sphinx LaTeX builder
- Sphinx style sheet: keep the admonition title together with the body
- Sphinx style sheet: color linked references as in the LaTeX output (#62)
- Sphinx style sheet: disable hyphenation/ligatures for literal strong text
- no more DocumentSection; a document now consists of parts (containing pages)
- template configuration:
 - refer to document part templates by name so that they can be replaced
 - the list of document parts can be changed in the template configuration
 - document parts take the 'end_at_page' option (left, right, or any)
 - find (left/right) page templates via the document part name they belong to
 - fall back to <doc_part>_page when the right or left template is not found
 - each template configuration requires a name
- DocumentTree: make the source_file argument optional
- don't abort when the document section hierarchy is missing levels (#67)
- use the PDF backend by default (no need to specify it)
- store the unit with Dimension instances (better printing)
- rename the float module to image

Fixed:

- improve compatibility with Windows: Windows path names and file encoding
- crash if a StyledText is passed to HeadingStyle.number_separator
- GroupedLabeledFlowables label width could be unnecessarily wide
- fix and improve automatic table column sizing
- Figures can now be referenced using the 'reference' format ("Figure 1.2")

- HorizontallyAlignedFlowable: make more robust
- make document elements referenceable by secondary IDs
- reStructuredText: only the first classifier for a definition term was shown
- Sphinx frontend: support the ‘centered’ directive
- Sphinx frontend: basic support for the ‘hlist’ directive
- Sphinx frontend: handle :abbr: without explanation
- Sphinx frontend: support nested inline nodes (guilabel & samp roles)
- PDF backend: fix writing of Type 1 fonts from a parsed PDF file
- PDF reader: handle multi-page PDFs (#71)
- PDF reader: fix parsing of XRef streams
- PDF reader: fix writing of parsed files

12.8 Release 0.2.1 (2016-08-18)

New Features:

- optionally limit the width of large images and make use of this to simulate the Sphinx LaTeX builder behavior (#46)
- reStructuredText/Sphinx: support for images with hyperlinks (#49)
- record the styled page numbers in the PDF as page labels (#41)
- unsupported Python versions: prevent installation where possible (sdist) or exit on import (wheel)
- support Python 3.6

Bugfixes:

- make StyleSheet objects pickleable so the Sphinx builder’s rinoht_stylesheet option can actually be used
- Fix #47: ClassNotFound exception in Literal_Block.lexer_getter()
- Fix #45: Images that don’t fit are still placed on the page
- don’t warn about duplicate style matches that resolve to the same style

12.9 Release 0.2.0 (2016-08-10)

Styling:

- generate a style log (show matching styles) to help style sheet development
- keep_with_next style attribute: prevent splitting two flowables across pages

- stylesheets can be loaded from files in INI format
- check the type of attributes passed to styles
- source code highlighting using Pygments
- table of contents entries can be styled more freely
- allow hiding the section numbers of table of contents entries
- allow for custom chapter titles
- selectors can now also select based on document part/section
- various small tweaks to selectors and matchers
- various fixes relating to style sheets

Templates:

- configurable standard document templates: article and book
- a proper infrastructure for creating custom document templates
- support for left/right page templates
- make the Article template more configurable
- pages now have background, content and header/footer layers
- support for generating an index
- make certain strings configurable (for localization, for example)

Frontends:

- Sphinx: interpret the LaTeX configuration variables if the corresponding rinohtype variable is not set
- Sphinx: roughly match the LaTeX output (document template and style sheet)
- added a CommonMark frontend based on recommonmark
- added basic ePUB and DocBook frontends
- XML frontends: fix whitespace handling
- frontends now return generators yielding flowables (more flexible)

Command-line Renderer (rinoh):

- allow specifying a template and style sheet
- automatically install typefaces used in the style sheet from PyPI

Fonts:

- typefaces are discovered/loaded by entry point
- more complete support for OpenType fonts

- fix support for the 14 base Type 1 fonts

Images:

- more versatile image sizing: absolute width/height & scaling
- allow specifying the baseline for inline images
- several fixes in the JPEG reader

Miscellaneous:

- reorganize the Container class hierarchy
- fixes in footnote handling
- drop Python 3.2 support (3.3, 3.4 and 3.5 are supported)

12.10Release 0.1.3 (2015-08-04)

- recover from the slow rendering speed caused by a bugfix in 0.1.2 (thanks to optimized element matching in the style sheets)
- other improvements and bugfixes related to style sheets

12.11Release 0.1.2 (2015-07-31)

- much improved Sphinx support (we can now render the Sphinx documentation)
- more complete support for reStructuredText (docutils) elements
- various fixes related to footnote placement
- page break option when starting a new section
- fixes in handling of document sections and parts
- improvements to section/figure/table references
- native support for PNG and JPEG images (drops PIL/Pillow requirement, but adds PurePNG 0.1.1 requirement)
- new ‘sphinx’ stylesheet used by the Sphinx builder (~ Sphinx LaTeX style)
- restores Python 3.2 compatibility

12.12Release 0.1.1 (2015-04-12)

First preview release

Python Module Index

r

rinoh
 rinoh.attribute, 115
 rinoh.color, 115
 rinoh.dimension, 116
 rinoh.document, 117
 rinoh.draw, 118
 rinoh.flowable, 119
 rinoh.font, 121
 rinoh.font.style, 123
 rinoh.image, 123
 rinoh.index, 124
 rinoh.inline, 131
 rinoh.language, 125
 rinoh.number, 128
 rinoh.paper, 129
 rinoh.paragraph, 129
 rinoh.reference, 133
 rinoh.strings, 136
 rinoh.structure, 134
 rinoh.style, 136
 rinoh.stylesheets, 34
 rinoh.table, 138
 rinoh.template, 139
 rinoh.templates.article, 109
 rinoh.templates.book, 110
 rinoh.text, 130

Index

Symbols

- docs
 - rinoh command line option, 32
- format <format>
 - rinoh command line option, 31
- help
 - rinoh command line option, 31
- install-resources
 - rinoh command line option, 31
- list-fonts <filename>
 - rinoh command line option, 32
- list-formats
 - rinoh command line option, 32
- list-options <frontend>
 - rinoh command line option, 32
- list-stylesheets
 - rinoh command line option, 31
- list-templates
 - rinoh command line option, 31
- option <option=value>
 - rinoh command line option, 31
- output <filename or directory>
 - rinoh command line option, 31
- paper <paper>
 - rinoh command line option, 31
- stylesheet <name or filename>
 - rinoh command line option, 31
- template <name or filename>
 - rinoh command line option, 31
- version
 - rinoh command line option, 32
- f <format>
 - rinoh command line option, 31
- h
 - rinoh command line option, 31
- i
 - rinoh command line option, 31
- O <filename or directory>
 - rinoh command line option, 31
- o <option=value>
 - rinoh command line option, 31
- p <paper>

```
    rino command line option, 31
-s <name or filename>
    rino command line option, 31
-t <name or filename>
    rino command line option, 31
```

A

A0 (in module rino.paper), 129
A1 (in module rino.paper), 129
A10 (in module rino.paper), 129
A2 (in module rino.paper), 129
A3 (in module rino.paper), 129
A4 (in module rino.paper), 129
A5 (in module rino.paper), 129
A6 (in module rino.paper), 129
A7 (in module rino.paper), 129
A8 (in module rino.paper), 129
A9 (in module rino.paper), 129
abstract_location (rino.templates.article.Article attribute), 109
AbstractLocation (class in rino.templates.article), 110
AcceptNoneAttributeType (class in rino.attribute), 115
add_page() (rino.template.DocumentPart method), 140
Admonition (class in rino.structure), 135
AdmonitionStyle (class in rino.structure), 99
AdmonitionTitles (class in rino.structure), 135
advance() (rino.paragraph.DefaultSpacing method), 131
advance() (rino.paragraph.FixedSpacing method), 132
advance() (rino.paragraph.Leading method), 132
advance() (rino.paragraph.LineSpacing method), 131
advance() (rino.paragraph.ProportionalSpacing method), 131
after (rino.image.CaptionStyle attribute), 56
after (rino.inline.InlineFlowableStyle attribute), 69
after (rino.paragraph.ParagraphStyle attribute), 65
after (rino.reference.NoteMarkerStyle attribute), 75
after (rino.reference.ReferencingParagraphStyle attribute), 74
after (rino.structure.HeadingStyle attribute), 82
after (rino.structure.ListItemLabelStyle attribute), 90
after (rino.structure.TableOfContentsEntryStyle attribute), 99
after (rino.structure.TableOfContentsStyle attribute), 94
after (rino.text.TextStyle attribute), 67
after_break_background (rino.template.PageTemplate attribute), 145
after_break_background (rino.template.PageTemplateBase attribute), 147
after_break_background (rino.template.TitlePageTemplate attribute), 146
align (rino.image.ImageArgs attribute), 124
align_baselines (rino.flowable.LabeledFlowableStyle attribute), 46
AnchorFlowable (class in rino.flowable), 119
append() (rino.text.MixedStyledText method), 131
arguments (rino.image.BackgroundImage attribute), 123
arguments (rino.image.InlineImage attribute), 123
Article (class in rino.templates.article), 109
attention (rino.structure.AdmonitionTitles attribute), 135
Attribute (class in rino.attribute), 115
AttributesDictionary (class in rino.attribute), 115

B

back_matter (rino.templates.book.Book attribute), 111
back_matter_left_page (rino.templates.book.Book attribute), 114

back_matter_page (rinoh.templates.book.Book attribute), 113
back_matter_right_page (rinoh.templates.book.Book attribute), 113
background (rinoh.template.PageTemplate attribute), 144
background (rinoh.template.PageTemplateBase attribute), 147
background (rinoh.template.TitlePageTemplate attribute), 146
background_color (rinoh.flowable.FloatStyle attribute), 52
background_color (rinoh.flowable.FlowableStyle attribute), 45
background_color (rinoh.flowable.GroupedFlowablesStyle attribute), 50
background_color (rinoh.flowable.LabeledFlowableStyle attribute), 47
background_color (rinoh.image.CaptionStyle attribute), 54
background_color (rinoh.image.FigureStyle attribute), 58
background_color (rinoh.index.IndexStyle attribute), 61
background_color (rinoh.inline.InlineFlowableStyle attribute), 69
background_color (rinoh.paragraph.ParagraphStyle attribute), 63
background_color (rinoh.reference.ReferencingParagraphStyle attribute), 72
background_color (rinoh.structure.AdmonitionStyle attribute), 101
background_color (rinoh.structure.HeadingStyle attribute), 80
background_color (rinoh.structure.HorizontalRuleStyle attribute), 103
background_color (rinoh.structure.ListItemLabelStyle attribute), 88
background_color (rinoh.structure.ListStyle attribute), 85
background_color (rinoh.structure.SectionStyle attribute), 78
background_color (rinoh.structure.TableOfContentsEntryStyle attribute), 97
background_color (rinoh.structure.TableOfContentsStyle attribute), 92
background_color (rinoh.table.TableCellStyle attribute), 108
background_color (rinoh.table.TableStyle attribute), 106
BackgroundImage (class in rinoh.image), 123
baseline (rinoh.inline.InlineFlowableStyle attribute), 67
before (rinoh.image.CaptionStyle attribute), 56
before (rinoh.inline.InlineFlowableStyle attribute), 69
before (rinoh.paragraph.ParagraphStyle attribute), 65
before (rinoh.reference.NoteMarkerStyle attribute), 75
before (rinoh.reference.ReferencingParagraphStyle attribute), 73
before (rinoh.structure.HeadingStyle attribute), 82
before (rinoh.structure.ListItemLabelStyle attribute), 89
before (rinoh.structure.TableOfContentsEntryStyle attribute), 99
before (rinoh.structure.TableOfContentsStyle attribute), 94
before (rinoh.text.TextStyle attribute), 67
Book (class in rinoh.templates.book), 110
Bool (class in rinoh.attribute), 115
border (rinoh.flowable.FloatStyle attribute), 51
border (rinoh.flowable.FlowableStyle attribute), 45
border (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border (rinoh.flowable.LabeledFlowableStyle attribute), 47
border (rinoh.image.CaptionStyle attribute), 54
border (rinoh.image.FigureStyle attribute), 58
border (rinoh.index.IndexStyle attribute), 60
border (rinoh.inline.InlineFlowableStyle attribute), 68
border (rinoh.paragraph.ParagraphStyle attribute), 63
border (rinoh.reference.ReferencingParagraphStyle attribute), 71
border (rinoh.structure.AdmonitionStyle attribute), 101
border (rinoh.structure.HeadingStyle attribute), 80
border (rinoh.structure.HorizontalRuleStyle attribute), 103
border (rinoh.structure.ListItemLabelStyle attribute), 87
border (rinoh.structure.ListStyle attribute), 84
border (rinoh.structure.SectionStyle attribute), 77
border (rinoh.structure.TableOfContentsEntryStyle attribute), 97
border (rinoh.structure.TableOfContentsStyle attribute), 91
border (rinoh.table.TableCellStyle attribute), 107

border (rinoh.table.TableStyle attribute), 105
border_bottom (rinoh.flowable.FloatStyle attribute), 51
border_bottom (rinoh.flowable.FlowableStyle attribute), 45
border_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_bottom (rinoh.image.CaptionStyle attribute), 54
border_bottom (rinoh.image.FigureStyle attribute), 58
border_bottom (rinoh.index.IndexStyle attribute), 60
border_bottom (rinoh.inline.InlineFlowableStyle attribute), 68
border_bottom (rinoh.paragraph.ParagraphStyle attribute), 63
border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 72
border_bottom (rinoh.structure.AdmonitionStyle attribute), 101
border_bottom (rinoh.structure.HeadingStyle attribute), 80
border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 103
border_bottom (rinoh.structure.ListItemLabelStyle attribute), 88
border_bottom (rinoh.structure.ListStyle attribute), 84
border_bottom (rinoh.structure.SectionStyle attribute), 78
border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 97
border_bottom (rinoh.structure.TableOfContentsStyle attribute), 92
border_bottom (rinoh.table.TableCellStyle attribute), 108
border_bottom (rinoh.table.TableStyle attribute), 105
border_left (rinoh.flowable.FloatStyle attribute), 51
border_left (rinoh.flowable.FlowableStyle attribute), 45
border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_left (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_left (rinoh.image.CaptionStyle attribute), 54
border_left (rinoh.image.FigureStyle attribute), 58
border_left (rinoh.index.IndexStyle attribute), 60
border_left (rinoh.inline.InlineFlowableStyle attribute), 68
border_left (rinoh.paragraph.ParagraphStyle attribute), 63
border_left (rinoh.reference.ReferencingParagraphStyle attribute), 71
border_left (rinoh.structure.AdmonitionStyle attribute), 101
border_left (rinoh.structure.HeadingStyle attribute), 80
border_left (rinoh.structure.HorizontalRuleStyle attribute), 103
border_left (rinoh.structure.ListItemLabelStyle attribute), 87
border_left (rinoh.structure.ListStyle attribute), 84
border_left (rinoh.structure.SectionStyle attribute), 77
border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 97
border_left (rinoh.structure.TableOfContentsStyle attribute), 91
border_left (rinoh.table.TableCellStyle attribute), 107
border_left (rinoh.table.TableStyle attribute), 105
border_right (rinoh.flowable.FloatStyle attribute), 51
border_right (rinoh.flowable.FlowableStyle attribute), 45
border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_right (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_right (rinoh.image.CaptionStyle attribute), 54
border_right (rinoh.image.FigureStyle attribute), 58
border_right (rinoh.index.IndexStyle attribute), 60
border_right (rinoh.inline.InlineFlowableStyle attribute), 68
border_right (rinoh.paragraph.ParagraphStyle attribute), 63
border_right (rinoh.reference.ReferencingParagraphStyle attribute), 71
border_right (rinoh.structure.AdmonitionStyle attribute), 101
border_right (rinoh.structure.HeadingStyle attribute), 80
border_right (rinoh.structure.HorizontalRuleStyle attribute), 103
border_right (rinoh.structure.ListItemLabelStyle attribute), 87
border_right (rinoh.structure.ListStyle attribute), 84
border_right (rinoh.structure.SectionStyle attribute), 77
border_right (rinoh.structure.TableOfContentsEntryStyle attribute), 97

border_right (rinoh.structure.TableOfContentsStyle attribute), 91
border_right (rinoh.table.TableCellStyle attribute), 108
border_right (rinoh.table.TableStyle attribute), 105
border_top (rinoh.flowable.FloatStyle attribute), 51
border_top (rinoh.flowable.FlowableStyle attribute), 45
border_top (rinoh.flowable.GroupedFlowablesStyle attribute), 49
border_top (rinoh.flowable.LabeledFlowableStyle attribute), 47
border_top (rinoh.image.CaptionStyle attribute), 54
border_top (rinoh.image.FigureStyle attribute), 58
border_top (rinoh.index.IndexStyle attribute), 60
border_top (rinoh.inline.InlineFlowableStyle attribute), 68
border_top (rinoh.paragraph.ParagraphStyle attribute), 63
border_top (rinoh.reference.ReferencingParagraphStyle attribute), 72
border_top (rinoh.structure.AdmonitionStyle attribute), 101
border_top (rinoh.structure.HeadingStyle attribute), 80
border_top (rinoh.structure.HorizontalRuleStyle attribute), 103
border_top (rinoh.structure.ListItemLabelStyle attribute), 88
border_top (rinoh.structure.ListStyle attribute), 84
border_top (rinoh.structure.SectionStyle attribute), 77
border_top (rinoh.structure.TableOfContentsEntryStyle attribute), 97
border_top (rinoh.structure.TableOfContentsStyle attribute), 92
border_top (rinoh.table.TableCellStyle attribute), 108
border_top (rinoh.table.TableStyle attribute), 105
bottom_margin (rinoh.template.PageTemplate attribute), 144
bottom_margin (rinoh.template.PageTemplateBase attribute), 146
bottom_margin (rinoh.template.TitlePageTemplate attribute), 146
build_document() (rinoh.flowable.StaticGroupedFlowables method), 120
bullet (rinoh.structure.ListStyle attribute), 83

C

Caption (class in rinoh.image), 124
CaptionStyle (class in rinoh.image), 52
caution (rinoh.structure.AdmonitionTitles attribute), 135
chapter (rinoh.structure.SectionTitles attribute), 134
chapter_footer_text (rinoh.template.PageTemplate attribute), 143
chapter_header_text (rinoh.template.PageTemplate attribute), 143
chapter_title_flowables (rinoh.template.PageTemplate attribute), 144
chapter_title_height (rinoh.template.PageTemplate attribute), 144
CM (in module rinoh.dimension), 117
Color (class in rinoh.color), 115
column_spacing (rinoh.template.PageTemplate attribute), 143
column_widths (rinoh.table.TableStyle attribute), 104
columns (rinoh.template.PageTemplate attribute), 143
Configuration (rinoh.template.DocumentTemplate attribute), 139
Configuration (rinoh.templates.article.Article attribute), 110
Configuration (rinoh.templates.book.Book attribute), 114
configuration_class (rinoh.template.DocumentPart attribute), 140
ConfigurationFile (rinoh.template.DocumentTemplate attribute), 139
ConfigurationFile (rinoh.templates.article.Article attribute), 110
ConfigurationFile (rinoh.templates.book.Book attribute), 114
contents (rinoh.structure.SectionTitles attribute), 134
contents (rinoh.templates.article.Article attribute), 110
contents (rinoh.templates.book.Book attribute), 111
contents_left_page (rinoh.templates.book.Book attribute), 113
contents_page (rinoh.templates.article.Article attribute), 110
contents_page (rinoh.templates.book.Book attribute), 112
contents_right_page (rinoh.templates.book.Book attribute), 113

ContentsPartTemplate (class in rinoh.template), 142
copy() (rinoh.text.MixedStyledText method), 131
cover (rinoh.templates.book.Book attribute), 111
cover_page (rinoh.templates.book.Book attribute), 112
custom_label (rinoh.image.CaptionStyle attribute), 55
custom_label (rinoh.number.NumberStyle attribute), 128
custom_label (rinoh.paragraph.ParagraphStyle attribute), 64
custom_label (rinoh.reference.NoteMarkerStyle attribute), 76
custom_label (rinoh.reference.ReferencingParagraphStyle attribute), 72
custom_label (rinoh.structure.HeadingStyle attribute), 81
custom_label (rinoh.structure.ListItemLabelStyle attribute), 88
custom_label (rinoh.structure.ListStyle attribute), 85
custom_label (rinoh.structure.TableOfContentsEntryStyle attribute), 98
custom_label (rinoh.structure.TableOfContentsStyle attribute), 93

D

danger (rinoh.structure.AdmonitionTitles attribute), 135
DEFAULT (in module rinoh.paragraph), 132
DefaultSpacing (class in rinoh.paragraph), 131
DefinitionList (class in rinoh.structure), 135
depth (rinoh.structure.TableOfContentsStyle attribute), 90
Dimension (class in rinoh.dimension), 116
doc_format() (rinoh.color.Color class method), 116
Document (class in rinoh.document), 117
document() (rinoh.template.TemplateConfiguration method), 140
DocumentPart (class in rinoh.template), 140
DocumentPartTemplate (class in rinoh.template), 141
DocumentTemplate (class in rinoh.template), 139
DocumentTree (class in rinoh.document), 117
DOUBLE (in module rinoh.paragraph), 132
dpi (rinoh.image.ImageArgs attribute), 124
drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 142
drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 141
drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 142
drop_if_empty (rinoh.template.TitlePartTemplate attribute), 141
DummyFlowable (class in rinoh.flowable), 119

E

EN (in module rinoh.language), 125
encoding (rinoh.font.Font attribute), 122
end_at_page (rinoh.template.ContentsPartTemplate attribute), 142
end_at_page (rinoh.template.DocumentPartTemplate attribute), 141
end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 142
end_at_page (rinoh.template.TitlePartTemplate attribute), 141
environment variable
 PATH, 11
error (rinoh.structure.AdmonitionTitles attribute), 135
extra (rinoh.template.TitlePageTemplate attribute), 145

F

Field (class in rinoh.reference), 134
Figure (class in rinoh.image), 124
FigureStyle (class in rinoh.image), 56
file_or_filename (rinoh.image.ImageArgs attribute), 124
fill_color (rinoh.draw.ShapeStyle attribute), 43
fill_color (rinoh.table.TableCellBackgroundColor attribute), 108
FixedDocumentPartTemplate (class in rinoh.template), 142

FixedSpacing (class in `rinoh.paragraph`), 132
Float (class in `rinoh.flowable`), 121
`float` (`rinoh.flowable.FloatStyle` attribute), 50
`float` (`rinoh.image.FigureStyle` attribute), 56
FloatStyle (class in `rinoh.flowable`), 50
`flow()` (`rinoh.flowable.Float` method), 121
`flow()` (`rinoh.index.IndexTarget` method), 125
`flow()` (`rinoh.structure.Heading` method), 134
Flowable (class in `rinoh.flowable`), 119
`flowable_spacing` (`rinoh.flowable.GroupedFlowablesStyle` attribute), 48
`flowable_spacing` (`rinoh.image.FigureStyle` attribute), 58
`flowable_spacing` (`rinoh.index.IndexStyle` attribute), 59
`flowable_spacing` (`rinoh.structure.AdmonitionStyle` attribute), 100
`flowable_spacing` (`rinoh.structure.ListStyle` attribute), 83
`flowable_spacing` (`rinoh.structure.SectionStyle` attribute), 76
`flowable_spacing` (`rinoh.structure.TableOfContentsStyle` attribute), 90
`flowable_spacing` (`rinoh.table.TableCellStyle` attribute), 106
flowables (`rinoh.template.FixedDocumentPartTemplate` attribute), 142
`flowables()` (`rinoh.flowable.GroupedFlowables` method), 120
`flowables()` (`rinoh.flowable.StaticGroupedFlowables` method), 120
`flowables()` (`rinoh.index.Index` method), 125
`flowables()` (`rinoh.structure.Admonition` method), 135
`flowables()` (`rinoh.structure.TableOfContents` method), 135
FlowableState (class in `rinoh.flowable`), 119
FlowableStyle (class in `rinoh.flowable`), 43
FlowableWidth (class in `rinoh.flowable`), 121
Font (class in `rinoh.font`), 121
`font_color` (`rinoh.image.CaptionStyle` attribute), 55
`font_color` (`rinoh.paragraph.ParagraphStyle` attribute), 64
`font_color` (`rinoh.reference.NoteMarkerStyle` attribute), 74
`font_color` (`rinoh.reference.ReferencingParagraphStyle` attribute), 73
`font_color` (`rinoh.structure.HeadingStyle` attribute), 81
`font_color` (`rinoh.structure.ListItemLabelStyle` attribute), 89
`font_color` (`rinoh.structure.TableOfContentsEntryStyle` attribute), 98
`font_color` (`rinoh.structure.TableOfContentsStyle` attribute), 94
`font_color` (`rinoh.text.TextStyle` attribute), 66
`font_size` (`rinoh.image.CaptionStyle` attribute), 55
`font_size` (`rinoh.paragraph.ParagraphStyle` attribute), 64
`font_size` (`rinoh.reference.NoteMarkerStyle` attribute), 74
`font_size` (`rinoh.reference.ReferencingParagraphStyle` attribute), 73
`font_size` (`rinoh.structure.HeadingStyle` attribute), 81
`font_size` (`rinoh.structure.ListItemLabelStyle` attribute), 89
`font_size` (`rinoh.structure.TableOfContentsEntryStyle` attribute), 98
`font_size` (`rinoh.structure.TableOfContentsStyle` attribute), 94
`font_size` (`rinoh.text.TextStyle` attribute), 66
`font_slant` (`rinoh.image.CaptionStyle` attribute), 55
`font_slant` (`rinoh.paragraph.ParagraphStyle` attribute), 64
`font_slant` (`rinoh.reference.NoteMarkerStyle` attribute), 74
`font_slant` (`rinoh.reference.ReferencingParagraphStyle` attribute), 72
`font_slant` (`rinoh.structure.HeadingStyle` attribute), 81
`font_slant` (`rinoh.structure.ListItemLabelStyle` attribute), 88
`font_slant` (`rinoh.structure.TableOfContentsEntryStyle` attribute), 98
`font_slant` (`rinoh.structure.TableOfContentsStyle` attribute), 93
`font_slant` (`rinoh.text.TextStyle` attribute), 66
`font_variant` (`rinoh.image.CaptionStyle` attribute), 55
`font_variant` (`rinoh.paragraph.ParagraphStyle` attribute), 65
`font_variant` (`rinoh.reference.NoteMarkerStyle` attribute), 74
`font_variant` (`rinoh.reference.ReferencingParagraphStyle` attribute), 73

font_variant (rinoh.structure.HeadingStyle attribute), 82
font_variant (rinoh.structure.ListItemLabelStyle attribute), 89
font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 98
font_variant (rinoh.structure.TableOfContentsStyle attribute), 94
font_variant (rinoh.text.TextStyle attribute), 66
font_weight (rinoh.image.CaptionStyle attribute), 55
font_weight (rinoh.paragraph.ParagraphStyle attribute), 64
font_weight (rinoh.reference.NoteMarkerStyle attribute), 74
font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 72
font_weight (rinoh.structure.HeadingStyle attribute), 81
font_weight (rinoh.structure.ListItemLabelStyle attribute), 88
font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 98
font_weight (rinoh.structure.TableOfContentsStyle attribute), 93
font_weight (rinoh.text.TextStyle attribute), 65
font_width (rinoh.image.CaptionStyle attribute), 55
font_width (rinoh.paragraph.ParagraphStyle attribute), 64
font_width (rinoh.reference.NoteMarkerStyle attribute), 74
font_width (rinoh.reference.ReferencingParagraphStyle attribute), 73
font_width (rinoh.structure.HeadingStyle attribute), 81
font_width (rinoh.structure.ListItemLabelStyle attribute), 89
font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 98
font_width (rinoh.structure.TableOfContentsStyle attribute), 93
font_width (rinoh.text.TextStyle attribute), 66
fonts() (rinoh.font.Typeface method), 122
FontSlant (class in rinoh.font.style), 123
FontVariant (class in rinoh.font.style), 123
FontWeight (class in rinoh.font.style), 123
FontWidth (class in rinoh.font.style), 123
footer_text (rinoh.template.PageTemplate attribute), 143
format_number() (in module rinoh.number), 128
FR (in module rinoh.language), 126
front_matter (rinoh.templates.article.Article attribute), 110
front_matter (rinoh.templates.book.Book attribute), 111
front_matter_left_page (rinoh.templates.book.Book attribute), 112
front_matter_page (rinoh.templates.article.Article attribute), 110
front_matter_page (rinoh.templates.book.Book attribute), 112
front_matter_right_page (rinoh.templates.book.Book attribute), 112

G

get_font() (rinoh.font.Typeface method), 123
get_glyph() (rinoh.font.Font method), 122
get_kerning() (rinoh.font.Font method), 122
get_ligature() (rinoh.font.Font method), 122
get_position() (rinoh.paragraph.TabStop method), 132
get_rowspanned_columns() (rinoh.table.TableRow method), 138
get_selector() (rinoh.style.StyleSheet method), 137
Glyph (class in rinoh.paragraph), 133
GlyphsSpan (class in rinoh.paragraph), 133
Gray (class in rinoh.color), 116
GroupedFlowables (class in rinoh.flowable), 120
GroupedFlowablesState (class in rinoh.flowable), 120
GroupedFlowablesStyle (class in rinoh.flowable), 48
GroupedLabeledFlowables (class in rinoh.flowable), 121
grow() (rinoh.dimension.Dimension method), 116

H

has_class() (rinoh.style.Styled property), 137

has_classes() (rinoh.style.Styled property), 137
header_footer_distance (rinoh.template.PageTemplate attribute), 143
header_text (rinoh.template.PageTemplate attribute), 143
Heading (class in rinoh.structure), 134
HeadingStyle (class in rinoh.structure), 78
height (rinoh.image.ImageArgs attribute), 124
height() (rinoh.text.StyledText method), 130
HexColor (class in rinoh.color), 116
hide (rinoh.draw.LineStyle attribute), 43
hide (rinoh.draw.ShapeStyle attribute), 43
hide (rinoh.flowable.FloatStyle attribute), 52
hide (rinoh.flowable.FlowableStyle attribute), 45
hide (rinoh.flowable.GroupedFlowablesStyle attribute), 50
hide (rinoh.flowable.LabeledFlowableStyle attribute), 48
hide (rinoh.image.CaptionStyle attribute), 56
hide (rinoh.image.FigureStyle attribute), 58
hide (rinoh.index.IndexStyle attribute), 61
hide (rinoh.inline.InlineFlowableStyle attribute), 69
hide (rinoh.number.NumberStyle attribute), 128
hide (rinoh.paragraph.ParagraphStyle attribute), 64
hide (rinoh.reference.NoteMarkerStyle attribute), 75
hide (rinoh.reference.ReferencingParagraphStyle attribute), 74
hide (rinoh.structure.AdmonitionStyle attribute), 101
hide (rinoh.structure.HeadingStyle attribute), 82
hide (rinoh.structure.HorizontalRuleStyle attribute), 103
hide (rinoh.structure.ListItemLabelStyle attribute), 90
hide (rinoh.structure.ListStyle attribute), 85
hide (rinoh.structure.SectionStyle attribute), 78
hide (rinoh.structure.TableOfContentsEntryStyle attribute), 99
hide (rinoh.structure.TableOfContentsStyle attribute), 92
hide (rinoh.style.Style attribute), 137
hide (rinoh.table.TableCellBackgroundColor attribute), 109
hide (rinoh.table.TableCellBorderStyle attribute), 108
hide (rinoh.table.TableCellStyle attribute), 108
hide (rinoh.table.TableStyle attribute), 106
hide (rinoh.text.TextStyle attribute), 67
hint (rinoh.structure.AdmonitionTitles attribute), 135
horizontal_align (rinoh.flowable.FloatStyle attribute), 50
horizontal_align (rinoh.flowable.FlowableStyle attribute), 44
horizontal_align (rinoh.flowable.GroupedFlowablesStyle attribute), 48
horizontal_align (rinoh.flowable.LabeledFlowableStyle attribute), 46
horizontal_align (rinoh.image.CaptionStyle attribute), 53
horizontal_align (rinoh.image.FigureStyle attribute), 57
horizontal_align (rinoh.index.IndexStyle attribute), 59
horizontal_align (rinoh.inline.InlineFlowableStyle attribute), 67
horizontal_align (rinoh.paragraph.ParagraphStyle attribute), 62
horizontal_align (rinoh.reference.ReferencingParagraphStyle attribute), 70
horizontal_align (rinoh.structure.AdmonitionStyle attribute), 100
horizontal_align (rinoh.structure.HeadingStyle attribute), 79
horizontal_align (rinoh.structure.HorizontalRuleStyle attribute), 102
horizontal_align (rinoh.structure.ListItemLabelStyle attribute), 86
horizontal_align (rinoh.structure.ListStyle attribute), 83
horizontal_align (rinoh.structure.SectionStyle attribute), 76
horizontal_align (rinoh.structure.TableOfContentsEntryStyle attribute), 96
horizontal_align (rinoh.structure.TableOfContentsStyle attribute), 90
horizontal_align (rinoh.table.TableCellStyle attribute), 106
horizontal_align (rinoh.table.TableStyle attribute), 104
HorizontalAlignment (class in rinoh.flowable), 121

HorizontalRule (class in rinoh.structure), 136
HorizontalRuleStyle (class in rinoh.structure), 102
hyphen_chars (rinoh.image.CaptionStyle attribute), 56
hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 65
hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 75
hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 73
hyphen_chars (rinoh.structure.HeadingStyle attribute), 82
hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 89
hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 99
hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 94
hyphen_chars (rinoh.text.TextStyle attribute), 66
hyphen_lang (rinoh.image.CaptionStyle attribute), 56
hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 65
hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 75
hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 73
hyphen_lang (rinoh.structure.HeadingStyle attribute), 82
hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 89
hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 99
hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 94
hyphen_lang (rinoh.text.TextStyle attribute), 66
hyphenate (rinoh.image.CaptionStyle attribute), 56
hyphenate (rinoh.paragraph.ParagraphStyle attribute), 65
hyphenate (rinoh.reference.NoteMarkerStyle attribute), 75
hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 73
hyphenate (rinoh.structure.HeadingStyle attribute), 82
hyphenate (rinoh.structure.ListItemLabelStyle attribute), 89
hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 99
hyphenate (rinoh.structure.TableOfContentsStyle attribute), 94
hyphenate (rinoh.text.TextStyle attribute), 66
HyphenatorStore (class in rinoh.paragraph), 133

|

Image (class in rinoh.image), 123
ImageArgs (class in rinoh.image), 123
important (rinoh.structure.AdmonitionTitles attribute), 135
INCH (in module rinoh.dimension), 117
indent_first (rinoh.image.CaptionStyle attribute), 52
indent_first (rinoh.paragraph.ParagraphStyle attribute), 61
indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 69
indent_first (rinoh.structure.HeadingStyle attribute), 78
indent_first (rinoh.structure.ListItemLabelStyle attribute), 85
indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 95
indent_first (rinoh.structure.TableOfContentsStyle attribute), 92
Index (class in rinoh.index), 125
index (rinoh.structure.SectionTitles attribute), 134
IndexLabel (class in rinoh.index), 125
IndexSection (class in rinoh.index), 124
IndexStyle (class in rinoh.index), 59
IndexTarget (class in rinoh.index), 125
IndexTerm (class in rinoh.index), 125
initials (rinoh.index.IndexStyle attribute), 59
inline_title (rinoh.structure.AdmonitionStyle attribute), 99
InlineFlowable (class in rinoh.inline), 131
InlineFlowableStyle (class in rinoh.inline), 67
InlineImage (class in rinoh.image), 123
InlineIndexTarget (class in rinoh.index), 125
input

rinoh command line option, 31
 Integer (class in rinoh.attribute), 115
 is_script() (rinoh.text.StyledText method), 130
 IT (in module rinoh.language), 126
 items() (rinoh.text.MixedStyledText property), 131
 items() (rinoh.text.StyledText property), 130

J

JUNIOR_LEGAL (in module rinoh.paper), 129

K

 keep_with_next (rinoh.flowable.FloatStyle attribute), 51
 keep_with_next (rinoh.flowable.FlowableStyle attribute), 44
 keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 49
 keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 47
 keep_with_next (rinoh.image.CaptionStyle attribute), 54
 keep_with_next (rinoh.image.FigureStyle attribute), 58
 keep_with_next (rinoh.index.IndexStyle attribute), 60
 keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 68
 keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 63
 keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 71
 keep_with_next (rinoh.structure.AdmonitionStyle attribute), 101
 keep_with_next (rinoh.structure.HeadingStyle attribute), 78
 keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 103
 keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 87
 keep_with_next (rinoh.structure.ListStyle attribute), 84
 keep_with_next (rinoh.structure.SectionStyle attribute), 77
 keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 97
 keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 91
 keep_with_next (rinoh.table.TableCellStyle attribute), 107
 keep_with_next (rinoh.table.TableStyle attribute), 105
 kerning (rinoh.image.CaptionStyle attribute), 56
 kerning (rinoh.paragraph.ParagraphStyle attribute), 65
 kerning (rinoh.reference.NoteMarkerStyle attribute), 75
 kerning (rinoh.reference.ReferencingParagraphStyle attribute), 73
 kerning (rinoh.structure.HeadingStyle attribute), 82
 kerning (rinoh.structure.ListItemLabelStyle attribute), 89
 kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 98
 kerning (rinoh.structure.TableOfContentsStyle attribute), 94
 kerning (rinoh.text.TextStyle attribute), 66

L

 Label (class in rinoh.number), 128
 label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 45
 label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 45
 label_prefix (rinoh.image.CaptionStyle attribute), 55
 label_prefix (rinoh.number.NumberStyle attribute), 128
 label_prefix (rinoh.paragraph.ParagraphStyle attribute), 64
 label_prefix (rinoh.reference.NoteMarkerStyle attribute), 75
 label_prefix (rinoh.reference.ReferencingParagraphStyle attribute), 72
 label_prefix (rinoh.structure.HeadingStyle attribute), 81
 label_prefix (rinoh.structure.ListItemLabelStyle attribute), 88
 label_prefix (rinoh.structure.ListStyle attribute), 85
 label_prefix (rinoh.structure.TableOfContentsEntryStyle attribute), 97
 label_prefix (rinoh.structure.TableOfContentsStyle attribute), 93
 label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 46
 label_suffix (rinoh.image.CaptionStyle attribute), 55

label_suffix (rinoh.number.NumberStyle attribute), 128
label_suffix (rinoh.paragraph.ParagraphStyle attribute), 64
label_suffix (rinoh.reference.NoteMarkerStyle attribute), 75
label_suffix (rinoh.reference.ReferencingParagraphStyle attribute), 72
label_suffix (rinoh.structure.HeadingStyle attribute), 81
label_suffix (rinoh.structure.ListItemLabelStyle attribute), 88
label_suffix (rinoh.structure.ListStyle attribute), 85
label_suffix (rinoh.structure.TableOfContentsEntryStyle attribute), 98
label_suffix (rinoh.structure.TableOfContentsStyle attribute), 93
LabeledFlowable (class in rinoh.flowable), 119
LabeledFlowableState (class in rinoh.flowable), 120
LabeledFlowableStyle (class in rinoh.flowable), 45
Language (class in rinoh.language), 125
language (rinoh.template.DocumentTemplate attribute), 139
language (rinoh.templates.article.Article attribute), 109
language (rinoh.templates.book.Book attribute), 110
languages (rinoh.language.Language attribute), 125
Leading (class in rinoh.paragraph), 132
LEDGER (in module rinoh.paper), 129
left_margin (rinoh.template.PageTemplate attribute), 144
left_margin (rinoh.template.PageTemplateBase attribute), 146
left_margin (rinoh.template.TitlePageTemplate attribute), 145
LEGAL (in module rinoh.paper), 129
LETTER (in module rinoh.paper), 129
ligatures (rinoh.image.CaptionStyle attribute), 56
ligatures (rinoh.paragraph.ParagraphStyle attribute), 65
ligatures (rinoh.reference.NoteMarkerStyle attribute), 75
ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 73
ligatures (rinoh.structure.HeadingStyle attribute), 82
ligatures (rinoh.structure.ListItemLabelStyle attribute), 89
ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 99
ligatures (rinoh.structure.TableOfContentsStyle attribute), 94
ligatures (rinoh.text.TextStyle attribute), 66
limit_width (rinoh.image.ImageArgs attribute), 123
Line (class in rinoh.draw), 118
line_spacing (rinoh.image.CaptionStyle attribute), 52
line_spacing (rinoh.paragraph.ParagraphStyle attribute), 61
line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 69
line_spacing (rinoh.structure.HeadingStyle attribute), 78
line_spacing (rinoh.structure.ListItemLabelStyle attribute), 86
line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 95
line_spacing (rinoh.structure.TableOfContentsStyle attribute), 92
LineSpacing (class in rinoh.paragraph), 131
LineStyle (class in rinoh.draw), 43
List (class in rinoh.structure), 135
list_class (rinoh.image.ListOfFiguresSection attribute), 124
list_class (rinoh.table.ListOfTablesSection attribute), 139
list_of_figures (rinoh.structure.SectionTitles attribute), 134
list_of_tables (rinoh.structure.SectionTitles attribute), 134
ListItemLabelStyle (class in rinoh.structure), 85
ListOfFigures (class in rinoh.image), 124
ListOfFiguresSection (class in rinoh.image), 124
ListOfTables (class in rinoh.table), 139
ListOfTablesSection (class in rinoh.table), 139
LineStyle (class in rinoh.structure), 82
Locale (class in rinoh.text), 131
location() (rinoh.attribute.RuleSetFile property), 115

M

margin_left (rinoh.flowable.FloatStyle attribute), 50
margin_left (rinoh.flowable.FlowableStyle attribute), 44
margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 48
margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 46
margin_left (rinoh.image.CaptionStyle attribute), 53
margin_left (rinoh.image.FigureStyle attribute), 57
margin_left (rinoh.index.IndexStyle attribute), 59
margin_left (rinoh.inline.InlineFlowableStyle attribute), 67
margin_left (rinoh.paragraph.ParagraphStyle attribute), 62
margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 71
margin_left (rinoh.structure.AdmonitionStyle attribute), 100
margin_left (rinoh.structure.HeadingStyle attribute), 79
margin_left (rinoh.structure.HorizontalRuleStyle attribute), 102
margin_left (rinoh.structure.ListItemLabelStyle attribute), 87
margin_left (rinoh.structure.ListStyle attribute), 83
margin_left (rinoh.structure.SectionStyle attribute), 76
margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 96
margin_left (rinoh.structure.TableOfContentsStyle attribute), 91
margin_left (rinoh.table.TableCellStyle attribute), 107
margin_left (rinoh.table.TableStyle attribute), 104
margin_right (rinoh.flowable.FloatStyle attribute), 50
margin_right (rinoh.flowable.FlowableStyle attribute), 44
margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 48
margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 46
margin_right (rinoh.image.CaptionStyle attribute), 53
margin_right (rinoh.image.FigureStyle attribute), 57
margin_right (rinoh.index.IndexStyle attribute), 59
margin_right (rinoh.inline.InlineFlowableStyle attribute), 67
margin_right (rinoh.paragraph.ParagraphStyle attribute), 62
margin_right (rinoh.reference.ReferencingParagraphStyle attribute), 71
margin_right (rinoh.structure.AdmonitionStyle attribute), 100
margin_right (rinoh.structure.HeadingStyle attribute), 79
margin_right (rinoh.structure.HorizontalRuleStyle attribute), 102
margin_right (rinoh.structure.ListItemLabelStyle attribute), 87
margin_right (rinoh.structure.ListStyle attribute), 83
margin_right (rinoh.structure.SectionStyle attribute), 77
margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 96
margin_right (rinoh.structure.TableOfContentsStyle attribute), 91
margin_right (rinoh.table.TableCellStyle attribute), 107
margin_right (rinoh.table.TableStyle attribute), 104
matcher (in module rinoh.stylesheets), 34
MixedStyledText (class in rinoh.text), 130
MM (in module rinoh.dimension), 117
module
 rinoh.attribute, 115
 rinoh.color, 115
 rinoh.dimension, 116
 rinoh.document, 117
 rinoh.draw, 118
 rinoh.flowable, 119
 rinoh.font, 121
 rinoh.font.style, 123
 rinoh.image, 123
 rinoh.index, 124
 rinoh.inline, 131
 rinoh.language, 125

rinoh.number, 128
rinoh.paper, 129
rinoh.paragraph, 129
rinoh.reference, 133
rinoh.strings, 136
rinoh.structure, 134
rinoh.style, 136
rinoh.stylesheets, 34
rinoh.table, 138
rinoh.template, 139
rinoh.templates.article, 109
rinoh.templates.book, 110
rinoh.text, 130

N

new_page() (rinoh.template.DocumentPart method), 140
NL (in module rinoh.language), 127
Note (class in rinoh.reference), 133
note (rinoh.structure.AdmonitionTitles attribute), 135
NoteMarkerBase (class in rinoh.reference), 133
NoteMarkerByID (class in rinoh.reference), 133
NoteMarkerStyle (class in rinoh.reference), 74
NoteMarkerWithNote (class in rinoh.reference), 134
number_format (rinoh.image.CaptionStyle attribute), 52
number_format (rinoh.number.NumberStyle attribute), 128
number_format (rinoh.paragraph.ParagraphStyle attribute), 61
number_format (rinoh.reference.NoteMarkerStyle attribute), 75
number_format (rinoh.reference.ReferencingParagraphStyle attribute), 70
number_format (rinoh.structure.HeadingStyle attribute), 79
number_format (rinoh.structure.ListItemLabelStyle attribute), 86
number_format (rinoh.structure.ListStyle attribute), 85
number_format (rinoh.structure.TableOfContentsEntryStyle attribute), 95
number_format (rinoh.structure.TableOfContentsStyle attribute), 92
number_separator (rinoh.image.CaptionStyle attribute), 53
number_separator (rinoh.paragraph.ParagraphStyle attribute), 62
number_separator (rinoh.reference.ReferencingParagraphStyle attribute), 70
number_separator (rinoh.structure.HeadingStyle attribute), 79
number_separator (rinoh.structure.ListItemLabelStyle attribute), 86
number_separator (rinoh.structure.TableOfContentsEntryStyle attribute), 95
number_separator (rinoh.structure.TableOfContentsStyle attribute), 93
NumberFormat (class in rinoh.number), 128
numbering_level (rinoh.image.CaptionStyle attribute), 52
numbering_level (rinoh.paragraph.ParagraphStyle attribute), 62
numbering_level (rinoh.reference.ReferencingParagraphStyle attribute), 70
numbering_level (rinoh.structure.HeadingStyle attribute), 78
numbering_level (rinoh.structure.ListItemLabelStyle attribute), 86
numbering_level (rinoh.structure.TableOfContentsEntryStyle attribute), 96
numbering_level (rinoh.structure.TableOfContentsStyle attribute), 93
NumberStyle (class in rinoh.number), 128

O

OptionSet (class in rinoh.attribute), 115
ordered (rinoh.structure.ListStyle attribute), 82
OverrideDefault (class in rinoh.attribute), 115

P

padding (rinoh.flowable.FloatStyle attribute), 51

padding (rinoh.flowable.FlowableStyle attribute), 44
padding (rinoh.flowable.GroupedFlowablesStyle attribute), 49
padding (rinoh.flowable.LabeledFlowableStyle attribute), 46
padding (rinoh.image.CaptionStyle attribute), 53
padding (rinoh.image.FigureStyle attribute), 57
padding (rinoh.index.IndexStyle attribute), 60
padding (rinoh.inline.InlineFlowableStyle attribute), 68
padding (rinoh.paragraph.ParagraphStyle attribute), 62
padding (rinoh.reference.ReferencingParagraphStyle attribute), 71
padding (rinoh.structure.AdmonitionStyle attribute), 100
padding (rinoh.structure.HeadingStyle attribute), 79
padding (rinoh.structure.HorizontalRuleStyle attribute), 102
padding (rinoh.structure.ListItemLabelStyle attribute), 87
padding (rinoh.structure.ListStyle attribute), 83
padding (rinoh.structure.SectionStyle attribute), 77
padding (rinoh.structure.TableOfContentsEntryStyle attribute), 96
padding (rinoh.structure.TableOfContentsStyle attribute), 91
padding (rinoh.table.TableCellStyle attribute), 107
padding (rinoh.table.TableStyle attribute), 105
padding_bottom (rinoh.flowable.FloatStyle attribute), 51
padding_bottom (rinoh.flowable.FlowableStyle attribute), 44
padding_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 49
padding_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 47
padding_bottom (rinoh.image.CaptionStyle attribute), 54
padding_bottom (rinoh.image.FigureStyle attribute), 57
padding_bottom (rinoh.index.IndexStyle attribute), 60
padding_bottom (rinoh.inline.InlineFlowableStyle attribute), 68
padding_bottom (rinoh.paragraph.ParagraphStyle attribute), 63
padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 71
padding_bottom (rinoh.structure.AdmonitionStyle attribute), 101
padding_bottom (rinoh.structure.HeadingStyle attribute), 80
padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 103
padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 87
padding_bottom (rinoh.structure.ListStyle attribute), 84
padding_bottom (rinoh.structure.SectionStyle attribute), 77
padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 97
padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 91
padding_bottom (rinoh.table.TableCellStyle attribute), 107
padding_bottom (rinoh.table.TableStyle attribute), 105
padding_left (rinoh.flowable.FloatStyle attribute), 51
padding_left (rinoh.flowable.FlowableStyle attribute), 44
padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 49
padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 46
padding_left (rinoh.image.CaptionStyle attribute), 53
padding_left (rinoh.image.FigureStyle attribute), 57
padding_left (rinoh.index.IndexStyle attribute), 60
padding_left (rinoh.inline.InlineFlowableStyle attribute), 68
padding_left (rinoh.paragraph.ParagraphStyle attribute), 62
padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 71
padding_left (rinoh.structure.AdmonitionStyle attribute), 100
padding_left (rinoh.structure.HeadingStyle attribute), 80
padding_left (rinoh.structure.HorizontalRuleStyle attribute), 102
padding_left (rinoh.structure.ListItemLabelStyle attribute), 87
padding_left (rinoh.structure.ListStyle attribute), 84
padding_left (rinoh.structure.SectionStyle attribute), 77
padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 96
padding_left (rinoh.structure.TableOfContentsStyle attribute), 91
padding_left (rinoh.table.TableCellStyle attribute), 107

padding_left (rinoh.table.TableStyle attribute), 105
padding_right (rinoh.flowable.FloatStyle attribute), 51
padding_right (rinoh.flowable.FlowableStyle attribute), 44
padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 49
padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 47
padding_right (rinoh.image.CaptionStyle attribute), 53
padding_right (rinoh.image.FigureStyle attribute), 57
padding_right (rinoh.index.IndexStyle attribute), 60
padding_right (rinoh.inline.InlineFlowableStyle attribute), 68
padding_right (rinoh.paragraph.ParagraphStyle attribute), 62
padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 71
padding_right (rinoh.structure.AdmonitionStyle attribute), 100
padding_right (rinoh.structure.HeadingStyle attribute), 80
padding_right (rinoh.structure.HorizontalRuleStyle attribute), 102
padding_right (rinoh.structure.ListItemLabelStyle attribute), 87
padding_right (rinoh.structure.ListStyle attribute), 84
padding_right (rinoh.structure.SectionStyle attribute), 77
padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 96
padding_right (rinoh.structure.TableOfContentsStyle attribute), 91
padding_right (rinoh.table.TableCellStyle attribute), 107
padding_right (rinoh.table.TableStyle attribute), 105
padding_top (rinoh.flowable.FloatStyle attribute), 51
padding_top (rinoh.flowable.FlowableStyle attribute), 44
padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 49
padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 47
padding_top (rinoh.image.CaptionStyle attribute), 54
padding_top (rinoh.image.FigureStyle attribute), 57
padding_top (rinoh.index.IndexStyle attribute), 60
padding_top (rinoh.inline.InlineFlowableStyle attribute), 68
padding_top (rinoh.paragraph.ParagraphStyle attribute), 63
padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 71
padding_top (rinoh.structure.AdmonitionStyle attribute), 100
padding_top (rinoh.structure.HeadingStyle attribute), 80
padding_top (rinoh.structure.HorizontalRuleStyle attribute), 102
padding_top (rinoh.structure.ListItemLabelStyle attribute), 87
padding_top (rinoh.structure.ListStyle attribute), 84
padding_top (rinoh.structure.SectionStyle attribute), 77
padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 96
padding_top (rinoh.structure.TableOfContentsStyle attribute), 91
padding_top (rinoh.table.TableCellStyle attribute), 107
padding_top (rinoh.table.TableStyle attribute), 105
Page (class in rinoh.document), 118
page (rinoh.templates.article.Article attribute), 110
page (rinoh.templates.book.Book attribute), 111
page() (rinoh.document.Page property), 118
page_break (rinoh.flowable.FloatStyle attribute), 52
page_break (rinoh.flowable.FlowableStyle attribute), 45
page_break (rinoh.flowable.GroupedFlowablesStyle attribute), 50
page_break (rinoh.flowable.LabeledFlowableStyle attribute), 47
page_break (rinoh.image.CaptionStyle attribute), 54
page_break (rinoh.image.FigureStyle attribute), 58
page_break (rinoh.index.IndexStyle attribute), 61
page_break (rinoh.inline.InlineFlowableStyle attribute), 69
page_break (rinoh.paragraph.ParagraphStyle attribute), 63
page_break (rinoh.reference.ReferencingParagraphStyle attribute), 72
page_break (rinoh.structure.AdmonitionStyle attribute), 101
page_break (rinoh.structure.HeadingStyle attribute), 81
page_break (rinoh.structure.HorizontalRuleStyle attribute), 103

page_break (rinoh.structure.ListItemLabelStyle attribute), 88
page_break (rinoh.structure.ListStyle attribute), 85
page_break (rinoh.structure.SectionStyle attribute), 78
page_break (rinoh.structure.TableOfContentsEntryStyle attribute), 97
page_break (rinoh.structure.TableOfContentsStyle attribute), 92
page_break (rinoh.table.TableCellStyle attribute), 108
page_break (rinoh.table.TableStyle attribute), 106
page_number_format (rinoh.template.ContentsPartTemplate attribute), 142
page_number_format (rinoh.template.DocumentPartTemplate attribute), 141
page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 142
page_number_format (rinoh.template.TitlePartTemplate attribute), 141
page_orientation (rinoh.template.PageTemplate attribute), 144
page_orientation (rinoh.template.PageTemplateBase attribute), 146
page_orientation (rinoh.template.TitlePageTemplate attribute), 145
page_size (rinoh.template.PageTemplate attribute), 144
page_size (rinoh.template.PageTemplateBase attribute), 146
page_size (rinoh.template.TitlePageTemplate attribute), 145
PageBreak (class in rinoh.flowable), 119
PageOrientation (class in rinoh.document), 118
PageTemplate (class in rinoh.template), 143
PageTemplateBase (class in rinoh.template), 146
PageType (class in rinoh.document), 118
Paper (class in rinoh.paper), 129
Paragraph (class in rinoh.paragraph), 130
ParagraphBase (class in rinoh.paragraph), 129
ParagraphState (class in rinoh.paragraph), 130
ParagraphStyle (class in rinoh.paragraph), 61
parse_string() (rinoh.color.Color class method), 116
ParseError, 115
parts (rinoh.template.DocumentTemplate attribute), 139
parts (rinoh.templates.article.Article attribute), 109
parts (rinoh.templates.book.Book attribute), 110
PartsList (class in rinoh.template), 140
PATH, 11
PERCENT (in module rinoh.dimension), 117
PICA (in module rinoh.dimension), 117
PL (in module rinoh.language), 127
place() (rinoh.document.Page method), 118
Polygon (class in rinoh.draw), 118
position (rinoh.image.CaptionStyle attribute), 56
position (rinoh.paragraph.ParagraphStyle attribute), 65
position (rinoh.reference.NoteMarkerStyle attribute), 74
position (rinoh.reference.ReferencingParagraphStyle attribute), 73
position (rinoh.structure.HeadingStyle attribute), 82
position (rinoh.structure.ListItemLabelStyle attribute), 89
position (rinoh.structure.TableOfContentsEntryStyle attribute), 98
position (rinoh.structure.TableOfContentsStyle attribute), 94
position (rinoh.text.TextStyle attribute), 66
prepare() (rinoh.flowable.LabeledFlowable method), 120
prepare() (rinoh.flowable.StaticGroupedFlowables method), 120
prepare() (rinoh.paragraph.ParagraphBase method), 129
prepare() (rinoh.reference.NoteMarkerBase method), 133
prepare() (rinoh.reference.NoteMarkerWithNote method), 134
prepare() (rinoh.reference.RegisterNote method), 133
prepare() (rinoh.structure.Heading method), 134
prepare() (rinoh.table.Table method), 138
prepare() (rinoh.table.TableRow method), 138
prepare() (rinoh.table.TableSection method), 138

prepare() (rinoh.text.MixedStyledText method), 131
ProportionalSpacing (class in rinoh.paragraph), 131
PT (in module rinoh.dimension), 116

Q

QUARTERS (in module rinoh.dimension), 117

R

Rectangle (class in rinoh.draw), 118
Reference (class in rinoh.reference), 133
ReferenceField (class in rinoh.reference), 133
ReferenceText (class in rinoh.reference), 133
ReferenceType (class in rinoh.reference), 133
ReferencingParagraph (class in rinoh.reference), 133
ReferencingParagraphStyle (class in rinoh.reference), 69
RegisterNote (class in rinoh.reference), 133
render() (rinoh.document.Document method), 117
render() (rinoh.document.Page method), 118
render() (rinoh.flowable.GroupedFlowables method), 120
render() (rinoh.flowable.GroupedLabeledFlowables method), 121
render() (rinoh.flowable.LabeledFlowable method), 120
render() (rinoh.paragraph.ParagraphBase method), 129
render() (rinoh.structure.HorizontalRule method), 136
render() (rinoh.table.Table method), 138
repeat_head (rinoh.table.TableStyle attribute), 104
rgba() (rinoh.color.Color property), 116
right_margin (rinoh.template.PageTemplate attribute), 144
right_margin (rinoh.template.PageTemplateBase attribute), 146
right_margin (rinoh.template.TitlePageTemplate attribute), 145
rinoh command line option

- docs, 32
- format <format>, 31
- help, 31
- install-resources, 31
- list-fonts <filename>, 32
- list-formats, 32
- list-options <frontend>, 32
- list-stylesheets, 31
- list-templates, 31
- option <option=value>, 31
- output <filename or directory>, 31
- paper <paper>, 31
- stylesheet <name or filename>, 31
- template <name or filename>, 31
- version, 32
- f <format>, 31
- h, 31
- i, 31
- O <filename or directory>, 31
- o <option=value>, 31
- p <paper>, 31
- s <name or filename>, 31
- t <name or filename>, 31
- input, 31

rinoh.attribute

- module, 115

rinoh.color

```
    module, 115
rinoh.dimension
    module, 116
rinoh.document
    module, 117
rinoh.draw
    module, 118
rinoh.flowable
    module, 119
rinoh.font
    module, 121
rinoh.font.style
    module, 123
rinoh.image
    module, 123
rinoh.index
    module, 124
rinoh.inline
    module, 131
rinoh.language
    module, 125
rinoh.number
    module, 128
rinoh.paper
    module, 129
rinoh.paragraph
    module, 129
rinoh.reference
    module, 133
rinoh.strings
    module, 136
rinoh.structure
    module, 134
rinoh.style
    module, 136
rinoh.stylesheets
    module, 34
rinoh.table
    module, 138
rinoh.template
    module, 139
rinoh.templates.article
    module, 109
rinoh.templates.book
    module, 110
rinoh.text
    module, 130
rinoh_documents
    Sphinx builder configuration value, 32
rinoh_domain_indices
    Sphinx builder configuration value, 33
rinoh_logo
    Sphinx builder configuration value, 33
rinoh_metadata
    Sphinx builder configuration value, 33
rinoh_paper_size
    Sphinx builder configuration value, 33
rinoh_stylesheet
```

Sphinx builder configuration value, 33
rinoh_template
 Sphinx builder configuration value, 33
root() (rinoh.attribute.RuleSetFile property), 115
rotate (rinoh.image.ImageArgs attribute), 124
RuleSet (class in rinoh.attribute), 115
RuleSetFile (class in rinoh.attribute), 115

S

Scale (class in rinoh.image), 124
scale (rinoh.image.ImageArgs attribute), 124
script_level() (rinoh.text.StyledText method), 130
Section (class in rinoh.structure), 134
SectionStyle (class in rinoh.structure), 76
SectionTitles (class in rinoh.structure), 134
seealso (rinoh.structure.AdmonitionTitles attribute), 136
SetMetadataFlowable (class in rinoh.flowable), 119
Shape (class in rinoh.draw), 118
ShapeStyle (class in rinoh.draw), 43
show_author (rinoh.template.TitlePageTemplate attribute), 145
show_date (rinoh.template.TitlePageTemplate attribute), 145
show_in_toc (rinoh.structure.SectionStyle attribute), 76
SINGLE (in module rinoh.paragraph), 132
SingleStyledText (class in rinoh.text), 130
space_above (rinoh.flowable.FloatStyle attribute), 50
space_above (rinoh.flowable.FlowableStyle attribute), 44
space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 48
space_above (rinoh.flowable.LabeledFlowableStyle attribute), 46
space_above (rinoh.image.CaptionStyle attribute), 53
space_above (rinoh.image.FigureStyle attribute), 57
space_above (rinoh.index.IndexStyle attribute), 59
space_above (rinoh.inline.InlineFlowableStyle attribute), 67
space_above (rinoh.paragraph.ParagraphStyle attribute), 62
space_above (rinoh.reference.ReferencingParagraphStyle attribute), 70
space_above (rinoh.structure.AdmonitionStyle attribute), 100
space_above (rinoh.structure.HeadingStyle attribute), 79
space_above (rinoh.structure.HorizontalRuleStyle attribute), 102
space_above (rinoh.structure.ListItemLabelStyle attribute), 86
space_above (rinoh.structure.ListStyle attribute), 83
space_above (rinoh.structure.SectionStyle attribute), 76
space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 96
space_above (rinoh.structure.TableOfContentsStyle attribute), 90
space_above (rinoh.table.TableCellStyle attribute), 106
space_above (rinoh.table.TableStyle attribute), 104
space_below (rinoh.flowable.FloatStyle attribute), 50
space_below (rinoh.flowable.FlowableStyle attribute), 44
space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 48
space_below (rinoh.flowable.LabeledFlowableStyle attribute), 46
space_below (rinoh.image.CaptionStyle attribute), 53
space_below (rinoh.image.FigureStyle attribute), 57
space_below (rinoh.index.IndexStyle attribute), 59
space_below (rinoh.inline.InlineFlowableStyle attribute), 67
space_below (rinoh.paragraph.ParagraphStyle attribute), 62
space_below (rinoh.reference.ReferencingParagraphStyle attribute), 70
space_below (rinoh.structure.AdmonitionStyle attribute), 100
space_below (rinoh.structure.HeadingStyle attribute), 79
space_below (rinoh.structure.HorizontalRuleStyle attribute), 102

space_below (rinoh.structure.ListItemLabelStyle attribute), 86
space_below (rinoh.structure.ListStyle attribute), 83
space_below (rinoh.structure.SectionStyle attribute), 76
space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 96
space_below (rinoh.structure.TableOfContentsStyle attribute), 90
space_below (rinoh.table.TableCellStyle attribute), 107
space_below (rinoh.table.TableStyle attribute), 104
sphinx (in module rinoh.stylesheets), 34
Sphinx builder configuration value
 rinoh_documents, 32
 rinoh_domain_indices, 33
 rinoh_logo, 33
 rinoh_metadata, 33
 rinoh_paper_size, 33
 rinoh_stylesheet, 33
 rinoh_template, 33
sphinx_article (in module rinoh.stylesheets), 34
sphinx_base14 (in module rinoh.stylesheets), 34
split_minimum_rows (rinoh.table.TableStyle attribute), 104
STANDARD (in module rinoh.paragraph), 132
StaticGroupedFlowables (class in rinoh.flowable), 120
String (class in rinoh.strings), 136
StringCollection (class in rinoh.strings), 136
StringField (class in rinoh.strings), 136
Strings (class in rinoh.strings), 136
strings (rinoh.template.DocumentTemplate attribute), 139
strings (rinoh.templates.article.Article attribute), 109
strings (rinoh.templates.book.Book attribute), 111
Stroke (class in rinoh.draw), 118
stroke (rinoh.draw.LineStyle attribute), 43
stroke (rinoh.draw.ShapeStyle attribute), 43
stroke (rinoh.structure.HorizontalRuleStyle attribute), 103
stroke (rinoh.table.TableCellBackgroundStyle attribute), 109
stroke (rinoh.table.TableCellBorderStyle attribute), 108
Style (class in rinoh.style), 137
style log, 27
style_class (rinoh.draw.Line attribute), 118
style_class (rinoh.draw.Shape attribute), 118
style_class (rinoh.flowable.GroupedFlowables attribute), 120
style_class (rinoh.flowable.LabeledFlowable attribute), 120
style_class (rinoh.image.Caption attribute), 124
style_class (rinoh.image.Figure attribute), 124
style_class (rinoh.index.Index attribute), 125
style_class (rinoh.inline.InlineFlowable attribute), 131
style_class (rinoh.paragraph.ParagraphBase attribute), 129
style_class (rinoh.reference.NoteMarkerBase attribute), 133
style_class (rinoh.reference.ReferencingParagraph attribute), 133
style_class (rinoh.structure.Admonition attribute), 135
style_class (rinoh.structure.Heading attribute), 134
style_class (rinoh.structure.HorizontalRule attribute), 136
style_class (rinoh.structure.List attribute), 135
style_class (rinoh.structure.TableOfContents attribute), 135
style_class (rinoh.structure.TableOfContentsEntry attribute), 135
style_class (rinoh.style.Styled attribute), 137
style_class (rinoh.table.Table attribute), 138
style_class (rinoh.table.TableCell attribute), 138
style_class (rinoh.table.TableCellBackground attribute), 139
style_class (rinoh.table.TableCellBorder attribute), 139

style_class (rinoh.table.TableWithCaption attribute), 138
style_class (rinoh.text.StyledText attribute), 130
Styled (class in rinoh.style), 136
StyledMatcher (class in rinoh.style), 138
StyledText (class in rinoh.text), 130
StyleSheet (class in rinoh.style), 137
stylesheet (rinoh.template.DocumentTemplate attribute), 139
stylesheet (rinoh.templates.article.Article attribute), 109
stylesheet (rinoh.templates.book.Book attribute), 110
StyleSheetFile (class in rinoh.style), 137

T

tab_stops (rinoh.image.CaptionStyle attribute), 52
tab_stops (rinoh.paragraph.ParagraphStyle attribute), 61
tab_stops (rinoh.reference.ReferencingParagraphStyle attribute), 70
tab_stops (rinoh.structure.HeadingStyle attribute), 79
tab_stops (rinoh.structure.ListItemLabelStyle attribute), 86
tab_stops (rinoh.structure.TableOfContentsEntryStyle attribute), 95
tab_stops (rinoh.structure.TableOfContentsStyle attribute), 92
TabAlign (class in rinoh.paragraph), 132
Table (class in rinoh.table), 138
table_of_contents (rinoh.templates.article.Article attribute), 109
TableBody (class in rinoh.table), 138
TableCell (class in rinoh.table), 138
TableCellBackground (class in rinoh.table), 139
TableCellBackgroundColor (class in rinoh.table), 108
TableCellBorder (class in rinoh.table), 139
TableCellBorderStyle (class in rinoh.table), 108
TableCellStyle (class in rinoh.table), 106
TableHead (class in rinoh.table), 138
TableOfContents (class in rinoh.structure), 135
TableOfContentsEntry (class in rinoh.structure), 135
TableOfContentsEntryStyle (class in rinoh.structure), 95
TableOfContentsSection (class in rinoh.structure), 135
TableOfContentsStyle (class in rinoh.structure), 90
TableRow (class in rinoh.table), 138
TableSection (class in rinoh.table), 138
TableStyle (class in rinoh.table), 104
TableWithCaption (class in rinoh.table), 138
TABLOID (in module rinoh.paper), 129
TabStop (class in rinoh.paragraph), 132
TabStopList (class in rinoh.paragraph), 133
target_has_class() (rinoh.reference.ReferencingParagraph method), 133
target_has_classes() (rinoh.reference.ReferencingParagraph method), 133
target_style() (rinoh.reference.ReferencingParagraph method), 133
template (rinoh.template.TemplateConfiguration attribute), 140
TemplateConfiguration (class in rinoh.template), 140
text (rinoh.reference.ReferencingParagraphStyle attribute), 69
text (rinoh.structure.TableOfContentsEntryStyle attribute), 95
text_align (rinoh.image.CaptionStyle attribute), 52
text_align (rinoh.paragraph.ParagraphStyle attribute), 61
text_align (rinoh.reference.ReferencingParagraphStyle attribute), 70
text_align (rinoh.structure.HeadingStyle attribute), 78
text_align (rinoh.structure.ListItemLabelStyle attribute), 86
text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 95
text_align (rinoh.structure.TableOfContentsStyle attribute), 92
TextAlign (class in rinoh.paragraph), 131

TextPosition (class in rinoh.font.style), 123
TextStyle (class in rinoh.text), 65
tip (rinoh.structure.AdmonitionTitles attribute), 135
title (rinoh.flowable.GroupedFlowablesStyle attribute), 48
title (rinoh.image.FigureStyle attribute), 58
title (rinoh.index.IndexStyle attribute), 59
title (rinoh.structure.AdmonitionStyle attribute), 99
title (rinoh.structure.ListStyle attribute), 83
title (rinoh.structure.SectionStyle attribute), 76
title (rinoh.structure.TableOfContentsStyle attribute), 90
title (rinoh.table.TableCellStyle attribute), 106
title (rinoh.templates.article.Article attribute), 109
title (rinoh.templates.book.Book attribute), 111
title_page (rinoh.templates.article.Article attribute), 110
title_page (rinoh.templates.book.Book attribute), 112
TitlePageTemplate (class in rinoh.template), 145
TitlePartTemplate (class in rinoh.template), 141
to_string() (rinoh.index.InlineIndexTarget method), 125
to_string() (rinoh.text.StyledText method), 130
top_margin (rinoh.template.PageTemplate attribute), 144
top_margin (rinoh.template.PageTemplateBase attribute), 146
top_margin (rinoh.template.TitlePageTemplate attribute), 145
Typeface (class in rinoh.font), 122
typeface (rinoh.image.CaptionStyle attribute), 55
typeface (rinoh.paragraph.ParagraphStyle attribute), 64
typeface (rinoh.reference.NoteMarkerStyle attribute), 74
typeface (rinoh.reference.ReferencingParagraphStyle attribute), 72
typeface (rinoh.structure.HeadingStyle attribute), 81
typeface (rinoh.structure.ListItemLabelStyle attribute), 88
typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 98
typeface (rinoh.structure.TableOfContentsStyle attribute), 93
typeface (rinoh.text.TextStyle attribute), 65

U

update() (rinoh.style.StyledMatcher method), 138
UserStrings (class in rinoh.strings), 136

V

vertical_align (rinoh.table.TableCellStyle attribute), 106
VerticalAlign (class in rinoh.table), 139

W

WarnFlowable (class in rinoh.flowable), 119
warning (rinoh.structure.AdmonitionTitles attribute), 136
width (rinoh.flowable.FloatStyle attribute), 50
width (rinoh.flowable.FlowableStyle attribute), 44
width (rinoh.flowable.GroupedFlowablesStyle attribute), 48
width (rinoh.flowable.LabeledFlowableStyle attribute), 46
width (rinoh.image.CaptionStyle attribute), 52
width (rinoh.image.FigureStyle attribute), 56
width (rinoh.image.ImageArgs attribute), 124
width (rinoh.index.IndexStyle attribute), 59
width (rinoh.inline.InlineFlowableStyle attribute), 67
width (rinoh.paragraph.ParagraphStyle attribute), 61
width (rinoh.reference.ReferencingParagraphStyle attribute), 69
width (rinoh.structure.AdmonitionStyle attribute), 99
width (rinoh.structure.HeadingStyle attribute), 78

width (rinoh.structure.HorizontalRuleStyle attribute), 102
width (rinoh.structure.ListItemLabelStyle attribute), 85
width (rinoh.structure.ListStyle attribute), 83
width (rinoh.structure.SectionStyle attribute), 76
width (rinoh.structure.TableOfContentsEntryStyle attribute), 95
width (rinoh.structure.TableOfContentsStyle attribute), 90
width (rinoh.table.TableCellStyle attribute), 106
width (rinoh.table.TableStyle attribute), 104
wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 46

Y

y_offset() (rinoh.text.StyledText method), 130